



US009826986B2

(12) **United States Patent**
Donner et al.

(10) **Patent No.:** **US 9,826,986 B2**

(45) **Date of Patent:** **Nov. 28, 2017**

(54) **SYSTEMS FOR AND METHODS OF PREPARING A SACROILIAC JOINT FOR FUSION**

(58) **Field of Classification Search**
CPC . A61B 17/1659; A61B 17/149; A61B 17/144;
A61B 17/1604; A61B 17/1735;
(Continued)

(71) Applicant: **JCBD, LLC**, Fort Collins, CO (US)

(56) **References Cited**

(72) Inventors: **Edward Jeffrey Donner**, Fort Collins, CO (US); **Christopher Thomas Donner**, Fort Collins, CO (US); **Ryan Lewis**, Waxhaw, NC (US)

U.S. PATENT DOCUMENTS

4,488,542 A 12/1984 Helland
4,569,338 A 2/1986 Edwards
(Continued)

(73) Assignee: **JCBD, LLC**, Fort Collins, CO (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 140 days.

AU 1753200 8/2000
CN 2265765 10/1997
(Continued)

(21) Appl. No.: **14/514,221**

OTHER PUBLICATIONS

(22) Filed: **Oct. 14, 2014**

U.S. Appl. No. 14/447,612, filed Jul. 31, 2014.
(Continued)

(65) **Prior Publication Data**

US 2015/0039037 A1 Feb. 5, 2015

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/447,612, filed on Jul. 31, 2014.
(Continued)

(57) **ABSTRACT**


A surgical preparation tool for preparing a sacroiliac joint for a surgical procedure comprising a trial tool assembly and a cutting tool configured to releasably and slidably couple with the trial tool assembly, wherein the trial tool assembly is configured to guide the cutting tool during distal-proximal translation such that as the cutting tool distally advances relative to an implant trial of the trial tool assembly, at least a portion of a cutting element of the cutting tool extends generally over and perpendicularly outward from a first top surface of a body of the implant trial.

(51) **Int. Cl.**
A61B 17/88 (2006.01)
A61B 17/16 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/1659** (2013.01); **A61B 17/144** (2016.11); **A61B 17/149** (2016.11);
(Continued)

107 Claims, 90 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 61/954,594, filed on Mar. 17, 2014, provisional application No. 61/914,409, filed on Dec. 11, 2013, provisional application No. 61/912,494, filed on Dec. 5, 2013, provisional application No. 61/891,345, filed on Oct. 15, 2013, provisional application No. 61/891,330, filed on Oct. 15, 2013, provisional application No. 61/979,857, filed on Apr. 15, 2014, provisional application No. 61/955,126, filed on Mar. 18, 2014, provisional application No. 61/914,409, filed on Dec. 11, 2013, provisional application No. 61/860,185, filed on Jul. 30, 2013.

(51) **Int. Cl.**

A61B 17/68 (2006.01)
A61B 17/14 (2006.01)
A61B 17/17 (2006.01)
A61B 17/15 (2006.01)
A61B 17/92 (2006.01)
A61F 2/30 (2006.01)

(52) **U.S. Cl.**

CPC *A61B 17/1604* (2013.01); *A61B 17/1735* (2013.01); *A61B 17/1739* (2013.01); *A61B 17/68* (2013.01); *A61B 17/15* (2013.01); *A61B 17/1757* (2013.01); *A61B 2017/922* (2013.01); *A61F 2002/30995* (2013.01)

(58) **Field of Classification Search**

CPC *A61B 17/1739*; *A61B 17/68*; *A61B 17/15*; *A61B 17/1757*; *A61B 2017/922*; *A61F 2002/30995*
 USPC 606/246, 279, 300, 79, 80, 84, 85, 99, 606/100, 104, 86 A
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,590,928 A 5/1986 Hunt et al.
 4,622,959 A 11/1986 Marcus
 4,714,469 A 12/1987 Kenna
 4,773,402 A 9/1988 Asher et al.
 4,794,918 A 1/1989 Wolter
 4,863,476 A 9/1989 Shepperd
 4,881,535 A 11/1989 Sohngen
 4,911,153 A 3/1990 Border
 4,920,958 A 5/1990 Walt et al.
 4,950,270 A 8/1990 Bowman et al.
 5,026,373 A 6/1991 Ray et al.
 5,052,375 A 10/1991 Stark et al.
 5,108,397 A 4/1992 White
 5,112,337 A 5/1992 Paulos et al.
 5,176,681 A 1/1993 Lawes et al.
 5,192,327 A 3/1993 Brantigan
 5,242,444 A 9/1993 MacMillan
 5,282,861 A 2/1994 Kaplan
 5,334,192 A 8/1994 Behrens
 5,334,205 A 8/1994 Cain
 5,336,225 A 8/1994 Zang
 5,368,546 A 11/1994 Stark et al.
 5,368,593 A 11/1994 Stark
 5,437,674 A 8/1995 Worcel et al.
 5,443,509 A 8/1995 Boucher et al.
 5,456,267 A 10/1995 Stark
 5,480,402 A 1/1996 Kim
 5,484,389 A 1/1996 Stark et al.
 5,591,235 A 1/1997 Kuslich
 5,593,407 A 1/1997 Reis
 5,607,424 A 3/1997 Tropicano
 5,609,635 A 3/1997 Michelson

5,609,636 A 3/1997 Kohrs et al.
 5,626,434 A 5/1997 Cook
 5,658,337 A 8/1997 Kohrs et al.
 5,669,909 A 9/1997 Zdeblick et al.
 5,688,284 A 11/1997 Chervitz et al.
 5,743,914 A 4/1998 Skiba
 5,772,594 A 6/1998 Barrick
 5,823,975 A 10/1998 Stark et al.
 5,888,224 A 3/1999 Beckers et al.
 5,891,150 A 4/1999 Chan
 5,919,193 A 7/1999 Slavitt
 5,928,239 A 7/1999 Mirza
 5,929,782 A 7/1999 Stark et al.
 5,993,463 A 11/1999 Truwit
 6,053,916 A 4/2000 Moore
 6,056,749 A 5/2000 Kuslich
 6,063,442 A 5/2000 Cohen et al.
 6,175,758 B1 1/2001 Kambin
 6,184,797 B1 2/2001 Stark et al.
 6,236,891 B1 5/2001 Ingle et al.
 6,241,771 B1 6/2001 Gresser et al.
 6,290,724 B1 9/2001 Marino
 6,296,595 B1 10/2001 Stark et al.
 6,302,885 B1 10/2001 Essiger
 6,322,562 B1 11/2001 Wolter
 6,371,123 B1 4/2002 Stark et al.
 6,413,278 B1 7/2002 Marchosky
 6,432,107 B1 8/2002 Ferree
 6,432,140 B1 8/2002 Lin
 6,515,593 B1 2/2003 Stark et al.
 6,520,990 B1 2/2003 Ray
 6,540,707 B1 4/2003 Stark et al.
 6,547,795 B2 4/2003 Schneiderman
 6,547,823 B2 4/2003 Scarborough et al.
 6,558,423 B1 5/2003 Michelson
 6,565,605 B2 5/2003 Goble et al.
 6,572,622 B1 6/2003 Schäfer et al.
 6,579,318 B2 6/2003 Varga et al.
 6,607,487 B2 8/2003 Chang et al.
 6,635,059 B2 10/2003 Randall et al.
 6,641,614 B1 11/2003 Wagner
 6,660,224 B2 12/2003 Lefebvre et al.
 6,663,669 B1 12/2003 Reiley
 6,669,698 B1 12/2003 Tromanhauser et al.
 6,682,563 B2 1/2004 Scharf
 6,682,567 B1 1/2004 Schroeder
 6,716,245 B2 4/2004 Pasquet et al.
 6,723,099 B1 4/2004 Goshert
 6,743,256 B2 6/2004 Mason
 6,746,451 B2 6/2004 Middleton et al.
 6,824,564 B2 11/2004 Crozet
 6,827,670 B1 12/2004 Stark et al.
 6,835,208 B2 12/2004 Marchosky
 6,855,166 B2 2/2005 Kohrs
 6,855,167 B2 2/2005 Shimp et al.
 6,860,902 B2 3/2005 Reiley
 6,872,187 B1 3/2005 Stark et al.
 6,875,236 B2 4/2005 Reiley
 6,902,567 B2 6/2005 Del Medico
 6,908,465 B2 6/2005 von Hoffmann et al.
 6,945,448 B2 9/2005 Medlin et al.
 6,972,019 B2 12/2005 Michelson
 6,974,461 B1 12/2005 Wolter
 7,011,660 B2 3/2006 Sherman et al.
 7,087,056 B2 8/2006 Vaughan
 7,087,058 B2 8/2006 Cragg
 7,108,828 B2 9/2006 Lefebvre et al.
 7,144,399 B2 12/2006 Hayes et al.
 7,163,560 B2 1/2007 Mason
 7,192,447 B2 3/2007 Rhoda
 7,201,775 B2 4/2007 Gorensek et al.
 7,208,222 B2 4/2007 Rolfe et al.
 7,217,291 B2 5/2007 Zucherman et al.
 7,229,448 B2 6/2007 Goble et al.
 7,235,101 B2 6/2007 Berry et al.
 7,235,105 B2 6/2007 Jackson
 7,247,157 B2 7/2007 Prager et al.
 7,255,712 B1 8/2007 Steinberg
 7,303,563 B2 12/2007 Poyner et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,331,995 B2	2/2008	Eisermann et al.	D697,209 S	1/2014	Walthall, Jr. et al.
7,396,360 B2	7/2008	Lieberman	8,623,062 B2	1/2014	Kondrashov
7,410,501 B2	8/2008	Michelson	8,778,026 B2	7/2014	Mauldin
7,416,537 B1	8/2008	Stark et al.	8,808,305 B2	8/2014	Kleiner
7,458,991 B2	12/2008	Wang et al.	8,808,336 B2	8/2014	Duggal et al.
7,465,317 B2	12/2008	Malberg et al.	8,808,377 B2	8/2014	Donner
7,520,898 B2	4/2009	Re et al.	8,808,380 B2	8/2014	Fox et al.
7,537,616 B1	5/2009	Branch et al.	8,808,389 B2	8/2014	Reiley
7,575,600 B2	8/2009	Zucherman et al.	8,821,546 B2	9/2014	Vaughan
7,621,939 B2	11/2009	Zucherman et al.	8,840,651 B2	9/2014	Reiley
7,635,447 B2	12/2009	Hamman et al.	8,882,818 B1	11/2014	Vestgaarden
7,637,954 B2	12/2009	Michelson	8,894,708 B2	11/2014	Thalgott et al.
7,641,697 B2	1/2010	Reiley	8,979,928 B2	3/2015	Donner
7,648,509 B2	1/2010	Stark	8,992,579 B1	3/2015	Gustine et al.
7,666,209 B2	2/2010	Zucherman et al.	9,017,407 B2	4/2015	Donner
7,670,383 B1	3/2010	Brown et al.	9,044,321 B2	6/2015	Mauldin
7,704,279 B2	4/2010	Moskowitz et al.	9,060,815 B1	6/2015	Gustine et al.
7,713,290 B2	5/2010	Vaughan	9,186,155 B2	11/2015	Katzman et al.
7,740,795 B2	6/2010	Wang et al.	2001/0005796 A1	6/2001	Zdeblick et al.
7,771,441 B2	8/2010	Cerundolo	2001/0018616 A1	8/2001	Schwab
7,789,895 B2	9/2010	Heinz	2001/0020143 A1	9/2001	Stark et al.
7,794,465 B2	9/2010	Marik et al.	2002/0029784 A1	3/2002	Stark et al.
7,799,081 B2	9/2010	McKinley	2002/0032484 A1	3/2002	Hyde, Jr.
7,819,869 B2	10/2010	Godara et al.	2002/0068941 A1*	6/2002	Hanson A61B 17/1671 606/79
7,824,404 B2	11/2010	Godara et al.	2002/0068977 A1	6/2002	Jackson
7,837,732 B2	11/2010	Zucherman et al.	2002/0082701 A1	6/2002	Zdeblick et al.
7,837,734 B2	11/2010	Zucherman et al.	2002/0087161 A1	7/2002	Randall et al.
7,846,162 B2	12/2010	Nelson et al.	2002/0147461 A1	10/2002	Aldrich et al.
7,850,690 B2	12/2010	Frigg et al.	2002/0147496 A1	10/2002	Belef et al.
7,850,719 B2	12/2010	Gournay et al.	2002/0183846 A1	12/2002	Kuslich et al.
7,850,732 B2	12/2010	Heinz	2003/0114931 A1	6/2003	Lee et al.
7,909,871 B2	3/2011	Abdou	2003/0124486 A1	7/2003	McDevitt
7,918,891 B1	4/2011	Curran et al.	2003/0181981 A1	9/2003	Lemaire
7,922,765 B2	4/2011	Reiley	2003/0208202 A1	11/2003	Falahee
7,963,970 B2	6/2011	Marino et al.	2004/0073216 A1	4/2004	Lieberman
7,972,363 B2	7/2011	Moskowitz et al.	2004/0127988 A1	7/2004	Goble et al.
7,972,382 B2	7/2011	Foley et al.	2004/0162558 A1	8/2004	Hegde et al.
7,985,255 B2	7/2011	Bray et al.	2004/0162616 A1	8/2004	Simonton
8,034,114 B2	10/2011	Reiley	2004/0186482 A1	9/2004	Kolb et al.
8,034,115 B2	10/2011	Reiley	2004/0199256 A1	10/2004	Wang
8,048,164 B2	11/2011	Reiley	2004/0220668 A1	11/2004	Eisermann et al.
8,070,782 B2	12/2011	Mckay	2004/0228901 A1	11/2004	Trieu et al.
8,075,561 B2	12/2011	Wolter	2004/0249675 A1	12/2004	Stark et al.
8,083,796 B1	12/2011	Raiszadeh et al.	2004/0260286 A1	12/2004	Ferree
8,088,163 B1	1/2012	Kleiner	2005/0043660 A1	2/2005	Stark et al.
8,128,666 B2	3/2012	Falahee	2005/0101887 A1	5/2005	Stark et al.
8,162,981 B2	4/2012	Vestgaarden	2005/0113652 A1	5/2005	Stark et al.
8,187,332 B2	5/2012	McLuen	2005/0131539 A1	6/2005	Kohrs
8,202,305 B2	6/2012	Reiley	2005/0149192 A1	7/2005	Zucherman et al.
8,221,428 B2	7/2012	Trieu	2005/0154391 A1	7/2005	Doherty et al.
8,231,661 B2	7/2012	Carls et al.	2005/0203515 A1	9/2005	Doherty et al.
8,308,779 B2	11/2012	Reiley	2005/0216088 A1	9/2005	McKinley et al.
8,308,794 B2	11/2012	Martinson et al.	2005/0240264 A1	10/2005	Tokish, Jr. et al.
8,317,862 B2	11/2012	Troger et al.	2005/0245925 A1	11/2005	Iki et al.
8,343,189 B2	1/2013	Assell et al.	2005/0267482 A1	12/2005	Hyde, Jr.
8,343,219 B2	1/2013	Allain et al.	2005/0273099 A1	12/2005	Baccelli et al.
8,348,950 B2	1/2013	Assell et al.	2006/0054171 A1	3/2006	Dall
8,388,667 B2	3/2013	Reiley	2006/0058876 A1	3/2006	McKinley
8,414,648 B2	4/2013	Reiley	2006/0069438 A1	3/2006	Zucherman et al.
8,425,570 B2	4/2013	Reiley	2006/0085068 A1	4/2006	Barry
8,425,603 B2	4/2013	Reichen et al.	2006/0089716 A1	4/2006	Felix
8,439,925 B2	5/2013	Marino et al.	2006/0095134 A1	5/2006	Trieu et al.
8,444,693 B2	5/2013	Reiley	2006/0129244 A1	6/2006	Ensign
8,454,618 B2	6/2013	Stark	2006/0147332 A1	7/2006	Jones et al.
8,470,004 B2	6/2013	Reiley	2006/0161154 A1	7/2006	McAfee
8,470,037 B2	6/2013	Re et al.	2006/0167547 A1	7/2006	Suddaby
8,480,755 B2	7/2013	Reiley	2006/0229729 A1	10/2006	Gordon
8,491,572 B2	7/2013	Martinson et al.	2007/0027543 A1	2/2007	Gimble et al.
8,491,653 B2	7/2013	Zucherman et al.	2007/0055374 A1	3/2007	Copf, Jr. et al.
8,496,712 B2	7/2013	Reiley	2007/0155588 A1	7/2007	Stark et al.
8,501,690 B2	8/2013	Stark	2007/0156241 A1	7/2007	Reiley et al.
8,518,120 B2	8/2013	Glerum	2007/0162134 A1	7/2007	Marnay et al.
8,551,171 B2	10/2013	Johnson et al.	2007/0179610 A1	8/2007	Biedermann
8,579,912 B2	11/2013	Isaza et al.	2007/0179621 A1	8/2007	McClellan, III et al.
8,585,744 B2	11/2013	Duggal et al.	2007/0198093 A1	8/2007	Brodke et al.
			2007/0225714 A1	9/2007	Gratl
			2007/0239164 A1	10/2007	Prager et al.
			2007/0265621 A1	11/2007	Matthis et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0270879	A1	11/2007	Isaza et al.	2011/0184520	A1	7/2011	Trieu
2007/0270968	A1	11/2007	Baynham	2011/0185306	A1	7/2011	Aravamudan
2007/0276501	A1	11/2007	Betz et al.	2011/0230966	A1	9/2011	Trieu
2007/0293949	A1	12/2007	Salerni et al.	2011/0238181	A1	9/2011	Trieu
2007/0299525	A1	12/2007	Binotto	2011/0264233	A1	10/2011	Song
2008/0021454	A1	1/2008	Chao et al.	2011/0295272	A1	12/2011	Assell et al.
2008/0021455	A1	1/2008	Chao et al.	2012/0010714	A1	1/2012	Moskowitz et al.
2008/0021456	A1	1/2008	Gupta et al.	2012/0022535	A1	1/2012	Mayer et al.
2008/0039843	A1	2/2008	Abdou	2012/0022595	A1	1/2012	Pham et al.
2008/0045968	A1	2/2008	Yu et al.	2012/0029641	A1	2/2012	Curran et al.
2008/0065215	A1	3/2008	Reiley	2012/0032808	A1	2/2012	Cherubini
2008/0133016	A1	6/2008	Heinz	2012/0035729	A1	2/2012	Glerum
2008/0140082	A1	6/2008	Erdem et al.	2012/0083883	A1	4/2012	Ginn
2008/0140207	A1	6/2008	Olmos	2012/0095560	A1	4/2012	Donner
2008/0154314	A1	6/2008	McDevitt	2012/0101582	A1	4/2012	Raiszadeh et al.
2008/0154377	A1	6/2008	Voellmicke	2012/0116454	A1	5/2012	Edidin et al.
2008/0183293	A1	7/2008	Parry et al.	2012/0116806	A1	5/2012	Stark et al.
2008/0228276	A1	9/2008	Mathews et al.	2012/0150300	A1	6/2012	Nihalani
2008/0262621	A1	10/2008	Gorek	2012/0185049	A1	7/2012	Varela
2008/0281425	A1	11/2008	Thalgott et al.	2012/0209388	A1	8/2012	Curran et al.
2008/0288081	A1	11/2008	Scrafton et al.	2012/0215315	A1	8/2012	Hochschuler et al.
2008/0300685	A1	12/2008	Carls et al.	2012/0253398	A1	10/2012	Metcalf et al.
2009/0018660	A1	1/2009	Roush	2012/0259370	A1	10/2012	Vaidya
2009/0024174	A1	1/2009	Stark	2012/0271200	A1	10/2012	Martinson et al.
2009/0024217	A1	1/2009	Levy	2012/0271424	A1	10/2012	Crawford
2009/0043394	A1	2/2009	Zdeblick et al.	2012/0296428	A1	11/2012	Donner
2009/0076553	A1	3/2009	Wolter	2012/0316565	A1	12/2012	Stark
2009/0088849	A1	4/2009	Armstrong et al.	2012/0323285	A1	12/2012	Assell et al.
2009/0105833	A1	4/2009	Hovda et al.	2013/0006361	A1	1/2013	Glerum
2009/0105834	A1	4/2009	Hovda et al.	2013/0018427	A1	1/2013	Pham et al.
2009/0131986	A1	5/2009	Lee et al.	2013/0023994	A1	1/2013	Glerum
2009/0132035	A1	5/2009	Roth et al.	2013/0030456	A1	1/2013	Assell et al.
2009/0149957	A1	6/2009	Burd et al.	2013/0035723	A1	2/2013	Donner
2009/0192621	A1	7/2009	Winslow et al.	2013/0035727	A1	2/2013	Datta
2009/0216238	A1	8/2009	Stark	2013/0053854	A1	2/2013	Schoenefeld et al.
2009/0216276	A1	8/2009	Pasquet	2013/0053902	A1	2/2013	Trudeau
2009/0248163	A1	10/2009	King et al.	2013/0053964	A1	2/2013	Talwar
2009/0259261	A1	10/2009	Reiley	2013/0060337	A1	3/2013	Petersheim et al.
2009/0259316	A1	10/2009	Ginn et al.	2013/0066426	A1	3/2013	Martinson et al.
2009/0287254	A1	11/2009	Nayet et al.	2013/0085535	A1	4/2013	Greenhalgh et al.
2009/0306671	A1	12/2009	McCormack et al.	2013/0090735	A1	4/2013	Mermuys et al.
2010/0057204	A1	3/2010	Kadaba	2013/0116790	A1	5/2013	Seifert
2010/0076443	A1	3/2010	Bertagnoli et al.	2013/0123850	A1	5/2013	Schoenefeld et al.
2010/0094290	A1	4/2010	Vaidya	2013/0123923	A1	5/2013	Pavlov et al.
2010/0100135	A1	4/2010	Phan	2013/0144343	A1	6/2013	Arnett et al.
2010/0106200	A1	4/2010	Stark	2013/0158669	A1	6/2013	Sungarian
2010/0121160	A1	5/2010	Stark et al.	2013/0197590	A1	8/2013	Assell et al.
2010/0137910	A1	6/2010	Cawley et al.	2013/0218215	A1	8/2013	Ginn et al.
2010/0137919	A1	6/2010	Wolter	2013/0226181	A1	8/2013	Assell et al.
2010/0152785	A1	6/2010	Forton et al.	2013/0231746	A1	9/2013	Ginn et al.
2010/0179552	A1	7/2010	Wolter	2013/0245703	A1	9/2013	Warren et al.
2010/0185292	A1	7/2010	Hochschuler	2013/0253650	A1	9/2013	Ashley
2010/0204795	A1	8/2010	Greenhalgh	2013/0282012	A1	10/2013	Stark
2010/0211176	A1	8/2010	Greenhalgh	2013/0295202	A1	11/2013	Stark
2010/0268228	A1	10/2010	Petersen	2013/0297035	A1	11/2013	Reiley
2010/0286779	A1	11/2010	Thibodeau	2014/0012330	A1	1/2014	Johnson, II et al.
2010/0286785	A1	11/2010	Grayson	2014/0012340	A1	1/2014	Beck et al.
2010/0292796	A1	11/2010	Greenhalgh	2014/0031934	A1	1/2014	Trieu
2010/0292800	A1	11/2010	Zubok	2014/0031935	A1	1/2014	Donner et al.
2010/0305702	A1	12/2010	Michelson	2014/0039628	A1	2/2014	DeLurio et al.
2010/0305704	A1	12/2010	Messerli	2014/0046380	A1	2/2014	Asfora
2010/0324607	A1	12/2010	Davis	2014/0074175	A1	3/2014	Ehler et al.
2010/0331981	A1	12/2010	Mohammed	2014/0088707	A1	3/2014	Donner et al.
2011/0034957	A1	2/2011	Biedermann	2014/0100662	A1	4/2014	Patterson et al.
2011/0046737	A1	2/2011	Teisen	2014/0114415	A1	4/2014	Tyber
2011/0071568	A1	3/2011	Ginn et al.	2014/0135850	A1	5/2014	Parent et al.
2011/0071635	A1	3/2011	Zhang et al.	2014/0135927	A1	5/2014	Pavlov et al.
2011/0087294	A1	4/2011	Reiley	2014/0156007	A1	6/2014	Pabst et al.
2011/0093074	A1	4/2011	Glerum et al.	2014/0200618	A1	7/2014	Donner et al.
2011/0098816	A1	4/2011	Jacob et al.	2014/0249581	A1	9/2014	Stachniak
2011/0098817	A1	4/2011	Eckhardt et al.	2014/0257294	A1	9/2014	Gedet et al.
2011/0118796	A1	5/2011	Reiley	2014/0257399	A1	9/2014	Rezach
2011/0172774	A1	7/2011	Varela	2014/0257408	A1	9/2014	Trieu et al.
2011/0184518	A1	7/2011	Trieu	2014/0257411	A1	9/2014	Rezach
2011/0184519	A1	7/2011	Trieu	2014/0257486	A1	9/2014	Alheidt
				2014/0277460	A1	9/2014	Schifano
				2014/0277478	A1	9/2014	Moore
				2014/0277504	A1	9/2014	Forton et al.
				2014/0288601	A1	9/2014	Baynham

(56) **References Cited**

U.S. PATENT DOCUMENTS

2014/0336763 A1 11/2014 Donner et al.
 2014/0336775 A1 11/2014 Reiley
 2014/0343678 A1 11/2014 Suddaby et al.
 2015/0150683 A1 6/2015 Donner et al.
 2015/0182268 A1 7/2015 Donner et al.
 2015/0209087 A1 7/2015 Donner et al.
 2015/0250612 A1 9/2015 Schifano
 2015/0342753 A1 12/2015 Donner et al.
 2016/0157897 A1 6/2016 Vaidya
 2016/0184105 A1 6/2016 Donner et al.
 2016/0278818 A1 9/2016 Donner et al.
 2016/0278819 A1 9/2016 Donner et al.
 2016/0324643 A1 11/2016 Donner et al.
 2017/0135733 A1 5/2017 Donner et al.

FOREIGN PATENT DOCUMENTS

CN 201073333 Y 6/2008
 CN 201139628 10/2008
 CN 201275132 7/2009
 CN 201275133 7/2009
 CN 201275134 7/2009
 CN 202235633 U 5/2012
 DE 102013011322 A1 5/2014
 EP 1663037 B1 6/2006
 JP 2007-275592 10/2007
 KR 10-1037206 5/2011
 RU 2364359 C1 8/2009
 WO WO 93/08745 A1 5/1993
 WO WO 95/23559 9/1995
 WO WO 95/31947 11/1995
 WO WO 98/48717 11/1998
 WO WO 01/30264 A2 5/2001
 WO WO 01/95823 A1 12/2001
 WO WO 02/067759 A2 9/2002
 WO WO 02/085182 A2 10/2002
 WO WO 2006/020463 A1 2/2006
 WO WO 2006/099270 9/2006
 WO WO 2007/022790 A1 3/2007
 WO WO 2007/115295 A2 10/2007
 WO WO 2008/011410 A2 1/2008
 WO WO 2008/088685 A2 7/2008
 WO WO 2008/089537 A1 7/2008
 WO WO 2009/011774 A2 1/2009
 WO WO 2009/029074 A1 3/2009
 WO WO 2009/108318 A2 9/2009
 WO WO 2010/045749 A1 4/2010
 WO WO 2010/065015 A1 6/2010
 WO WO 2010/108166 A1 9/2010
 WO WO 2011014135 A2 2/2011
 WO WO 2011/056690 A2 5/2011
 WO WO 2011/066053 A2 6/2011
 WO WO 2011/087912 A1 7/2011
 WO WO 2011/091349 A2 7/2011
 WO WO 2012/015976 A1 2/2012
 WO WO 2012/174485 A1 12/2012
 WO WO 2013/020123 A2 2/2013
 WO WO 2013/166496 A1 11/2013
 WO WO 2014/055529 A2 4/2014
 WO WO 2014/074853 A1 5/2014

OTHER PUBLICATIONS

U.S. Appl. No. 14/567,956, filed Dec. 11, 2014.
 U.S. Appl. No. 14/660,784, filed Mar. 17, 2015.
 Arman et al. *The Human Sacrum and Safe Approaches for Screw Placement. Journal of Clinical Neuroscience* 2008 Elsevier Inc. ;16(2009):1046-1049.
 Atlihan et al. Anatomy of the Posterior Iliac Crest as a Reference to Sacral Bar Insertion. *Clin Orthop* 2004;418:141-145.
 Baria, Dinah, "Sacroiliac Joint Biomechanics and Effects of Fusion" (2010). Open Access Dissertations. Paper 466. http://scholarlyrepository.miami.edu/oa_dissertations, 179 pages.

Belanger, et al. "Sacroiliac Arthrodesis Using a Posterior Midline Fascial Splitting Approach and Pedicle Screw Instrumentation: A New Technique." *Journal of Spinal Disorders*, vol. 14 No. 2, pp. 118-124, 2001.
 Buchowski, et al. "Functional and Radiographic Outcome of Sacroiliac Arthrodesis for the Disorders of the Sacroiliac Joint." *The Spine Journal*, 5, 2005, pp. 520-528.
 Cecil et al. Projection of the S2 Pedicle Onto the Posterolateral Surface of the Ilium: A Technique for Lag Screw Fixation, Sacral Fractures or Sacroiliac Joint Dislocations. *Spine* 1996;21(7):875-878.
 Chang et al. Low Profile Pelvic Fixation. *Spine* 2009;34(5):436-440.
 Dayer R. et al. Pelvic fixation for neuromuscular scoliosis deformity correction. *Curr Rev Musculoskelet Med* (2012) 5:91-101.
 DePuy Spine. ISOLA® Spinopelvic System, Surgical Technique. c. 2003 DePuy Spine, Inc., 28 pages.
 Ebraheim, et al. "A Posterior Approach for Inspection of Reduction of Sacroiliac Joint Disruption." *Surg. Radiol. Anat.*, 1999, 21(5), pp. 305-307.
 Ebraheim, et al. "Anatomic considerations for Posterior Approach to the Sacroiliac Joint." *Spine*, 21(23), Dec. 1, 1996, pp. 2709-2712.
 Garrido B.J. et al. Navigated placement of iliac bolts: description of a new technique. *The Spine Journal* 11 (2011) 331-335.
 Giannikas, et al. "Sacroiliac Joint Fusion for Chronic Pain: A Simple Technique Avoiding the Use of Metalwork." *Eur. Spine J*, 13, 2004, pp. 253-256.
 Globus Medical. REVERE® ADDITION® Sacroiliac Components, Surgical Technique. c. 2012 Globus Medical, 64 pages.
 Globus Medical. SI-LOK™ Sacroiliac Joint Fixation System, Surgical Technique. c. 2011 Globus Medical, 44 pages.
 LDR. Avenue®L Lateral Lumbar Cage. Sep. 2011, 3 pages.
 LDR. ROI-A™ Anterior Approach Implant. Apr. 2008, 2 pages.
 LDR. Surgical Technique ROI-C™ Anterior Cervical Cage. Apr. 2010, 15 pages.
 Lee et al. Trajectory of Transsacral Iliac Screw for Lumbopelvic Fixation. *J Spinal Disord Tech* 2011;24(3):151-156.
 Lehman, Jr. et al. Advantage of Pedicle Screw Fixation Directed Into the Apex of the Sacral Promontory Over Bicortical Fixation. *Spine* 2002;27(8):806-811.
 Liebergall, Meir (Iri) M.D., *Lumbosacral and Spinopelvic Fixation*, Lippincott-Raven, Philadelphia, PA, 1996, Chap. 48, "Sacroiliac Joint Fusion," pp. 611-618.
 Luk et al. A Stronger Bicortical Sacral Pedicle Screw Fixation Through the S1 Endplate. *Spine* 2005;30(5):525-529.
 Margulies, J.Y. et al., *Movement, Stability & Low Back Pain, The essential role of the pelvis*, Churchill Livingstone, London, 1997, Chapters 44-47, "Surgical Fusion of the Spine to the Sacrum, etc.," pp. 555-593.
 Marotta N. et al. A novel minimally invasive presacral approach and instrumentation technique for anterior L5-S1 intervertebral disectomy and fusion. *Neurosurg Focus*, vol. 20, Jan. 2006, 8 pages.
 Martin et al. Sacropelvic Fixation: Two Case Reports of a New Percutaneous Technique. *Spine* 2011;36(9):E618-21.
 McLauchlan, et al. "Sacral and Iliac Articular Cartilage Thickness and Cellularity: Relationship to Subchondral Bone End-Plate Thickness and Cancellous Bone Density." *Rheumatology* 2002; 41:375-380.
 Mendel et al. The Lateral Sacral Triangle—A Decision Support for Secure Transverse Sacroiliac Screw Insertion. *Injury J. Care Injured* 2010;42(2011):1164-1170.
 O'Brien et al. An Anatomic Study of the S2 Iliac Technique for Lumbopelvic Screw Placement. *Spine* 2009;34(12):E439-E442.
 O'Brien et al. Feasibility of Minimally Invasive Sacropelvic Fixation. *Spine* 2010;35(4):460-464.
 O'Brien et al. Sacropelvic Instrumentation: Anatomic and Biomechanical Zones of Fixation. *Seminars in Spine Surgery* 2004;16(2):76-90.
 Ouellet et al. Surgical Anatomy of the Pelvis, Sacrum, and Lumbar Spine Relevant to Spinal Surgery. *Seminars in Spine Surgery* 2004 Elsevier Inc.;16:91-100.

(56)

References Cited

OTHER PUBLICATIONS

- Pan W. et al. The clinical application of an iliosacral screw fixation guide and its preliminary clinical application. *Orthopaedic Surgery* (2012), vol. 4, No. 1, pp. 55-59.
- Puhakka, et al. "MR Imaging of the Normal Sacroiliac Joint with Correlation to Histology." *Skeletal Radiol.*, 33, 2004, pp. 15-28.
- SI-BONE iFuse Implant System, Surgical Technique Manual. c. 2011 SI-BONE, Inc., 35 pages.
- SI-BONE iFuse Implant System™. SI-BONE, Inc. 2010, 4 pages.
- Signus Medizintechnik GmbH. DIANA Operationstechnik. Rev. 2010-05/01, 20 pages.
- Sponseller P.D. et al. Low profile pelvic fixation with the sacral alar iliac technique in the pediatric population improves results at two-year minimum follow-up. *Spine* vol. 35, No. 20, pp. 1887-1892.
- Stark J. G. et al. The history of sacroiliac joint arthrodesis: a critical review and introduction of a new technique. *Current Orthopaedic Practice*, vol. 22, No. 6, Nov./Dec. 2011, pp. 545-557.
- Stark. "The Diagnosis and Treatment of Sacroiliac Joint Abnormalities." *Current Orthopaedic Practice*, 21(4), Jul./Aug. 2010, pp. 336-347.
- Synthes Spine. ProDisc-C Total Disc Replacement. Product Information. © 2008 Synthes, Inc., 14 pages.
- Synthes Spine. SynFix-LR System. Instruments and implants for stand-alone anterior lumbar interbody fusion (ALIF). Technique Guide. © 2008 Synthes, Inc., 45 pages.
- Synthes Spine. Universal Spinal System (USS) Polyaxial and Iliosacral Spine Fixation. A versatile system for posterior stabilization of spinal segments. Technique Guide, c. 2009 Synthes, Inc., 61 pages.
- Szadek, et al. "Possible Nociceptive Structures in the Sacroiliac Joint Cartilage: An Immunohistochemical Study." *Clinical Anatomy*, 23, 2010, pp. 192-198.
- Tenon Medical, *Catamaran SI Joint Implant*, <http://tctig.com/projects> (last visited Nov. 19, 2014).
- tifix® Technology Pressure Plate Technology: Multidirectional Locking Technology Titanium Plate and Screw Systems, General & Specific Instructions. litos/GmbH & CO. KG, Rev: Sep. 9, 2008.
- Tobler W.D. et al. The presacral retroperitoneal approach for axial lumbar interbody fusion. *J Bone Joint Surg [Br]*, vol. 93-B, No. 7, Jul. 2011, pp. 955-960.
- Ugur, et al. "New Needle Holder Facilitates Percutaneous Fluoroscopy-Guided Sacroiliac Puncture." *Acta Radiologica*, 2006, 47(5), pp. 481-483.
- Vanelderen, et al. "Evidence-Based Medicine. Evidence-Based Interventional Pain Medicine According to Clinical Diagnoses. 13. Sacroiliac Joint Pain." *Pain Practice*, 10(5), 2010, pp. 470-478.
- Waisbrod, et al. "Sacroiliac Joint Arthrodesis for Chronic Lower Back Pain." *Arch. Orthop. Trauma Surg.*, 106, 1987, pp. 238-240.
- Wise, et al. "Minimally Invasive Sacroiliac Arthrodesis. Outcomes of a New Technique." *Spinal Disord. Tech.*, 21(8), Dec. 2008, pp. 579-584.
- Yin, et al. "Sensory Stimulation-Guided Sacroiliac Joint Radiofrequency Neurotomy: Technique Based on Neuroanatomy of the Dorsal Sacral Plexus." *Spine*, 28(20), pp. 2419-2425.
- Zyga Technology, Inc. *Slmmetry Sacroiliac Joint Fusion System*, Surgeon Didactic, c. 2012 Zyga Technology, Inc., 45 pages.
- Zyga Technology, Inc. *Slmmetry Sacroiliac Joint Fusion System*, Technique Guide, known at least as early as Mar. 1, 2013, 20 pages.
- Advisory Action, U.S. Appl. No. 12/998,712, dated Jan. 28, 2014, 4 pages.
- Advisory Action, U.S. Appl. No. 13/135,381, mailed Jul. 23, 2013, 3 pages.
- Appeal Brief, U.S. Appl. No. 13/135,381, dated Dec. 23, 2013, 20 pages.
- European Search Report, EP Appl. No. 11733183.5, dated Dec. 18, 2013, 4 pages.
- European Search Report, EP Appl. No. 12799773.2, dated Oct. 29, 2014.
- Examination Report, SG Application No. 201205104-1, dated Jul. 17, 2014, Intellectual Property Office of Singapore.
- Final Rejection, U.S. Appl. No. 12/998,712, mailed Nov. 7, 2013, 24 pages.
- Final Rejection, U.S. Appl. No. 13/135,381, mailed May 9, 2013, 14 pages.
- Final Rejection, U.S. Appl. No. 13/236,411, dated Jan. 2, 2015.
- International Search Report and Written Opinion, PCT application No. PCT/US2012/042823, dated Nov. 5, 2012, 16 pages.
- International Search Report and Written Opinion, PCT Application No. PCT/US2012/055892, dated Mar. 25, 2013, 22 pages.
- International Search Report and Written Opinion, PCT application No. PCT/US2011/000070, dated Mar. 21, 2011, 13 pages.
- International Search Report and Written Opinion, PCT Application No. PCT/US2013/051381, dated Apr. 11, 2013, 16 pages.
- International Search Report and Written Opinion, PCT/US2014/030889, dated Jul. 16, 2014.
- International Search Report and Written Opinion, PCT/US2014/048990, dated Nov. 18, 2014.
- Japanese Office Action, JP2012-548960, dated Oct. 7, 2014.
- Non-Final Office Action, U.S. Appl. No. 12/998,712, mailed May 31, 2013, 44 pages.
- Non-Final Office Action, U.S. Appl. No. 12/998,712, dated Aug. 1, 2014.
- Non-Final Office Action, U.S. Appl. No. 13/135,381, mailed Nov. 5, 2012, 19 pages.
- Non-Final Office Action, U.S. Appl. No. 13/236,411, dated Apr. 11, 2014.
- Notice of Allowance, U.S. Appl. No. 13/236,411, dated Mar. 16, 2015.
- Notice of Allowance, U.S. Appl. No. 12/998,712, dated Dec. 23, 2014.
- Notice of Allowance, U.S. Appl. No. 13/135,381, dated Apr. 17, 2014.
- Response to Advisory Action, U.S. Appl. No. 13/135,381, filed Aug. 20, 2013, 12 pages.
- Response to Final Office Action, U.S. Appl. No. 13/236,411, dated Mar. 4, 2015.
- Response to Final Office Action, U.S. Appl. No. 12/998,712, dated Jan. 7, 2014, 16 pages.
- Response to Final Office Action, U.S. Appl. No. 13/135,381, filed Jul. 9, 2013, 11 pages.
- Response to Non-Final Office Action, U.S. Appl. No. 13/135,381, filed Feb. 4, 2013, 7 pages.
- Response to Non-Final Office Action, U.S. Appl. No. 12/998,712, filed Aug. 28, 2013, 17 pages.
- Response to Non-Final Office Action, U.S. Appl. No. 12/998,712, dated Sep. 4, 2014.
- Response to Non-Final Office Action, U.S. Appl. No. 13/236,411, dated Sep. 11, 2014.
- Response to Restriction, U.S. Appl. No. 13/236,411, filed Jun. 10, 2013, 13 pages.
- Response to Restriction, U.S. Appl. No. 13/236,411, filed Nov. 12, 2013, 14 pages.
- Response to Restriction, U.S. Appl. No. 13/945,053, dated Nov. 19, 2014.
- Restriction Requirement, U.S. Appl. No. 13/236,411, mailed May 10, 2013, 5 pages.
- Restriction Requirement, U.S. Appl. No. 13/236,411, mailed Oct. 16, 2013, 7 pages.
- Restriction Requirement, U.S. Appl. No. 13/945,053, dated Sep. 25, 2014.
- Singapore Search Report and Written Opinion, SG Appl. No. 201205104-1, dated Oct. 31, 2013, 29 pages.
- Supplemental Amendment, U.S. Appl. No. 12/998,712, dated Apr. 14, 2014, 14 pages.
- Australian Examination Report, AU2014204494, dated May 15, 2015.
- Chinese Office Action, CN201180001537.4, dated Mar. 19, 2015.
- Dall et al., *Surgery for the Painful, Dysfunctional Sacroiliac Joint*, Springer International Publishing, Switzerland, 2015.
- Non-Final Office Action, U.S. Appl. No. 13/945,053, dated Apr. 3, 2015.

(56)

References Cited

OTHER PUBLICATIONS

Restriction Requirement, U.S. Appl. No. 13/475,695, dated Mar. 30, 2015.

Medtronic Sofamor Danek. Colorado 2™ Sacro-Iliac Fixation, Surgical Technique. © 2003 Medtronic Sofamor Danek USA, Inc.

Medtronic Sofamor Danek. Colorado 2™ The New Revolution, Surgical Technique. © 2000 Medtronic Sofamor Danek, Inc.

Moshirfar et al. Pelvic Fixation in Spine Surgery. *The Journal of Bone & Joint Surgery* 2005;87-A(2 Suppl):89-106.

Synthes GmbH. Sacral Bars. Fixation of the posterior pelvis in cases of fractures or sacroiliac joint dislocations. © Apr. 2009 Synthes, Inc.

Amendment Under 1.312, U.S. Appl. No. 13/946,790, dated Dec. 14, 2015.

EP Examination Report, EP11733183.5, dated Sep. 9, 2015.

European Search Report, EP12834000.7, dated Jul. 13, 2015.

Final Rejection, U.S. Appl. No. 13/945,053, dated Dec. 22, 2015.

Japanese Office Action, JP2015-042238, dated Dec. 22, 2015.

Non-Final Office Action, U.S. Appl. No. 13/475,695, dated Jul. 30, 2015.

Notice of Allowance, U.S. Appl. No. 13/946,790, dated Nov. 20, 2015.

Response to Non-Final Office Action, U.S. Appl. No. 13/475,695, dated Oct. 30, 2015.

Response to Non-Final Office Action, U.S. Appl. No. 13/945,053, dated Aug. 31, 2015.

Response to Restriction, U.S. Appl. No. 13/946,790, dated Sep. 14, 2015.

Response to Restriction, U.S. Appl. No. 13/475,695, dated Jun. 30, 2015.

Response to Restriction, U.S. Appl. No. 14/216,975, dated Jan. 22, 2016.

Response to Restriction, U.S. Appl. No. 14/567,956, dated Jan. 19, 2016.

Restriction Requirement, U.S. Appl. No. 13/946,790, dated Jul. 14, 2015.

Restriction Requirement, U.S. Appl. No. 14/216,975, dated Oct. 23, 2015.

Restriction Requirement, U.S. Appl. No. 14/567,956, dated Nov. 20, 2015.

Taiwan Examination Report, TW100114376, dated Oct. 5, 2015.

Amendment and Response to Restriction, U.S. Appl. No. 14/447,612, dated Sep. 2, 2016.

Amendment Under 1.312, U.S. Appl. No. 13/475,695, dated Mar. 25, 2016.

Amendment Under 1.312, U.S. Appl. No. 13/945,053, dated May 19, 2016.

AU Patent Examination Report No. 1, AU2012312658, dated Jul. 18, 2016.

Non-Final Office Action, U.S. Appl. No. 14/127,119, dated Sep. 8, 2016.

Non-Final Office Action, U.S. Appl. No. 14/216,975, dated Jun. 20, 2016.

Non-Final Office Action, U.S. Appl. No. 14/413,318, dated May 3, 2016.

Non-Final Office Action, U.S. Appl. No. 14/567,956, dated Feb. 12, 2016.

Non-Final Office Action, U.S. Appl. No. 14/681,882, dated Oct. 6, 2016.

Notice of Allowance, U.S. Appl. No. 13/475,695, dated Feb. 18, 2016.

Notice of Allowance, U.S. Appl. No. 13/945,053, dated Mar. 28, 2016.

Notice of Allowance, U.S. Appl. No. 13/945,053, dated Jul. 5, 2016.

Notice of Allowance, U.S. Appl. No. 13/946,790, dated Feb. 16, 2016.

Notice of Allowance, U.S. Appl. No. 14/413,318, dated Aug. 31, 2016.

Notice of Allowance, U.S. Appl. No. 14/567,956, dated Sep. 13, 2016.

Response to Non-Final Office Action, U.S. Appl. No. 14/413,318, dated Aug. 3, 2016.

Response to Non-Final Office Action, U.S. Appl. No. 14/567,956, dated May 10, 2016.

Response to Restriction, U.S. Appl. No. 14/127,119, dated Jun. 6, 2016.

Response to Restriction, U.S. Appl. No. 14/344,876, dated Aug. 29, 2016.

Response to Restriction, U.S. Appl. No. 14/413,318, dated Apr. 19, 2016.

Restriction Requirement, U.S. Appl. No. 14/127,119, dated Apr. 5, 2016.

Restriction Requirement, U.S. Appl. No. 14/413,318, dated Feb. 19, 2016.

Restriction Requirement, U.S. Appl. No. 14/447,612, dated Jul. 6, 2016.

Canadian Office Action, CA2787152, dated Jan. 25, 2017.

Chinese Office Action, CN201510622898.0, dated Dec. 23, 2016 T.

EP Extended Search Report, EP16191003.9, dated Feb. 6, 2017.

Final Office Action, U.S. Appl. No. 14/216,975, dated Dec. 30, 2016.

Non-Final Office Action, U.S. Appl. No. 14/447,612, dated Dec. 15, 2016.

Notice of Allowance, U.S. Appl. No. 14/447,612, dated Feb. 28, 2017.

Response to Final Office Action, U.S. Appl. No. 14/216,975, dated Feb. 27, 2017.

Response to Non-Final Office Action, U.S. Appl. No. 14/344,876, dated Mar. 1, 2017.

Response to Non-Final Office Action, U.S. Appl. No. 14/447,612, dated Jan. 25, 2017.

Response to Non-Final Office Action, U.S. Appl. No. 14/681,882, dated Jan. 5, 2017.

Response to Restriction, U.S. Appl. No. 14/723,384, dated Feb. 24, 2017.

Restriction Requirement, U.S. Appl. No. 14/723,384, dated Dec. 29, 2016.

Globus Medical. Secure-C Cervical Artificial Disc. Copyright 2014.

Synthes Spine. ProDisc-L Total Disc Replacement. For replacement of a diseased and/or degenerated intervertebral disc of the lumbosacral regions. Technique Guide. Copyright 2006.

Amendment with RCE, U.S. Appl. No. 14/567,956, dated Dec. 9, 2016.

Non-Final Office Action, U.S. Appl. No. 14/344,876, dated Dec. 1, 2016.

Non-Final Office Action, U.S. Appl. No. 15/178,244, dated May 16, 2017.

Non-Final Office Action, U.S. Appl. No. 15/178,291, dated May 16, 2017.

Notice of Allowance, U.S. Appl. No. 14/127,119, dated Apr. 21, 2017.

Notice of Allowance, U.S. Appl. No. 14/216,975, dated Apr. 5, 2017.

Notice of Allowance, U.S. Appl. No. 14/567,956, dated Mar. 13, 2017.

Notice of Allowance, U.S. Appl. No. 14/681,882, dated May 10, 2017.

Response to Non-Final Office Action, U.S. Appl. No. 14/127,119, dated Dec. 29, 2016.

* cited by examiner





FIG.1
CONVENTIONAL ART






FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8






FIG. 10




FIG. 12




FIG. 11





FIG. 13






FIG. 15A

FIG. 15B




FIG. 15D

FIG. 15C




FIG. 17

FIG. 16





FIG. 18A FIG. 18B

FIG. 18D

FIG. 18C






FIG. 20A

FIG. 20B

FIG. 20C




FIG. 21C

FIG. 21A

FIG. 21B




FIG. 22A

FIG. 22B




FIG. 22C

FIG. 22D





FIG. 22E




FIG. 23A

FIG. 23B




FIG. 23C

FIG. 23D




FIG. 24A




FIG. 24B





FIG. 25






FIG. 26C




FIG. 26D




FIG. 26E




FIG. 26F




FIG. 26G




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31

FIG. 32





FIG. 33






FIG. 34




FIG. 35




FIG. 36A






FIG. 36B






FIG. 36E




FIG. 37




FIG. 38




FIG. 39




FIG. 40C

FIG. 40B

FIG. 40A




FIG. 41




FIG. 42A





FIG. 42B






FIG. 43E




FIG. 43F




FIG. 44




FIG. 45




FIG. 46




FIG. 47A




FIG. 47B




FIG. 48A




FIG. 48B




FIG. 48C




FIG. 49A




FIG. 49B




FIG. 49D

FIG. 49C




FIG. 49E




FIG. 49F




FIG. 49G




FIG. 49H




FIG. 49I






FIG. 49J






FIG. 49M




FIG. 49N




FIG. 490




FIG. 49P




FIG. 49Q




FIG. 49R




FIG. 50A




FIG. 50B




FIG. 50C




FIG. 50D




FIG. 50E




FIG. 50F




FIG. 51A




FIG. 51B




FIG. 51C




FIG. 51D




FIG. 51E




FIG. 52A




FIG. 52B




FIG. 53A




FIG. 53C




FIG. 53D




FIG. 54D 9034




FIG. 54E




FIG. 54B




FIG. 54C







FIG. 55A





1

SYSTEMS FOR AND METHODS OF PREPARING A SACROILIAC JOINT FOR FUSION

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority under 35 U.S.C. §119 to U.S. Provisional Patent Application 61/891,330, which was filed Oct. 15, 2013, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT,” and is hereby incorporated by reference in its entirety into the present application.

The present application also claims priority under 35 U.S.C. §119 to U.S. Provisional Patent Application 61/891,345, which was filed Oct. 15, 2013, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT,” and is hereby incorporated by reference in its entirety into the present application.

The present application also claims priority under 35 U.S.C. §119 to U.S. Provisional Patent Application 61/912,494, which was filed Dec. 5, 2013, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT,” and is hereby incorporated by reference in its entirety into the present application.

The present application also claims priority under 35 U.S.C. §119 to U.S. Provisional Patent Application 61/914,409, which was filed Dec. 11, 2013, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT,” and is hereby incorporated by reference in its entirety into the present application.

The present application also claims priority under 35 U.S.C. §119 to U.S. Provisional Patent Application 61/954,594, which was filed Mar. 17, 2014, entitled “SYSTEMS AND METHODS FOR FUSING A SACROILIAC JOINT AND ANCHORING AN ORTHOPEDIC APPLIANCE,” and is hereby incorporated by reference in its entirety into the present application.

The present application is also a continuation-in-part (“CIP”) application of, and claims priority to, U.S. patent application Ser. No. 14/447,612 (“the ‘612 application”), which was filed Jul. 31, 2014, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT.” The ‘612 application claims priority under 35 U.S.C. §119 to: 1) U.S. Provisional Patent Application 61/979,857, which was filed Apr. 15, 2014, entitled “SACROILIAC JOINT IMPLANT”; 2) U.S. provisional application 61/955,126, which was filed Mar. 18, 2014, entitled “SACROILIAC JOINT IMPLANT”; 3) U.S. Provisional Patent Application 61/914,409, which was filed Dec. 11, 2013, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT”; and 4) U.S. Provisional Patent Application 61/860,185, which was filed Jul. 30, 2013, entitled “SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT”. The ‘612 application and all Provisional patent application’s in which it claims priority to are hereby incorporated by reference in their entireties into the present application.

TECHNICAL FIELD

Aspects of the present disclosure relate to medical apparatus and methods. More specifically, the present disclosure relates to devices and methods for preparing a sacroiliac joint for fusion.

BACKGROUND

The sacroiliac joint is the joint between the sacrum and the ilium of the pelvis, which are joined by ligaments. In

2

humans, the sacrum supports the spine and is supported in turn by an ilium on each side. The sacroiliac joint is a synovial joint with articular cartilage and irregular elevations and depressions that produce interlocking of the two bones.

Pain associated with the sacroiliac joint can be caused by traumatic fracture dislocation of the pelvis, degenerative arthritis, sacroiliitis an inflammation or degenerative condition of the sacroiliac joint, osteitis condensans ilii, or other degenerative conditions of the sacroiliac joint. Currently, sacroiliac joint fusion is most commonly advocated as a surgical treatment for these conditions. Fusion of the sacroiliac joint can be accomplished by several different conventional methods encompassing an anterior approach, a posterior approach, and a lateral approach with or without percutaneous screw or other type implant fixation. However, while each of these methods has been utilized for fixation and fusion of the sacroiliac joint over the past several decades, substantial problems with respect to the fixation and fusion of the sacroiliac joint remain unresolved.

A significant problem with certain conventional methods for fixation and fusion of the sacroiliac joint including the anterior approach, posterior approach, or lateral approach may be that the surgeon has to make a substantial incision in the skin and tissues for direct access to the sacroiliac joint involved. These invasive approaches allow the sacroiliac joint to be seen and touched directly by the surgeon. Often referred to as an “open surgery”, these procedures have the attendant disadvantages of requiring general anesthesia and can involve increased operative time, hospitalization, pain, and recovery time due to the extensive soft tissue damage resulting from the open surgery.

A danger to open surgery using the anterior approach can be damage to the L5 nerve root, which lies approximately two centimeters medial to the sacroiliac joint or damage to the major blood vessels. Additionally and as seen in FIG. 1, which depicts a conventional fusion procedure (immobilization of the articular surfaces of the sacroiliac joint in relation to one another) on a sacroiliac joint 1, one or more screws or implants 2 are implanted transversely across the articular surfaces 3 and through the sacrum 4 and the ilium bones 5. That is, the joint 1 is immobilized by placement of a fusion device 2 transverse to or across a plane defined by articular surfaces 3 of the sacroiliac joint space.

Use of trans-sacroiliac and S1 pedicle-iliac bone implants can also involve the risk of damage to the lumbosacral neurovascular elements. Damage to the lumbosacral neurovascular elements as well as delayed union or non-union of the sacroiliac joint by use of these procedures may require revision surgery to remove all or a portion of the implants or repeat surgery as to these complications.

Another significant problem with conventional procedures utilizing minimally invasive small opening procedures can be that the procedures are technically difficult, requiring biplanar fluoroscopy of the articular surfaces of the sacroiliac joint and extensive surgical training and experience. Despite the level of surgical training and experience, there is a substantial incidence of damage to the lumbosacral neurovascular elements. Additionally, sacral anomalies can further lead to malplacement of implants leading to damage of surrounding structures. Additionally, these procedures are often performed without fusion of the sacroiliac joint, which does not remove the degenerative joint surface and thereby does not address the degenerative condition of the sacroiliac joint, which may lead to continued or recurrent sacroiliac joint pain.

3

Another significant problem with conventional procedures can be the utilization of multiple trans-sacroiliac elongate implants, which do not include a threaded surface. This approach requires the creation of trans-sacroiliac bores in the pelvis and nearby sacral foramen, which can be of relatively large dimension and which are subsequently broached with instruments, which can result in bone being impacted into the pelvis and neuroforamen.

The creation of the trans-sacroiliac bores and subsequent broaching of the bores requires a guide pin, which may be inadvertently advanced into the pelvis or sacral foramen, resulting in damage to other structures. Additionally, producing the trans-sacroiliac bores, broaching, or placement of the elongate implants may result in damage to the lumbosacral neurovascular elements, as above discussed. Additionally, there may be no actual fusion of the articular portion of the sacroiliac joint, which may result in continued or recurrent pain requiring additional surgery.

Another substantial problem with conventional procedures can be that placement of posterior extra-articular distracting fusion implants and bone grafts may be inadequate with respect to removal of the articular surface or preparation of cortical bone, the implant structure and fixation of the sacroiliac joint. The conventional procedures may not remove sufficient amounts of the articular surfaces or cortical surfaces of the sacroiliac joint to relieve pain in the sacroiliac joint. The conventional implant structures may have insufficient or avoid engagement with the articular surfaces or cortical bone of the sacroiliac joint for adequate fixation or fusion. The failure to sufficiently stabilize and fuse the sacroiliac joint with the conventional implant structures and methods may result in a failure to relieve the condition of sacroiliac joint being treated. Additionally, conventional methods of driving apart a sacrum and ilium may lead to mal-alignment of the sacroiliac joint and increased pain.

Improvements to sacroiliac joint fusion involve systems and methods for non-transverse delivery of an implant into the sacroiliac joint are described in U.S. patent application Ser. No. 12/998,712, filed May 23, 2011 entitled SACROILIAC JOINT FIXATION FUSION SYSTEM; Ser. No. 13/236,411, filed Sep. 19, 2011 entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT; and Ser. No. 13/475,695, filed May 18, 2012, entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT; and Ser. No. 13/945,053, filed Jul. 18, 2013, entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT; and Ser. No. 13/946,790, filed Jul. 19, 2013, entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT; and Ser. No. 14/216,975, filed Mar. 17, 2014, entitled SYSTEMS AND METHODS FOR FUSING A SACROILIAC JOINT AND ANCHORING AN ORTHOPEDIC APPLIANCE; and Ser. No. 14/447,612, filed Jul. 31, 2014, entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT. All of application Ser. Nos. 12/998,712, 13/236,411, 13/475,695, 13/945,053, 13/946,790, 14/216,975, and Ser. No. 14/447,612 are herein incorporated by reference in their entirety. In certain instances, it may be desirable to prepare the surfaces of the sacroiliac joint prior to implantation of the fusion device, e.g., the intraarticular or extra-articular surfaces. While surgical preparation tools may exist for procedures in other areas of the body, tools for preparing the sacroiliac joint for fusion are lacking. Thus, the systems and

4

methods discussed herein address the challenges in preparing the sacroiliac joint for fixation and fusion.

SUMMARY

One implementation of the present disclosure may take the form of a surgical preparation tool for preparing a sacroiliac joint having a sacrum and an ilium for a surgical procedure. In one embodiment, the tool may include a trial tool assembly and a cutting tool.

The trial tool assembly may include an implant trial at a distal end of the trial tool assembly and a trial shaft coupled to and extending proximally from the implant trial. The implant trial may include a body comprising a first length extending along a longitudinal axis from a proximal to a distal end, a top surface, a bottom surface generally opposite the top surface, a first side surface, and a second side surface generally opposite the first side surface. The implant trial may be configured to be delivered non-transversely into the sacroiliac joint such that the first top and first bottom surfaces oppose either the sacrum or the ilium.

The cutting tool of the surgical preparation tool may be configured to releasably and slidably couple with the trial tool assembly. The cutting tool may include a first cutting element at a distal end of the cutting tool and a cutting shaft extending proximally from the cutting element. The first cutting element may include a second length extending from a proximal to a distal end. The trial tool assembly is configured to guide the cutting tool during distal-proximal translation such that as the first cutting element distally advances relative to the implant trial, at least a portion of the first cutting element extends generally over and perpendicularly outward from the first side surface of the body of the implant trial.

Another implementation of the present disclosure may take the form of a surgical preparation tool for preparing a sacroiliac joint having a sacrum and an ilium for a surgical procedure. In one embodiment, the tool may include a trial tool assembly and a drill guide assembly.

The trial tool assembly may include an implant trial at a distal end of the trial tool assembly and a trial shaft coupled to and extending proximally from the implant trial. The implant trial may include a body comprising a first length extending along a longitudinal axis from a proximal to a distal end, a first top surface, a first bottom surface generally opposite the first top surface, and a thickness defined between the first top and first bottom surfaces. The implant trial may be configured to be delivered non-transversely into the sacroiliac joint such that the first top and first bottom surfaces oppose either the sacrum or the ilium.

The drill guide assembly may be configured to releasably and slidably couple with the trial tool assembly. The drill guide assembly may include a drill guide at a distal end of the cutting guide and a drill guide shaft extending proximally from the drill guide. The drill guide may include a first passageway that is configured to guide a drill bit during distal-proximal translation of the drill bit relative to the drill guide assembly. The trial tool assembly may be configured to guide the drill guide assembly during distal-proximal translation such that as the drill guide distally advances relative to the implant trial, the drill guide is positioned in an orientation to deliver the drill bit generally over at least a portion of the first top surface of the body of the implant trial.

5

Yet another implementation of the present disclosure may take the form of a method of surgically preparing a sacroiliac joint having a sacrum and an ilium for a surgical fusion procedure.

In one embodiment, the method may include approaching a sacroiliac joint space with a joint preparation tool that may include an implant trial assembly and a cutting tool. The implant trial assembly may include an implant trial at a distal end of the joint preparation tool and an implant trial shaft extending proximally from the implant trial. The implant trial may include a length extending from a proximal end to a distal end of the implant trial, a first top surface, and a first bottom surface generally opposite the first top surface. The cutting tool may be configured to releasably and slidably couple with the trial tool assembly. The cutting tool may include a cutting element at a distal end of the cutting tool and a cutting shaft extending proximally from the cutting element. The cutting element may include a second length extending from a proximal to a distal end, wherein the trial tool assembly is configured to guide the cutting tool during distal-proximal translation.

The method may also include delivering a portion of the implant trial non-transversely into the sacroiliac joint space. The implant trial may be oriented in the sacroiliac joint space such that the first top and bottom surfaces are generally coplanar with a joint plane of the sacroiliac joint space.

The method may further include causing the cutting tool to be distally driven relative to the trial tool assembly such that the cutting element makes a cut extending into the sacrum or the ilium.

Another implementation of the present disclosure may take the form of a surgical system for preparing a sacroiliac joint having a sacrum and an ilium for a surgical procedure. In one embodiment, the system may include a joint preparation tool and a first anchoring arm.

The joint preparation tool may include a rasping head at a distal end of the joint preparation tool, a shaft extending proximally from the rasping head, and a longitudinal axis extending from a proximal to a distal end of the joint preparation tool. The rasping head may include a length extending from a distal to a proximal end of the rasping head, a top surface, and a bottom surface opposite the top surface.

The first anchoring arm may include a proximal end and a distal end, where the distal end of the first anchoring arm may be configured to engage a proximal end of an anchor element, the first anchoring arm may be operably coupled to the joint preparation tool in an arrangement such that a longitudinal axis of the anchor element is generally transversely aligned with the longitudinal axis of the joint preparation tool when the distal end of the first anchoring arm is engaged with the proximal end of the anchor element, wherein the first anchoring arm is configured to deliver the anchor element across the sacroiliac joint according to the arrangement.

Another implementation of the present disclosure may take the form of a surgical preparation tool for preparing a sacroiliac joint having a sacrum and an ilium for a surgical procedure. In one embodiment, the tool may include a trial tool assembly and a cutting tool assembly.

The trial tool assembly may include an implant trial at a distal end of the trial tool assembly and a trial shaft coupled to and extending proximally from the implant trial. The implant trial may include a body comprising a first length extending along a longitudinal axis from a proximal to a distal end, a first top surface, a first bottom surface generally opposite the first top surface, and a thickness defined

6

between the first top and first bottom surfaces. The implant trial may be configured to be delivered non-transversely into the sacroiliac joint such that the first top and first bottom surfaces oppose either the sacrum or the ilium.

The cutting tool may be configured to releasably and slidably couple with the trial tool assembly. The cutting tool may include a cutting element at a distal end of the cutting tool and a cutting shaft extending proximally from the cutting element. The cutting element may include a second length extending from a proximal to a distal end. The trial tool assembly may be configured to guide the cutting tool during distal-proximal translation such that as the cutting element distally advances relative to the implant trial, at least a portion of the cutting element extends generally over and perpendicularly outward from the first top surface of the body of the implant trial.

While multiple embodiments are disclosed, still other embodiments of the present disclosure will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative embodiments of the disclosure. As will be realized, the various embodiments of the present disclosure are capable of modifications in various aspects, all without departing from the spirit and scope of the present disclosure. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an anterior view of the pelvic region and a conventional method and device for stabilizing the sacroiliac joint.

FIG. 2A is an isometric view of a first embodiment of a system for fusing a sacroiliac joint.

FIG. 2B is the same view as FIG. 2A, except the delivery tool and implant assembly are decoupled from each other.

FIG. 3 is the same view as FIG. 2A, except the system is exploded to better illustrate its components.

FIG. 4 is a posterior-inferior view of a sacroiliac joint with a patient body shown in broken line.

FIG. 5 is a close-up view of the implant and anchor element in the sacroiliac joint.

FIG. 6 is an isometric view of a first embodiment of a joint preparation tool.

FIG. 7 is an exploded side view of the first embodiment of the joint preparation tool.

FIG. 8 is an isometric and cross-sectional view of the first embodiment of the joint preparation tool.

FIGS. 9A-9B are isometric views of a cutting element at a distal end of the tooling head.

FIG. 10 is an isometric view of the proximal edge of the cutting element.

FIG. 11 is an isometric view of a tooling head with a closed distal end and an opened proximal end.

FIG. 12 is an isometric and cross-sectional view of the tooling head of FIG. 11.

FIG. 13 is a side view of a tooling head with a pair of cutting elements opposite each other.

FIG. 14A is a side view of the shaft of the tooling head and possible modifications.

FIG. 14B is a close-up side view of the distal end of the tooling head of FIG. 14A.

FIG. 15A is an isometric view of a tooling head with an ellipsoidal head.

FIG. 15B is a side view of the tooling head with the ellipsoidal head.

FIG. 15C is a close-up side view of the tooling head with the ellipsoidal head.

FIG. 15D is another side view of the tooling head with the ellipsoidal head.

FIG. 16 is an isometric view of a tooling head with a bisected ellipsoidal head.

FIG. 17 is an isometric view of another tooling head with a bisected ellipsoidal head.

FIG. 18A is a front view of a tooling head with a planar rasping head.

FIG. 18B is a side view of the tooling head of FIG. 18A.

FIG. 18C is a side cross-sectional view of the planar rasping head.

FIG. 18D is a close-up isometric view of the planar rasping head.

FIG. 19A is a front view of a tooling head with a planar rasping head and a single perpendicularly extending cutting element.

FIG. 19B is a side view of the tooling head of FIG. 19A.

FIG. 19C is a side cross-sectional view of the planar rasping head and the single perpendicularly extending cutting element.

FIG. 19D is a close-up isometric view of the planar rasping head and the single perpendicularly extending cutting element.

FIG. 20A is a front view of a tooling head with a smooth planar head and a single perpendicularly extending cutting element.

FIG. 20B is a side view of the tooling head of FIG. 20A.

FIG. 20C is a close-up isometric view of the smooth planar head and the single perpendicularly extending cutting element.

FIG. 21A is a front view of a tooling head with a smooth planar head and a pair of perpendicularly extending cutting elements.

FIG. 21B is a side view of the tooling head of FIG. 21A.

FIG. 21C is a close-up isometric view of the smooth planar head and the pair of perpendicularly extending cutting elements.

FIG. 22A is a front view of a tooling head with a planar rasping head and a pair of perpendicularly extending cutting elements.

FIG. 22B is a side view of the tooling head of FIG. 22A.

FIG. 22C is a side cross-sectional view of the tooling head of FIG. 22A.

FIG. 22D is a close-up isometric view of the planar rasping head and the pair of perpendicularly extending cutting elements.

FIG. 23A is a front view of a tooling head with a box osteotome head.

FIG. 23B is a side view of the tooling head of FIG. 23A.

FIG. 23C is a cross-sectional view of the box osteotome head.

FIG. 23D is a bottom close-up isometric view of the box osteotome head.

FIG. 24A is a side view of a surgical preparation tool attached to an anchor arm assembly.

FIG. 24B is a side view of the surgical preparation tool and the anchor arm assembly of FIG. 24A in a pre-assembled state.

FIG. 25 is a side view of another surgical preparation tool attached to an anchor arm assembly.

FIG. 26A is an isometric view of a joint preparation tool with a translating and rotation inhibiting distal handle assembly.

FIG. 26B is a cross-sectional view of a coupler member and a shaft of a tooling head of the tool of FIG. 26A.

FIG. 26C is a front isometric view of the joint preparation tool of FIG. 26A with a socket assembly in an uncoupled state.

FIG. 26D is a side view of the joint preparation tool of FIG. 26A with the distal handle assembly in a proximal position.

FIG. 26E is a close-up side view of a cutting element at a distal end of the tooling head of the joint preparation tool of FIG. 26A.

FIG. 26F is a cross-sectional view of the cutting element of FIG. 26E.

FIG. 26G is a cross-sectional view of another embodiment of a cutting element.

FIG. 27 is an isometric view of a bottom side of a surgical preparation tool assembly including a trial tool assembly and a cutting tool.

FIG. 28 is an isometric view of a top side of the surgical preparation tool assembly of FIG. 27.

FIG. 29 is an isometric view of the cutting tool of the surgical preparation tool assembly of FIG. 27.

FIG. 30 is a close-up isometric view of a distal end of the cutting tool.

FIG. 31 is an isometric back view of the surgical preparation tool assembly with a cross-section at the proximal end of the implant trial.

FIG. 32 is a front view of the trial tool assembly.

FIG. 33 is a back view of the trial tool assembly.

FIG. 34 is a side view of the trial tool assembly.

FIG. 35 is a cross-sectional isometric view of the handle assembly and the proximal end of the shaft of the trial tool.

FIG. 36A is a side view of another embodiment of a cutting tool.

FIG. 36B is a close-up isometric view of the cutting tool of FIG. 35A.

FIG. 36C is a side view of a cutting element formed of a chain of interconnected teeth.

FIG. 36D is a top view of an implant trial configured to guide the cutting element of FIG. 36C.

FIG. 36E is an isometric view of an arcuate implant trial configured to guide a cutting element formed of a chain of interconnected teeth.

FIG. 37 is an isometric view of a joint preparation tool assembly with coaxially aligned shafts of a cutting tool and a trial implant tool assembly.

FIG. 38 is an isometric view of the joint preparation tool assembly of FIG. 37 with the cutting tool and the trial implant tool assembly in an uncoupled state.

FIG. 39 is an isometric view of a joint preparation tool assembly with coaxially aligned shafts of a cutting tool, a trial implant tool assembly, and a trial impact rod assembly.

FIGS. 40A-40C are isometric views of the trial impact rod assembly and the trial tool assembly coupling together.

FIG. 41 is an isometric view of a handle assembly coupling with the trial impact rod assembly and the trial tool assembly.

FIG. 42A is an isometric view of the cutting tool and the trial tool assembly coupling together.

FIG. 42B is an isometric view of the handle assembly coupling with the cutting tool and the trial tool assembly.

FIG. 43A-43D are front view of implant trials with differing configurations of cutting tools.

FIG. 43E is an isometric view of an implant trial and an anchor member in a recessed condition.

FIG. 43F is an isometric view of an implant trial and an anchor member in a deployed condition.

FIG. 44 is an isometric view of a joint preparation tool assembly with a trial tool assembly and a drill guide.

FIG. 45 is an isometric view of the joint preparation tool assembly of FIG. 44 with the various components in an uncoupled state.

FIG. 46 is an isometric view of the joint preparation tool assembly of FIG. 44 with a drill bit positioned within a collar of the drill guide.

FIG. 47A-47B are differing configurations of the collar on the drill guide.

FIG. 48A is a right lateral view of a hip region of a patient lying in a prone position, wherein the soft tissue surrounding the skeletal structure of the patient is shown in dashed lines.

FIG. 48B is an enlarged view of the hip region of FIG. 48A.

FIG. 48C is generally the same view as FIG. 48B, except that the ilium is removed to show the sacroiliac joint space boundary defined along the sacrum and an implant positioned for implantation within the joint space.

FIGS. 49A-49D are each a step in the methodology and illustrated as the same transverse cross section taken along a plane extending generally medial-lateral and generally anterior posterior.

FIG. 49E is a posterior view of the pelvic region showing fixed placement of the cannula in relation to the sacroiliac joint having inserted within a cannula alignment jig.

FIG. 49F is a perspective view of the cannula jig insert shown in FIG. 49E having cross hairs.

FIG. 49G is a perspective view of the cannula shown in FIG. 49F having a cannula alignment jig inserted within having alignable cross hairs.

FIG. 49H is a posterior view of the pelvic region showing fixed placement of the cannula in relation to the sacroiliac joint having within a first drill jig.

FIG. 49I is a perspective view of the cannula of FIG. 49H having within the first drill jig.

FIG. 49J is a side view of a cannula, in one embodiment.

FIG. 49K is a top view of the cannula of FIG. 49J.

FIG. 49L is a front view of the cannula of FIG. 49J.

FIG. 49M is a posterior lateral view of the pelvic region showing the cannula of FIG. 49J positioned in relation to the sacroiliac joint.

FIG. 49N is another posterior lateral view of the pelvic region showing the cannula of FIG. 49J positioned in relation to the sacroiliac joint.

FIG. 49O is a posterior view of the pelvic region showing the cannula of FIG. 49J positioned in relation to the sacroiliac joint.

FIG. 49P is a posterior inferior view of the pelvic region showing the cannula of FIG. 49J positioned in relation to the sacroiliac joint.

FIG. 49Q is a posterior view of the pelvic region showing the cannula of FIG. 49J positioned in relation to the sacroiliac joint.

FIG. 49R is another posterior view of the pelvic region showing the cannula of FIG. 49J positioned in relation to the sacroiliac joint.

FIGS. 50A-50B are steps in the methodology of preparing the sacroiliac joint for fusion utilizing a tooling head, e.g., of FIGS. 9-10, and illustrated in the transverse cross section of FIGS. 49A-49D.

FIGS. 50C-50F are additional steps in the methodology that continue from those described in reference to FIGS. 50A-50B, except that the view is of the sacroiliac joint from the perspective in FIG. 48C.

FIGS. 51A-51E are additional steps in the methodology of preparing the sacroiliac joint for fusion including utilizing

a tooling head, e.g., of FIGS. 9-10, and illustrated in the transverse cross section of FIGS. 50A-50B.

FIGS. 52A-52B are steps in the methodology of preparing a sacroiliac joint for fusion utilizing a tooling head with dual cutting elements, e.g., as seen in FIG. 13, and shown in the transverse cross section of FIGS. 49A-49D.

FIGS. 53A-53D are steps in the methodology of preparing a sacroiliac joint for fusion utilizing the joint preparation tool assemblies described in FIGS. 27-47.

FIG. 54A-54E depict, respectively, an isometric view, top view, side view, back view, and front view of a joint implant, in one embodiment. The side view being the same as an opposite side view, and the top view being the same as the bottom view.

FIG. 55A-55E depict, respectively, an isometric view, top view, side view, back view, and front view of a joint implant, in one embodiment. The side view being the same as an opposite side view, and the top view being the same as the bottom view.

FIG. 56A is a side view of a telescoping anchor arm assembly.

FIG. 56B is a side view of the telescoping anchor arm assembly of FIG. 56A, except with a portion of the first section nested within the central lumen of the second section, resulting in a shorter elongate shape.

DETAILED DESCRIPTION

Implementations of the present disclosure involve a system for preparing a sacroiliac joint for fusion. In particular, the system may include a preparation tool for removing articular cartilage from the sacroiliac joint space, abrading of the articular surfaces to enhance boney fusion, and removal of portions of the cortical, subchondral or cancellous bone for implantation of a fusion device. The preparation tool may include an anchoring arm that is configured to direct an anchoring element for transverse delivery through the sacroiliac joint space. The anchor may be delivered into the joint space before, during, or after the joint space is prepared for implant delivery. Alternatively, an implant may not be delivered into the joint and instead, e.g., bone paste or slurry may be introduced into the prepared sacroiliac joint before or after anchor placement. And, the anchor may be delivered cranial, caudal, or in-line with the eventual placement of the implant. The preparation tool is configured to quickly, accurately and reliably prepare the joint space for insertion of an implant.

I. System for Fusion of the Sacroiliac Joint

To begin a detailed discussion of a system 10 for delivering an implant 12 into the sacroiliac joint, reference is made to FIGS. 2A-3. FIG. 2A is an isometric view of the system 10. FIG. 2B is the same view as FIG. 2A, except an implant assembly 14 of the system 10 is separated from a delivery tool 16 of the system 10. FIG. 3 is the same view as FIG. 2A, except the system 10 is shown exploded to better illustrate the components of the system 10.

As can be understood from FIGS. 2A and 2B, the system 10 includes a delivery tool 16 and an implant assembly 14 for implanting at the sacroiliac joint via the delivery tool 16, the implant assembly 14 being for fusing the sacroiliac joint. As indicated in FIG. 3, the implant assembly 14 includes an implant 12 and an anchor element 18 (e.g., a bone screw or other elongated body). As discussed below in greater detail, during the implantation of the implant assembly 14 at the sacroiliac joint, the implant 12 and anchor element 18 are supported by a distal end 20 of the delivery tool 16, as illustrated in FIG. 2A. The delivery tool 16 is used to deliver

11

the implant **12** into the sacroiliac joint space. The delivery tool **16** is then used to cause the anchor element **18** to extend through the ilium, sacrum and implant **12** generally transverse to the sacroiliac joint and implant **12**. The delivery tool **16** is then decoupled from the implanted implant assembly **14**, as can be understood from FIG. 2B. As illustrated in FIG. 3, the delivery tool **16** further includes a proximal end **22** opposite the distal end **20**, an arm assembly **24**, a handle **26**, an implant retainer **28**, a sleeve **30** and a trocar or guidewire **32**. While in the embodiment of FIGS. 2A-3, the delivery tool **16** is fixed and non-adjustable and configured to deliver the anchoring element **18** in a single orientation relative to the implant **12**, the delivery tool **16** may be adjustable and configured to deliver the anchoring element **18** within a range of orientations relative to the implant **12** that will orient the anchoring element **18** either within a bore of the implant **12**, or adjacent implant **12** as described in U.S. patent application Ser. No. 14/447,612, filed Jul. 31, 2014, entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT, which is hereby incorporated by reference in its entirety.

In particular embodiments, first and second articular faces of the implant **12** may be selected to match the contour of the joint space of the sacroiliac joint within which the implant **12** is to be inserted. For example, the sacral, medial or first articular face of the implant may be configured to be generally convex to match the contour of a sacral auricular bony surface or to match the contour of an extra-articular region of a sacrum (e.g., a sacral fossa). In one aspect and referring to portions of the anatomy shown FIG. 48C, the sacral, medial or first articular face of the implant **12** may be generally a surface negative of the articular surfaces **1016** of the extra-articular region **3007** and/or articular region **1044** of the sacrum **1004**. As another example, the lateral, iliac or second articular face of the implant **12** may be configured to be generally concave to match the contour of an iliac auricular bony surface or to match the contour of an extra-articular region of an ilium (e.g., an iliac tuberosity). In one aspect, the lateral, iliac or second articular face of the implant **12** may be generally a surface negative of the articular surfaces **1016** of the extra-articular region **3007** and/or articular region **1044** of the ilium **1005**.

Referring to FIGS. 54A-54E, in one embodiment the implant **9010** includes a first planar member **9012** extending a first top length of the implant and comprising a first planar top surface **9014** that extends between a first sacral side edge **9016** and a first ilium side edge **9018** that is opposite of and substantially parallel with the first sacral side edge, the side edges being substantially perpendicular to first planar top surface, the side edges extending the first top length of the implant and disposed a first thickness **9020** from a first bottom surface **9022** that is opposite the first planar top surface, the first planar top surface also extending between a substantially perpendicular proximal end edge **9024** and a tapered distal end edge **9026**, the tapered distal edge including a sloped taper **9028** along the first thickness between the first planar top surface and the first bottom surface such that the first top length is shorter than a first bottom length that extends a length of the first bottom surface, the tapered distal edge also including an inward tapering **9030** of the side edges towards a distal end of the implant, the side edges including a taper **9032** at a proximal end of the implant such that the first thickness substantially linearly increases until the side edges meet with the proximal end edge.

12

The implant further includes a second planar member **9034** that is opposite the first planar member, the second planar member extending a second top length of the implant and comprising a second planar top surface **9036** that extends between a second sacral side edge **9038** and a second ilium side edge **9040** that is opposite of and substantially parallel with the second sacral side edge, the side edges being substantially perpendicular to the second planar top surface, the side edges extending the second top length of the implant and disposed a second thickness **9042** from a second bottom surface **9044** that is opposite the first planar top surface and opposed to the first bottom surface, the second planar top surface also extending between a substantially perpendicular proximal end edge **9046** and a tapered distal end edge **9048**, the tapered distal edge including a sloped taper **9050** along the second thickness between the second planar top surface and the second bottom surface such that the second top length is shorter than a second bottom length that extends a length of the second bottom surface, the tapered distal edge also including an inward tapering **9052** of the side edges towards the distal end of the implant, the side edges including a taper **9054** at a proximal end of the implant such that the second thickness substantially linearly increases until the side edges meet with the proximal end edge.

The implant further includes a distal end member **9056** that couples the respective tapered distal end edges of the first planar member and the second planar member, the distal end member extending perpendicularly between the first planar member and the second planar member and including a distal front edge **9058**, a proximal edge **9060** opposite the distal front edge, and a pair of distal end member side surfaces **9062** between the distal front edge and the proximal edge, the proximal edge including a width that is larger than a width of the distal front edge such that the pair of distal end member side surfaces tapers or narrows **9064** towards the distal front edge, the distal front edge including a distal most point **9066** that slopes toward each of the respective first planar top surface and the second planar top surface, the sloping of the distal front edge smoothly transitioning **9068** with the sloped taper between the first planar top surface and the first bottom surface as well as the sloped taper between the second planar top surface and the second bottom surface, the distal front edge and the proximal edge both defining radial curves **9069**.

The implant further includes a proximal end member **9070** that couples the respective proximal end edges of the first planar member and the second planar member, the proximal end member including a proximal side **9072** that is in-line and parallel with the first and the second proximal end edge and a distal side **9074** that is opposite the proximal side, the distal side including a curve **9076** that is a mirror of the radial curve of the proximal edge of the distal end member, the proximal end member including an axial bore **9078** through the proximal end member, the proximal end member being slightly larger and including a similar shape to the axial bore, the axial bore being threaded and configured to mate with an implant insertion tool, wherein a bone graft or anchoring window **9080** is defined between the proximal edge of the distal end member and the distal side of the proximal end member, the window including a stadium shape that extends perpendicularly

through a longitudinal axis of the implant, the window being adapted to receive bone graft or an anchoring element to anchor the implant to the articular surfaces. In certain embodiments, the distal end member side edges and the proximal edge meet at a corner where the corner is perpendicular or rounded. Similarly, other meeting points between respective edges can be straight edges (e.g., perpendicular) or rounded.

In still other embodiments, among other figures, the first sacral side edge **9016** and the first ilium side edge **9018** taper inward from the proximal end **9024** to the distal end **9026** of the implant such that the first planar top surface **9014** and the second planar top surface **9016** defines a truncated isosceles triangle with the side edges forming sides of equal length.

While reference is made to the embodiment of the implant **9010** in FIGS. **54A-54E**, the reference numerals are similarly applicable to the implant **9010** in FIGS. **55A-55E**.

A system as described in FIGS. **2A-3** may be used in a surgical procedure via a posterior approach, as seen in FIGS. **4-5**. As can be understood from FIG. **4**, which is a posterior-inferior view of a sacroiliac joint **36** with a patient **40** shown in broken line, the delivery tool **16** is positioned to deliver the implant **12** into a caudal region **34** of the sacroiliac joint **36** and the anchoring element **18** through the ilium **5** and into the bore **38** of the implant **12**. Referring to FIG. **5**, the implant **12** and anchoring element **18** have been inserted into the caudal region **34** of the sacroiliac joint **36** and the delivery tool **16** has been removed.

With further reference to the boney anatomy shown in FIG. **48C**, a system as described herein may be used in a surgical procedure via an anterior approach (e.g., such that the surgical pathway includes traversing an anterior boundary segment **3004** and/or traversing an anterior-inferior corner **3010**) and may further include positioning an implant into a sacroiliac joint such that: 1) the implant longitudinal axis a) is generally parallel to a sacroiliac joint inferior boundary segment **3002**, or b) points towards a posterior superior iliac spine, or c) point towards a posterior inferior iliac spine, or d) points toward a sacroiliac extra-articular region; or, 2) the distal end of the implant generally lies within a) a caudal region of the sacroiliac joint articular region, or b) an extra-articular portion of the sacroiliac joint, or c) a cranial portion or cephalad region of the sacroiliac joint articular region.

Additionally, a system as described herein may be used in a surgical procedure via an approach which includes a surgical pathway which transverses a sacroiliac joint inferior boundary segment **3002**, e.g., as described in U.S. patent application Ser. No. 13/945,053, filed Jul. 18, 2013, entitled SYSTEMS AND METHODS OF FUSING A SACROILIAC JOINT, which is hereby incorporated by reference in its entirety. A surgical procedure via this pathway may further include positioning an implant into a sacroiliac joint such that: 1) the implant longitudinal axis a) is transverse to a sacroiliac joint inferior boundary segment **3002**, or b) points towards a posterior superior iliac spine, or c) point towards a posterior inferior iliac spine, or d) points toward a sacroiliac extra-articular region, or e) points towards a sacroiliac joint anterior boundary segment **3004**, or f) points towards either superior boundary segment corner **3014** or **3012** or somewhere in-between; or, 2) the distal end of the implant generally lies within a) a caudal region of the sacroiliac joint articular region, or b) an extra-articular portion of the sacroiliac joint, or c) a cranial portion or cephalad region of the sacroiliac joint articular region.

Furthermore, in an aspect, an implant **12** may be inserted along a generally arcuate path. Accordingly, a surgical preparation technique and tools may be utilized while operating in an arcuate path. The implant arcuate path may follow and generally match the surgical preparation arcuate path and the path arc may include a radius of between approximately 3 cm to 6 cm. The portion of the path having an arcuate path including a radius of between approximately 3 cm to 6 cm may reside substantially in the plane of the sacroiliac joint or in a plane in close proximity and generally parallel thereto. Furthermore, the arcuate path may generally or substantially reside in sacroiliac joint articular region **1044**. Additionally, an implant may be selected for use during the procedure which substantially matches the radius or curvature of the arcuate or curved insertion path or surgical preparation path.

According to a particular aspect, after drilling or otherwise producing an opening through an ilium (or sacrum) leading toward or into a sacroiliac joint, a sleeve may guide (alone or along with another cannulated tool, e.g., a needle) a bone paste, bone marrow aspirate, stem cells, allograft or any biocompatible material or substance into the sacroiliac joint space via a path with a trajectory which may be generally transverse to the plane of the sacroiliac joint. The sleeve may be caused to form a seal with a bone defining the sacroiliac joint, e.g. the ilium. The seal may be created by impacting a proximal end of sleeve which may, for example, cause the sleeve to slightly penetrate the cortex of the outer table of the ilium. Alternatively, a cannulated tool such as a large gauge needle or tube may either be interference fit within a hole in the ilium or the needle or tube may have a threaded distal end which may be threaded into the bore formed in the ilium. A plunger or bone tamp may be forced through a sleeve to advance the bone paste or other material into the sacroiliac joint space, adjacent/around the implant and/or into the bone graft window of the implant.

Subsequently, an anchor such as a bone screw may be advanced via the sleeve into engagement with an opening formed in the ilium and driven across the sacroiliac joint and further into the sacrum. Alternatively, a bone plug may be positioned into the opening formed in the ilium in order to occlude the passageway between the outer cortex of the ilium and the implanted bone paste or other material positioned which had be positioned generally in the plane of the joint.

As such, the systems and methods described herein are directed to preparing the sacroiliac joint for surgical fusion procedures of this type and others.

II. System for Preparing the Sacroiliac Joint for Fusion

Various surgical preparation tools and assemblies will be discussed herein. These tools and assemblies may be used by themselves or in combination with each other. Additionally, features of a particular embodiment are non-limiting and may be incorporated into any or all other embodiments without departing from the teachings in this disclosure.

A. Joint Preparation Tool with Interchangeable Heads

To begin a detailed discussion of the surgical preparation tools for preparing a sacroiliac joint for a fusion, reference is made to FIG. **6**, which is an isometric view of a first embodiment of a joint preparation tool **50** with interchangeable tooling heads **52**. Each of the tooling heads **52** described herein may be used by themselves, with one or more subcomponents of tool **50**, with the completed tool **50**, or with any other tool of the systems disclosed herein or incorporated herein. As seen in the figure, the joint preparation tool **50** includes a slap hammer assembly **54** and a cutting tool assembly **56**. The slap hammer assembly **54**

15

includes a proximal handle **58** that translates distal-proximal on a shaft **60**. The cutting tool assembly **56** includes a distal handle **62**. To better illustrate the components of the joint preparation tool **50**, reference is made to FIG. 7, which is an exploded side view of the tool **50**. As seen in the figure, a distal end **64** of the shaft **60** of the slap hammer assembly **54** is coupled to a proximal end **66** of a shaft **68** of the tooling head **52** via a connector **70** having dual-female threaded ports **72**. The distal end **64** of the shaft **60** and the proximal end **66** of the shaft **68** have thread features **74** that correspond and engage with the dual-female threaded ports **72**. In other embodiments, the connector **70** may include dual-male threaded ends and the shafts **60**, **68** may include corresponding female threaded ports. The distal handle **62** includes a lumen **76** extending through the handle **62** that is slightly larger than an outer diameter of the shaft **68** of the tooling head **52**. The distal handle **62** may be slidably positioned over the shaft **68** of the tooling head **52** and locked in place with a pair of set screws **78**. Thus, the distal handle **62** may be positioned as far proximally such that it abuts the connector **70**, as far distally so as not to interfere with the distal end of the tooling head **52**, or at any point in between.

Reference is now made to FIG. 8, which is an isometric and cross-sectional view of the first embodiment of the joint preparation tool **50**. As seen in the figure, the proximal handle **58** further includes a lumen **80** extending through the handle **58** that is slightly larger than an outer diameter of the shaft **60** of the slap hammer assembly **54**. The proximal handle **58** is configured to slide or translate distal-proximal on the shaft **60** between a proximal stop feature **82** and a distal stop feature **84**. In this way, a surgeon may grasp the distal handle **62** with one hand and the proximal handle **58** with the other hand. To facilitate distal driving of the tooling head **52**, the surgeon may distally slide the proximal handle until it makes contact with the distal stop feature **84**. The contact with the stop feature **84** will cause a force to be transmitted down the shaft **68** of the tooling head **52** such that head **52** will advance in the direction of the force. This type of driving of the tooling head **52** may be useful to advance a distal end **86** of the tooling head **52** into the sacroiliac joint.

Additionally, the proximal stop feature **82** may be configured such that an additional handle may be coupled to or integral with proximal stop feature **82**. The additional handle may be in-line with shaft **60** and extend proximally from the proximal stop feature **82**.

To facilitate backing-out of the tooling head **52**, the surgeon may proximally slide the proximal handle until it makes contact with the proximal stop feature **82**. This contact will cause a force to be transmitted proximally, which may aid in backing the tooling head **52** out from within the sacroiliac joint, for example.

As stated above, the first embodiment of the joint preparation tool **50** is configured to be used with a variety of interchangeable tooling heads **52**. In certain embodiments and referring to FIGS. 9A-9B, the tooling head **52** may include a cutting element **88** at the distal end **86** of the tooling head **52**. The cutting element **88** includes an aperture **90** at a distal most end of the tooling head **52** that extends between a distal edge **92** and a proximal edge **94**. The distal edge **92** forms a boundary of the aperture **90** and, in this embodiment, the distal edge **92** is blunt. Opposite the distal edge **92** is the proximal edge **94**, which, in this embodiment, is angled, sharp, and configured for cutting during "backing-out" of the preparation tool **50** from the sacroiliac joint.

In this embodiment, the aperture **90** is rectangular and is defined by a pair of generally parallel sidewall members **102**

16

that extend generally tangentially from the surface of the shaft **68** of the tooling head **52**. Adjacent and extending generally perpendicular between the parallel sidewall members **102** is a top wall member **104**. Opposite the top wall member **104** is an inner wall member **106** that may communicate with an opened end of a lumen **108** that extends through the shaft **68** of the tooling head **52**. Additional tooling (e.g., guidewire, suctioning device, irrigation, a (centreless/shaftless/flexible/etc.) screw conveyor, an auger, Archimedes' screw, or their various combinations) may communicate through the lumen **108** for interaction with the portion of the patient's body in contact with the distal end **86** of the tooling head **52**.

A tooling head **52** with a cutting element **88** as described in FIGS. 9A-9B may be useful, for example, during the initial preparations of the sacroiliac joint. That is, the cutting element **88** may be initially and carefully advanced into the sacroiliac joint via the slap hammer assembly **54**. Once at an appropriate depth into the caudal region of the joint, the cutting element **88** may be more aggressively backed-out by the application of force by the proximal handle **58** against the proximal stop feature **82**. In this way, the force used to cut the articular cartilage is applied in the safer, proximal direction. Applying force distally requires care because advancement of the cutting element **88** too far (i.e., outside of the sacroiliac joint) can risk damage to, for example, the ventral sacroiliac joint ligament or the neurovascular structures in proximity to the joint.

Other arrangements of the cutting element **88** are possible and contemplated by this disclosure. For example, the distal edge **92** may be sharp and configured for cutting, while the proximal edge **94** may be blunt. Additionally and as seen in FIG. 10, which is an isometric view of the proximal edge **94** of the cutting element **88**, the side wall members **102** are parallel, but the top wall member **104** and, thus, the distal edge, **92**, the proximal edge **94**, and the aperture **90** are rounded. As seen in the figure, the proximal edge **94** is sharpened along its radial edge **96** and is configured to cut during a "backing-out" of the cutting element **88**.

Other arrangements of the top wall member **104** and side wall members **102** are possible. For example, the side wall members **102** may converge to a blade-like point. The particular arrangement of the top wall member **104** and side wall members **102** may be chosen based on the density of the bony surface to be prepared. And, as will be discussed later, the tool **50** may be used oriented perpendicular to the articular surfaces of the sacroiliac joint in order to make "keel-cuts" into the bone of either or both of the sacrum or the ilium. Such keel-cuts may match or generally match a shape of an implant to be implanted into the joint. Alternatively, the keel-cuts may be sized smaller than portions of an implant to be implanted into the joint such that a portion of the implant when implanted may extend beyond the keel-cut void and further into the prepared bone. Alternatively, a keel-cut may be created in only one bone, for example, the ilium, and may generally match the shape of an implant to be implanted while the second bone, e.g., the sacrum, may have no keel-cut or a keel-cut which is significantly undersized in comparison to the shape or size of the feature of the implant which is to be implanted into the sacrum. Thus, the shape of the top wall member **104** and the side wall members **102** may be influenced by the type and configuration of the implant that is chosen for the fusion procedure.

Referring now to FIG. 11, which is an isometric view of another embodiment of a tooling head **52**, the head **52** may include a curette-type closed distal end **86** and an opened proximal end **98** that defines a cup-shape. The tooling head

17

52 may include a pair of generally parallel side wall members 102 and a rounded top wall member 104. A proximal edge 94 bounds the opened proximal end 98 and may or may not be sharpened. As best seen in FIG. 12, which is an isometric and cross-sectional view of the tooling head 52, the tooling head 52 defines an inner cavity 100 that is configured to gather cartilage or other material when scooping or backing the distal end 86 of the tooling head 52 out of the sacroiliac joint. While not depicted in this embodiment, the tooling head 52 may include an opening in the vicinity of the cavity 100 that communicates with a lumen that extends through the shaft 68 of the tooling head 52. In certain instances, it may be advantageous to use the cup-shaped tooling head 52 of FIGS. 11-12 to gather and remove biological material that was cut or abraded from the articular surfaces of the sacroiliac joint by the opened tooling head 52 of FIGS. 9-10. In other instances, however, the closed tooling head 52 of FIGS. 11-12 may be used without previous preparation of the joint.

Referring now to FIG. 13, which is a side view of another embodiment of the tooling head 52, the head 52 may include two cutting elements 88 opposite each other. Each cutting element 88 may be as described with reference to FIGS. 9A-9B, FIG. 10 or FIGS. 11-12. In particular, each cutting element 88 includes parallel side wall members 102, a top wall member 104 extending generally perpendicular between the parallel side wall members 102, a distal edge 92, a proximal edge 94 opposite the distal edge 92, and an aperture 90 extending between the distal and proximal edges 92, 94. In this embodiment, the distal edge 92 is blunt and the proximal edge 94 is sharpened such that the tooling head 52 is configured to cut or abrade cartilage or other material in the sacroiliac joint during backing-out of the tooling head 52 from the joint. An arrangement with two cutting elements as shown in FIG. 13 may be useful, for example, to prepare the plane of the joint as well as in making parallel side-cuts or keel-cuts into the surfaces of the ilium and sacrum. To prepare the plane of the joint, each of the cutting elements 88 may be oriented such that neither projects into the sacrum or the ilium. Rather, the cutting elements 88 are oriented vertically within the articular space. On the other hand, to prepare the sacrum and/or the ilium for a subsequent delivery of an implant, the cutting elements 88 may be oriented to project into the bone of the sacrum and ilium, and for example oriented perpendicularly with the plane of the joint such that the cutting elements protrude generally perpendicularly into the sacrum and the ilium to make cuts that match a shape of a portion of an implant that will be implanted in the joint.

Referring to FIG. 14A, which is a side view of a tooling head 52, the shaft 68 may include a gradual taper from the proximal end 66 of the tooling head 52 to the distal end 86. As seen in the figure, the shaft 68 extends along a straight longitudinal axis between the distal and proximal ends 86, 66. Other arrangements of the shaft 68, however, are possible. For example and as seen in FIG. 14A, the shaft 68 may include a dogleg 110 along the shaft 68. In this example, the distal and proximal ends 86, 66 of the shaft 68 extend along parallel axes, but a mid-portion 112 of the shaft 68 extends non-parallel to the distal and proximal ends 86, 66. The dogleg 110 at the mid-portion 112 of the shaft 68 defines an angle A between the proximal end 66 and the dogleg 110 and an angle B between the dogleg 110 and the distal end 86 of the shaft 68. Also, the proximal end 66 and distal end 86 may be offset by a distance D1, which, in certain instances, may be within a range of about 10 mm to about 25 mm or from about 15 mm to 70 mm. In certain embodiments, angle A

18

may be within a range of about 90 degrees to about 165 degrees or from about 120 degrees and 150 degrees, and angle B may be within a range of about 90 degrees to about 165 degrees or from about 120 degrees and 150 degrees.

Referring to FIG. 14B, which is a close-up of the distal end 86 of the tooling head 52, a distance D2 is defined between the top wall member 104 and an opposite radial edge 114 of the shaft 68 of the tooling head 52. In certain instances, distance D2 may be within a range of about 4 mm to about 5.5 mm, from about 4.5 mm to about 6 mm, from about 5 mm to about 6.5 mm, from about 5.5 mm to about 8 mm, from about 7.5 mm to about 10 mm, from about 9 mm to about 11.5 mm and from about 11 mm to about 15 mm. A distance D3 is defined by a length of the top wall member and in certain instances D3 may be within a range of about 1.5 mm to about 2.5 mm, from about 2 mm to about 3.5 mm, from about 3 mm to about 4.75 mm, from about 4.25 mm to about 6 mm, from about 5 mm to about 6.75 mm, from about 5.5 mm to about 8 mm, from about 7.5 mm to about 10 mm, from about 9 mm to about 11.5 mm and from about 11 mm to about 15 mm. Angle C is defined between the shaft 68 of the tooling head 52 and the extension of the proximal edge 94 of the side wall member 102. In certain instances, angle C may be within a range of about 15 degrees to about 35 degrees, from about 30 degrees to about 45 degrees, from about 40 degrees to about 65 degrees, from about 60 degrees to about 75 degrees, from about 70 degrees to about 100 degrees, from about 90 degrees to about 135 degrees, from about 120 degrees to about 155 degrees, from about 150 degrees to about 170 degrees, from about 160 degrees to about 175 degrees, and from about 170 degrees to about 180 degrees (e.g., substantially in-line with shaft 68).

As stated above, the first embodiment of the joint preparation tool 50 is configured to be used with a variety of interchangeable tooling heads 52. Additionally, the tooling heads 52 may be used independently from the joint preparation tool 50. In certain embodiments and referring to FIGS. 15A-15D, the tooling head 52 may include an elongate shaft 116 coupled with an ellipsoidal head 118 at a distal end 120 of the tooling head 52. A proximal end 119 of the tooling head 52 may include threading (not shown) in order to couple with the connector 70 of the joint preparation tool 50 described previously. In this embodiment, the ellipsoidal head 118 is a triaxial ellipsoid shape (semi-axes lengths $C > B > A$), however, the head 118 may be other shapes without departing from the teachings of this disclosure. As seen in the figures, the ellipsoid head 118 includes a rasp band 122 around one half of the circumference of the ellipsoid head 118. The rasp band 122 may include a rough surface texture, or geometrically repeating or non-repeating pattern that is configured to abrade a boney surface of a patient (e.g., articular surface of the sacroiliac joint). In this particular embodiment, the rasp band 122 is a repeating cone-shaped pattern that is in the plane AB but is bounded on one side by axis A. While no rasp band 122 is depicted on the opposite side of the ellipsoid head 118, such a side may include a similar or different type of rasp band 122. For example, a less rough or "less aggressive" rasp band 122 may be included on the side opposite of the current rasp band 122 or simply on one half of the currently depicted rasp band 122. In this way, the tooling head 52 may be used to simultaneously rasp two surfaces with different rasp bands 122. In practice, such a tooling head 52 may be used to abrade the surfaces of the sacrum and the ilium in preparation for delivery of a joint implant. Since the sacrum is generally a softer bone than the ilium, the sacrum may require less abrasion than the ilium. Thus, the tooling head

52 with the ellipsoid head 118 having rasp bands 122 of differing roughness on opposite sides of the head 118 may be beneficial to rasp the ilium with a rasp band 122 having greater roughness and the sacrum with a rasp band 122 having less or no roughness.

Reference is now made to FIGS. 16-17, which are isometric views of tooling heads 52 with bisected ellipsoidal heads 124 and bisected shafts 126. The bisected ellipsoidal head 124 includes an ellipsoid shaped surface 128 on one side and a planar surface 130 opposite the ellipsoid shaped surface 128. The planar surface 130 extends a length of the shaft 126 from a distal end to a proximal end 120, 119. In FIG. 16, the bisected ellipsoidal head 124 includes a small rasp band 132 on a portion of the intersection of the planar surface 130 and the ellipsoidal shaped surface 128. In this embodiment, the small rasp band 132 includes a single row of teeth or other geometrically repeating pattern; however, the small rasp band 132 may include other surfaces configured to abrade or rasp a surface. In FIG. 17, the bisected ellipsoidal head 124 includes a rasp band 134 that is similar to that as described in FIGS. 15A-15D. That is, the rasp band 134 wraps around the entirety of the ellipsoid shaped surface 128 and includes a rough surface texture, or geometrically repeating or non-repeating pattern that is configured to abrade a boney surface of a patient (e.g., articular surface of sacroiliac joint). This type of tooling head 52 may be useful, for example, when a single surface of a pair of opposed surfaces requires rasping. As such, the tooling head 52 may be used, for example, to rasp the ilium only while orienting the planar surface 130 generally parallel with a plane defined by the sacrum. Alternatively, the tooling head 52 may be oriented to rasp the sacrum while orienting the planar surface 130 in-line with the ilium.

Moving on, the discussion will focus on FIGS. 18-23 and additional types and configurations of tooling heads 52 that are applicable for use with the joint preparation tool 50. Additionally and as discussed previously, the tooling heads 52 discussed herein may also be used independently from the joint preparation tool 50.

Reference is now made to FIGS. 18A-18D, which depict a tooling head 52 with a planar rasping head 136 at a distal end 138. The planar rasping head 136 is configured to prepare a joint or boney surface for subsequent delivery of an implant. More particularly, the planar rasping head 136 may be used to abrade or roughen a joint surface, such as the sacroiliac joint, by removing cartilage from the joint and causing the boney surface of the sacrum and the ilium to hemorrhage, which may contribute to subsequent bone growth and fusion of the sacrum and the ilium.

As seen in the FIGS. 18A-18B, the planar rasping head 136 is coupled to a shaft 140 that extends to a handle 142 at a proximal end 144 of the shaft 140. A proximal end 146 of the handle 142 includes an impact plate 148 that is configured to be struck with a hammer, mallet, or other device in order to drive the planar rasping head 136 distally. While this embodiment is depicted with a handle 142 attached to the proximal end 144 of the shaft 140, the shaft 140 could, alternatively, be coupled to the connector 70 of the joint preparation tool 50 described previously.

As seen FIGS. 18A-18D, the planar rasping head 136 is a planar member that includes a pair of planar surfaces 150 opposite of and generally parallel to each other. Alternatively, the pair of planar surfaces 150 may be non-parallel (not shown) and may taper. The planar surfaces 150 are disposed between a side edge 152 that wraps around the planar rasping head 136. A distal tip 158 of the planar rasping head 136 is rounded, although, in other embodi-

ments, the distal tip may be pointed, flat, or otherwise. The planar rasping head 136 includes a rasping surface 154 on the planar surfaces 150 and the side edge 152. The rasping surface 154 may include ridges 156 in a chevron pattern, as seen in the figures, or other surfaces configured to roughen or abrade a biological surface. The rasping surface 154 may, for example, include geometrically repeating or non-repeating features (e.g., cones, pyramids, bubbles, spines, notches, teeth) formed by machining, surface treating, or otherwise.

As seen in FIG. 18A, the planar rasping head 136 may include a width W18 in a range of about 13 mm to about 19 mm. In certain instances, the width W18 may be 13 mm, 16 mm, or 19 mm. As seen in FIG. 18B, the planar rasping head 136 may include a thickness T18 between the planar surfaces 150 in a range of about 5 mm to about 7 mm. In certain instances, the thickness T18 may be 5 mm, 6 mm, or 7 mm.

Moving on, reference is made to FIGS. 19A-19D, which depict a tooling head 52 with a planar rasping head 160 at a distal end 162 of the tooling head 52 that includes a single perpendicularly extending cutting element 164. The planar rasping head 160 is a planar member that includes a planar top surface 166, a planar bottom surface 168 opposite the top surface 166, and a side edge 186 extending between the top and bottom surfaces 166, 168. The distal end 162 of the rasping head 160 includes a double chamfered tip 184. Both the top and bottom surfaces 166, 168 and the side edge 186 include a rasping surface 170 that is configured to abrade or roughen a boney surface or a joint. The rasping surface 170 may include a series of ridges 172 in a chevron pattern or otherwise, as described previously. The tooling head of this embodiment may also include a handle 142, an impact plate 148, and a shaft 140, among other features, as described in previous embodiments.

As seen in the figures, the cutting element 164 extends generally perpendicularly upward from a central portion of the top surface 166. The cutting element 164 is a planar member with opposite side surfaces 174 and a top surface 176 that includes a cutting element feature 178, which, in this embodiment, includes a series of teeth 180 with a rounded blade-tip 182 at the distal most end. The planar rasping head 136 is configured to prepare a joint or boney surface for subsequent delivery of an implant. More particularly, the bottom surface 168 of the planar rasping head 136 may be used to abrade or roughen a joint surface, such as the sacroiliac joint, by removing cartilage from the joint and causing the boney surface of the sacrum and the ilium to hemorrhage, which may contribute to subsequent bone growth within the joint space. The top surface 166 with the cutting element 164, on the other hand, may be used to cut into either the sacrum or the ilium in order to make way for a portion of an implant (e.g., keel or wing member) that will protrude into the bone of the sacrum or ilium. As previously described with reference to FIG. 5, an implant may include keels that extend generally perpendicularly into each of the ilium and the sacrum. Thus, a tooling head 52 such as seen in FIGS. 19A-19D may be useful in preparing a "keel-cut" into either or both of the sacrum or ilium such that when the implant 12 is delivered into the sacroiliac joint, the keels may be delivered and positioned within the keel-cuts made by the tooling head 52 with the planar rasping head 160 with the perpendicularly extending cutting element 164. While the tooling head 52 is described with a single perpendicularly extending cutting element 164, the head 52 may include a second cutting element (not shown) extending opposite the first cutting element 164 on the bottom surface 168 of the rasping head 160. In this way, the tooling head 52 may perform dual keel-cuts simultaneously in both the

21

sacrum and the ilium. In such an embodiment, the cutting element feature **178** may be different for each cutting element **164** since the ilium is a generally harder bone than the sacrum, which is generally softer.

As seen in FIG. **19A**, the planar rasping head **160** may include a width **W19** in a range of about 11 mm to about 17 mm. In certain instances, the width **W19** may be 11 mm, 14 mm, or 17 mm. Also seen in FIG. **19A**, the cutting element **164** may include a thickness **T19A** of about 2.5 mm. As seen in FIG. **19B**, the planar rasping head **160** may include a thickness **T19B** between the planar surfaces **166**, **168** in a range of about 5 mm to about 7 mm. In certain instances, the thickness **T19B** may be 5 mm, 6 mm, or 7 mm. Also as seen in FIG. **19B**, the planar rasping head **160** and the cutting element **164** may have a combined thickness **TC19B** in a range of about 5.5 mm to about 7.5 mm. In certain instances, the combined thickness **TC19B** may be about 5.5 mm, 6.5 mm, or 7.5 mm.

Moving on, reference is made to FIGS. **20A-20C**, which depict a tooling head **52** with a planar rasping head **160** at a distal end **162** of the tooling head **52** that includes a single perpendicularly extending cutting element **164**. This embodiment includes similar features to the tooling head **52** described in reference to FIGS. **19A-19D**, except that the present embodiment includes a smooth surface **188** instead of a rasping surface on the top surface, bottom surface, and side edges **166**, **168**, **186**. The present embodiment of the tooling head **52** may be useful in a surgical preparation when the articular surfaces of the sacroiliac joint need not be rasped, but merely require keel-cuts into the sacrum and/or the ilium in preparation for delivery of an implant.

Reference is now made to FIGS. **21A-21C**, which depict a tooling head **52** with a planar rasping head **190** with a pair of perpendicularly extending cutting elements **192** extending from side edges **194** of the head **52**. In this embodiment, the planar rasping head **190** is a planar member that includes a planar top surface **196**, a planar bottom surface **198** opposite the top surface **196**, both of which include a smooth surface texture **200**. The planar rasping head **190** also includes a double chamfered tip **202** at a distal end **204** of the rasping head **190**. Tip **202** may terminate distally in-line with the chamfered tip of cutting element **216**. Alternatively, tip **202** may extend a distance distally beyond the distal most portion of the chamfered tip of cutting element **216**, for example, said distance may be from about 1.5 mm to about 2.5 mm, from about 2 mm to about 3.5 mm, from about 3 mm to about 4.75 mm, from about 4.25 mm to about 6 mm, from about 5 mm to about 6.75 mm, from about 5.5 mm to about 8 mm, from about 7.5 mm to about 10 mm, from about 9 mm to about 11.5 mm and from about 11 mm to about 15 mm which may permit placement of a tip **202** within the plane of the joint thereby aligning cutting elements **192** to project toward or into the bone of the sacrum or ilium. Each of the cutting elements **192** includes an inner surface **206** that faces the smooth surface texture **200**, an outer surface **208** opposite the inner surface **206** that is smooth and lies flush with the side edge **194**, and a top surface **210** that includes a cutting element feature **212** that includes a series of teeth **214**. A distal end of the cutting elements **192** includes a chamfered tip **216**. Additionally, the tooling head **52** of the present embodiment may have similar features as described in the previous embodiments. The dimensions of the present embodiment may be similar to that as described in reference to FIGS. **19A-19D**.

Such a tooling head **52** with a pair of cutting elements **192** may be used to perform dual keel-cuts in either or both of the ilium and sacrum for delivery of an implant with dual keels

22

such as described in U.S. patent application Ser. No. 14/447,612, filed Jul. 31, 2014 and entitled SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT, which is hereby incorporated by reference in its entirety. To prepare the sacroiliac joint for delivery of a dual keel implant, the tooling head **52** with the pair of cutting elements **192** may be inserted into the sacroiliac joint of a patient with the cutting elements oriented towards the ilium, for example, and the tooling head **52** may be advanced distally in the caudal region of the joint such that the cutting elements **192** cut into the boney surface of the ilium. Once at a far end of the caudal region, the tooling head **52** may be proximally withdrawn and repeated if desired. After sufficiently cutting into the ilium, the tooling head **52** may be withdrawn from the joint. Next, the tooling head **52** may be rotated one hundred and eighty degrees such that the cutting elements are oriented towards the sacrum. The tooling head **52** may then be advanced into the sacroiliac joint and make keel-cuts into the sacrum as described previously with reference to the ilium. Once the tooling head **52** is removed from the joint, the implant may then be delivered into the joint such that the implant keels are positioned within the keel-cuts made with the cutting elements **192** of the tooling head **52**.

Continuing on, reference is made to FIGS. **22A-22D**, which depict a tooling head **52** with a planar rasping head **190** at a distal end **204** of the tooling head **52** that includes a pair of perpendicularly extending cutting element **192**. This embodiment includes similar features to the tooling head **52** described in reference to FIGS. **21A-21C**, except that the present embodiment includes a rasping surface **218** instead of a smooth surface on the top and bottom surface **196**, **198** of the rasping head **190**. The rasping surface **218** may be as described previously and may include a series of ridges **220** in a chevron pattern. A planar rasping head **190** of this embodiment may be useful for simultaneously rasping the intra-articulating surfaces of the sacroiliac joint to remove cartilage or abrade the boney surfaces and make dual keel-cuts into either the sacrum or the ilium for the subsequent delivery of an implant having similarly featured keels.

Reference is now made to FIGS. **23A-23D**, which depict a tooling head **52** with a box osteotome head **222**. As seen in the figures, the box osteotome head **222** includes a planar top member **224**, a planar bottom member **226** generally parallel to and opposite of the planar top member **224**, a pair of side members **228** that extend generally perpendicularly between the top and bottom members **224**, **226**, and a pair of coaxially aligned openings **230** in the top and bottom members **224**, **226**. In this embodiment, the openings **230** are bounded by four edges **236**; however, the configuration of the openings **230** may include a different number of edges **236** and shapes. The box osteotome head **222** defines a cavity **232** therein that is bounded by inner surfaces **242** of the top, bottom, and side members **224**, **226**, **228**. The cavity **232** is open on a distal end **234** of the box osteotome head **222**. A distal edge of the distal end **234** of each of the top, bottom, and side members **224**, **226**, **228** form a curved cutting edge **238** that includes an inward bevel **240** such that outer surfaces **244** of the members **224**, **226**, **228** extend further distally than the inner surfaces **242**.

As seen in the figures, the tooling head **52** additionally includes a shaft **246** that is four-sided, a handle **248** coupled to a proximal end **250** of the shaft **246**, and an impact plate **252** at a proximal end **254** of the handle **248**. The tooling head **52** of this embodiment may additionally include features as described in the previous embodiments without limitation.

23

The box osteotome head **222** may be useful in a surgical procedure where a section of bone or cartilage is to be removed. The box osteotome head **222** may be distally advanced into the sacroiliac joint and bone and/or cartilage in contact with the cutting edge **238** will be cut and urged via the inward bevel **240** within the cavity **232**. After an appropriate cut has been made, the box osteotome head **222** may be proximally removed from the joint space and the biological material within the cavity **232** may be removed through one or both of the coaxially aligned openings **230** in the top and bottom members **224**, **226**. The box osteotome head **222** may be used with the joint preparation tool **50**, as described previously, or independently.

As seen in FIG. **23A**, the box osteotome head **222** may include a width **W23** in a range of about 13 mm to about 19 mm. In certain instances, the width **W23** may be 13 mm, 16 mm, or 19 mm. As seen in FIG. **23B**, the box osteotome head **222** may include a thickness **T23** between the outer surfaces **244** of the top and bottom members **224**, **226** in a range of about 5 mm to about 7 mm. In certain instances, the thickness **T23** may be 5 mm, 6 mm, or 7 mm.

With reference to FIG. **23C**, the shape of cavity **232** may generally match the shape of the implant which may be subsequently implanted into the void created by the head **222**. In certain aspects, the cross sectional shape and dimensions of the cavity **232** may substantially match the corresponding cross sectional shape and dimensions of the implant to be implanted at the joint in the void created by head **222**.

B. Joint Preparation Tool with Anchoring Arm

Reference is now made to FIG. **24A**, which is a side view of a first embodiment of a joint preparation tool **256** attached to an anchoring arm assembly **258**. The anchoring arm assembly **258** may be similar to as described in U.S. patent application Ser. No. 14/447,612, mentioned previously, and hereby incorporated by reference in its entirety. The joint preparation tool **256** may be similar to those described previously and may include a tooling head **260** as also described previously. As seen in FIG. **24A**, the tooling head **260** includes a rasping head **284** with a pair of perpendicularly extending cutting elements **262** extending from side edges of the head **260**. The tooling head **260** is attached to a handle **286** at a proximal end of the tool **256**. Regarding the anchoring arm assembly **258**, it includes an extension member **264** that extends from the joint preparation tool **256**. A distal portion of the extension member **264** includes a pair of guide collars **272** that are configured to securely support and position an anchoring tool **274**. The anchoring tool **274** includes a tubular shaft **276** that is secured within the guide collars **272** via a set screw **278**. The anchoring tool **274** further includes a rotationally engaged handle **280** at a proximal end of the tool **274** that is configured to rotationally extend and retract an anchoring element **282** that is coupled to a distal portion of the tool **274**. The anchoring arm assembly **258** is configured to orient the anchoring element **282** in a single orientation relative to the rasping head **284**. That is, the anchoring arm assembly **258** or, more particularly, the orientation of the guide collars **272** relative to the rasping head **284** is fixed and nonadjustable once the anchoring arm assembly **258** is affixed to the joint preparation tool. In this and other embodiments, the orientation of the anchoring element **282** may be such that, when delivered into the joint space, the anchoring element **282** will be positioned cranial (above) to the rasping head **284**, caudal (below) to the rasping head **284**, or in-line with and distally of the rasping head **284**.

24

Turning to FIG. **24B**, reference is made to a pre-assembled state of the joint preparation tool **256** and the anchoring arm assembly **258**. As seen in the figure, the extension member **264** is coupled to and extends from a sleeve **266** that includes a lumen extending therethrough. The sleeve **266** is configured to receive a shaft **268** of the joint preparation tool **256** through the lumen. The sleeve **266** may be secured to the joint preparation tool **256** by any type of fastening mechanism such as, for example, corresponding threading on the sleeve **266** and a proximal portion **270** of the shaft **268** of the tool **256**. The rasping head **284** may be fixed to the shaft **268** of the joint preparation tool **256** or the head **284** may be releasably coupled to the shaft **268**.

Moving on to another embodiment of a joint preparation tool **256** attached to an anchoring arm assembly **258**, reference is made to FIG. **25**. The joint preparation tool **256** is identical to the tool **256** of FIGS. **24A-24B**. The anchoring arm assembly **258** of the present embodiment is similar to the assembly **258** in FIGS. **24A-24B**, except that the assembly **258** in the present embodiment includes a trio of guide collars **272**. Each guide collar **272** is configured to orient a tool (not shown) in a specific trajectory **T1**, **T2**, **T3** relative to the rasping head **284** of the joint preparation tool **256**. **T1** may, for example, orient an anchoring tool, as described previously, to deliver an anchor element cranial to the rasping head **284**. **T2** may, for example, orient an anchoring tool to deliver an anchor element distally, in-line with the rasping head **284**. **T3** may, for example, orient an anchoring tool to deliver an anchor element caudal to the rasping head **284**. **T2** may alternatively orient an anchoring tool to deliver an anchor element in-line with and towards a central portion of the rasping head **284**. In such an orientation, the rasping head may include an opening (not shown) on its planar surface that extends proximally from a distal edge of the rasping head **284** such that the rasping head **284** is pronged or fork-shaped. While the anchoring arm assembly **258** is described as coupling to an anchoring tool that delivers an anchoring element that may be a screw, the assembly **258** may couple with other types of tools. For example, the guide collars **272** may couple with a syringe barrel that delivers a bone paste or other biomaterial into the joint space to facilitate fusion of the bony surfaces of the joint.

While the anchor arm assemblies **258** of the various embodiments are described with reference to a joint preparation tool with a shaft attached with a handle at a proximal end of the tool, the anchor arm assemblies **258** may be used with other embodiments of the joint preparation tool. For example, the anchor arm assemblies **258** may be coupled with the joint preparation tool **50** with the slap hammer assembly **54** as described previously.

In another aspect, for example as shown and described in U.S. Provisional Patent Application 61/860,185, the anchor arm assembly **258** may be provided in the form of two or more linked structural elements thereby providing an adjustable elongate shape. For example, anchor arm assembly **258** may be telescoping and may include a first section ending in the first arm end and a second section ending in the second arm end; both sections may have matched circular arc shapes with a common center.

For example, FIG. **56A** and FIG. **56B** are side views of a telescoping anchor arm assembly **258**. Referring to FIG. **56A**, the anchor arm assembly **258** may include a first section **4102** ending in a first arm end **3802** and a second section **4104** ending in a second arm end **3804**; both sections **4102** and **4104** may have matched circular arc shapes with a common center **4110** as illustrated in FIG. **56A**. In an aspect, the second section **4104** may

25

have a hollow cross-section with a central lumen (not shown), and the first section **4102** may be shaped and dimensioned to fit within the central lumen by sliding along the arc length of the second section **4104**, FIG. **56B** illustrates the anchor arm assembly **258** with a portion of the first section **4102** nested within the central lumen of the second section **4104**, resulting in a shorter elongate shape. The second section **4104** includes the second arm end **3804** as well as a sliding attachment fitting **4106** at an end of the second section **4104** opposite to the second arm end **3804**. The sliding attachment fitting **4106** may slide along the first section **4102** to adjust the relative position of the first arm end **3802** and second arm end **3804** as illustrated in FIG. **56B**. The elongate shape of the anchor arm assembly **258** and the sliding attachment fitting **4106** may be locked into a fixed position using a locking mechanism including, but not limited to, a set screw **4108** as illustrated in FIG. **56A**. Any other known locking mechanism may be used to lock the adjustable anchor arm assembly **258** into a locked position including, but not limited to clamps, pegs, compression fittings, and any combination thereof. In this aspect, the shorter elongate shape illustrated in FIG. **56B** may result in a change in the angle **4112** between the anchor element **18** and/or anchoring tool **274** and the implant **12** and/or tooling head **260**. The adjustability of the anchor arm assembly **258** may further facilitate fine-tuning the entry paths of the various components during formation of the implant assembly **14**, or delivery of the anchor element **18** relative to the tooling head **260**, to account for variability in patient morphology and/or to avoid injury to vulnerable tissues including, but not limited to, nerves and/or blood vessels.

In an aspect, the second section may have a hollow cross-section with a central lumen, and the first section may be shaped and dimensioned to fit within the central lumen by sliding along the arc length of the second section. A portion of the first section may be nested within the central lumen of the second section, resulting in a shorter elongate shape. The second section includes the second arm end as well as a sliding attachment fitting at an end of the second section opposite to the second arm end. The sliding attachment fitting may slide along the first section to adjust the relative position of the first arm end and second arm end. The elongate shape of the anchor arm assembly **258** and the sliding attachment fitting may be locked into a fixed position using a locking mechanism including, but not limited to, a set screw. Any other known locking mechanism may be used to lock the adjustable anchor arm assembly **258** into a locked position including, but not limited to clamps, pegs, compression fittings, and any combination thereof. In this aspect, the shorter elongate shape may result in a change in the angle between the anchor and/or anchor guide and the implant body and/or implant guide. The adjustability of the anchor arm assembly **258** may further facilitate fine-tuning the entry paths of the various components during placement of the one or more anchors to account for variability in patient morphology and/or to avoid injury to vulnerable tissues including, but not limited to, nerves and/or blood vessels.

In other aspects, the anchor arm assembly **258** includes a straight horizontal segment and a straight vertical segment. The vertical segment includes the second arm end as well as a sliding attachment fitting at an end of the vertical segment opposite to the second arm end. The sliding attachment fitting may slide in a horizontal direction along the horizon-

26

tal segment to adjust the relative position of the first arm end and second arm end. The position of the sliding attachment fitting may be locked into place using any known locking mechanism described previously above including, but not limited to, a set screw.

In various other aspects, the anchor arm assembly **258** may be made adjustable by the incorporation of any other adjustable elements known in the art. Non-limiting examples of suitable adjustable elements include: two or more hinged or jointed subsections of the anchor arm assembly **258**, two or more telescoping subsections of the anchor arm assembly **258**, one or more bendable subsections of the anchor arm assembly **258** having limited deformability, and any combination thereof. In other additional aspects, different sizes of fixed-geometry anchor arm assembly **258** may be used to provide a suitable range of installation tool geometries to account for differences in patient morphologies, differences in orthopedic surgical procedures, and any other variable factor governing the selection of an anchor arm assembly **258** geometry.

C. Joint Preparation Tool with Translating and Rotation Inhibiting Distal Handle Assembly

Reference is now made to FIG. **26A**, which is a side isometric view of a joint preparation tool **800** having a proximal handle **802** and a distal handle assembly **804** that is slideably attached to a shaft **806** of a tooling head **808**. The distal handle assembly **804** is configured to translate on the shaft **806** along a set trajectory that inhibits rotation of the handle assembly **804** relative to the proximal handle **802** and shaft **806**. The tooling head **808** may be similar to the various embodiments previously described and the joint preparation tool **800** may be configured to couple with any of the tooling heads described herein. In this embodiment, there is a cutting element **812** at a distal end **810** of the tooling head **808**. Referring to the distal handle assembly **804**, it includes a coupler member **816** that releasably secures to the shaft **806** of the tooling head **808**. Proximal to the coupler member **816** is a handle **818** that is coupled to the coupler member **816** via an adjustable socket assembly **820**.

With continuing reference to FIG. **26A**, the joint preparation tool **800** may be further configured to have an indicator **803** coupled to or integral with a component (e.g., the proximal handle **802**) of the joint preparation tool **800**. The indicator **803** may indicate a position or orientation of the cutting element **812** when the cutting element is positioned out of view of the surgeon (e.g., in a joint space). Alternatively, an indicator **803** may be fixed to a portion of the patient's skeleton to act as a reference during the course of the procedure. The indicator **803** may be configured as a body visible to a human user during the course of employing the joint preparation tool **800** or one of its components. Additionally, the body may be configured to be visible to a user while using fluoroscopy or CT scan (e.g., the body may comprise a material which is radiopaque) or be identifiable by an O-arm® Surgical Imaging System from Medtronic or similar device or a StealthStation® S7® surgical navigation system by Medtronic which has both optical and electromagnetic tracking options, or a StealthStation i7™ also by Medtronic. The indicator **803** may be used as a reference guide when directly viewed by the human user or when identified by a computer, surgical robot or imaging system. According to an aspect, the indicator **803** may be a reference array and may include 3 or 4 balls supported in a predetermined spaced apart arrangement and connected to one another by a frame. The frame may be coupled to a component of the tool **800** or may be separately coupled to a

portion of the patient's skeleton or may be coupled to a delivery tool **16** of a system **10**.

In another aspect, the indicator **803** may indicate the position of the cutting element **812** supported by the tooling head **808** when the tooling head **808** may be obscured from view by the patient's soft tissues, by the positioning of the tooling head **808** within the joint, or by aspects of the operating environment which may otherwise obfuscate the arrangement or position of elements of the various components of the joint preparation tool **800**. For example, the indicators **803** may be elongate cylinders extending radially from a proximal handle **802** (or shaft of a tooling head **806**) longitudinal axis and projecting towards one or more outer cutting blades. In an aspect, the indicators **803** (when coupled to the tool **800**) have a longitudinal axis which is parallel to a cutting element axis which is defined as being coincident with the tooling head axis and also coincident with a point along a tip of an outer cutting blade **856**.

As such, the indicator **803** may permit a surgeon to align an outer cutting blade with the bone of an ilium and a second outer cutting blade with the bone of the sacrum. Alternatively or additionally, an indicator **803** may permit a surgeon to align an outer cutting blade **856** to be generally in-line with a plane of a sacroiliac joint.

As seen in FIG. 26B, which is a cross-sectional view of the coupler member **816** of the distal handle assembly **804** and the shaft **806** of the tooling head **808**, the shaft **806** is hexagonal and includes six outer surfaces **840** that are configured to matingly slide within and against matching inner surfaces **814** of the coupler member **816**. The inner surfaces **814** of the coupler member **816** are hexagonal and sized slightly larger than the six outer surfaces **840** of the shaft **806** in order to facilitate sliding of the distal handle assembly **804** relative to the shaft **806**. As seen in the figure, the coupler member **816** includes two sections that are held together by fasteners (e.g., bolt, screw) **822**. In this way, the coupler member **816** is releasably secured to the shaft **806** via the fasteners **822**. And, when the coupler member **816** is secured to the shaft **806**, the coupler member **816**, along with the socket assembly **820** and the handle **818**, are in a fixed position relative to the tooling head **808** and the proximal handle **802**. That is, the distal handle assembly **804** may translate on the shaft **806** of the tooling head **808**, but the distal handle assembly **804** may not rotate relative to the shaft **806**.

In one aspect, coupler member **816** may be caused to disengage matching inner surfaces **814** from outer surfaces **840** of the shaft **806** such that rotation between shaft **806** and coupler member **816** may be permitted. For example, coupler member **816** may be distally displaced relative to shaft **806** such that surfaces **814** and **840** disengage and then coupler member **816** may be rotated relative to shaft **806** to a different desired position and then coupler member **816** may be proximally displaced relative to shaft **806** such that inner surfaces **814** reengage the outer surfaces **840**.

Reference is now made to FIG. 26C, which is an isometric front view of the joint preparation tool **800** with the distal handle assembly **804** in an exploded view. As seen in the figure, the socket assembly **820** is releasably secured to the coupler member **816** via a fastener **824** that is fitted within a passageway **826** through a socket member **828** of the socket assembly **820**. The fastener **824** may be threaded and may engage with corresponding threads in the coupler member **816**. The socket member **828** is coupled to the handle at a proximal end **830** of the socket member **828** and includes a socket opening **832** at a distal end **834** of the member **828**. The socket opening **832** leads to the passage-

way **826** and includes a six-sided inner surface **836** that may be engaged with a matching male-end of a six-sided member **838** on the coupler member **816**. As such, the socket member **828** may engage with and be secured to the six-sided member **838** in one of six orientations such that the handle **818** extends at differing orientations relative to the shaft **806** of the tooling head **808** and the proximal handle **802**. This adjustability may be useful for a surgeon to appropriately position the handle **818** for a particular surgical procedure.

The present embodiment of the joint preparation tool **800** with a translating and rotation inhibiting distal handle assembly **804** may be useful to prevent inadvertent rotating of the cutting element **812** out of a desired cutting trajectory. For example, since the ilium is generally a harder bone than the sacrum, there may be a tendency for the cutting element **812** to deflect from being driven into the ilium by twisting into the joint space where this is less resistance. Such twisting of the tooling head **808** may be damaging to the patient and may inaccurately prepare the joint surfaces for fusion.

In operation, the cutting element **812** at the distal end **810** of the tooling head **808** may be distally driven into a joint (e.g., sacroiliac joint) while a surgeon controls the trajectory of delivery. More particularly, a surgeon may grasp the handle **818** of the distal handle assembly **804** with one hand and the proximal handle **802** with the other hand. At this initial stage, the joint preparation tool **800** may be oriented as shown in FIG. 26A, which depicts the distal handle assembly **804** in a distal position. The surgeon may then urge the proximal handle **802** distally while maintaining a stabilizing force on the distal handle assembly **804**. As the cutting element **812** is urged into the joint, the distal handle assembly **804** may displace proximally relative to the shaft **806** of the tooling head **808** as the surgeon maintains the stabilizing force on the assembly **804**. At this stage of the procedure, the joint preparation tool **800** may be oriented as shown in FIG. 26D, which depicts the distal handle assembly **804** in a proximal position. In this way, the stabilizing force exerted on the distal handle assembly **804** ensures that the cutting element **812** is not caused to inadvertently rotate out of alignment during the delivery of the head **808** into the joint space.

Additionally, the coupler member may house a brake shoe which in turn may carry a brake block or pad. The brake shoe may be coupled to a brake caliper. The brake caliper may be manipulated by a user acting upon a lever which may be configured with an ergonomic lever handle and which may be coupled to the distal handle assembly **804**. Such a braking system may resist longitudinal and rotational forces between shaft **806** and coupler member **816**.

Moving on, reference is made to FIG. 26E, which is an up-close side view of the cutting element **812**. As seen in the figure, the cutting element **812** includes a central cutting blade or central guide **842** and a pair of outer cutting blades **844**. The cutting element **812** also includes a front and back wall member **846** that extends between and couples the outer cutting blades **844** with the central cutting blade **842**. The front and back wall members **846** may include a distal beveled edge **848** extending between the outer cutting blades **844**.

Referring to FIG. 26F, which is a cross-sectional side view of the cutting element **812**, it can be seen that the shaft **806** of the tooling head **808** tapers into the central cutting blade **842**. In between opposite sides of the central cutting blade **842** and the outer cutting blades **844** are passageways **850** that extend from the distal beveled edge to a proximal edge **852** of the cutting element **812**. In operation, as the

cutting element **812** is distally advanced within a joint space articular cartilage and/or bone may be cut with the distal beveled edge **848** and the central and outer cutting blades **842**, **844** such that the severed bone/cartilage is caused to funnel through the passageway **850** to make way for additional bone/cartilage to be cut.

Such a cutting element **812** may be oriented within the joint plane or perpendicular to the joint plane. When oriented perpendicular to the joint plane, one of the outer cutting blades **844** may be positioned to cut the ilium and one of the outer cutting blades **844** may be positioned to cut the sacrum while the central cutting blade is positioned within the plane of the joint. Thus, as the tool **800** is distally advanced the cutting element **812** may make keel cuts into the sacrum and the ilium. The distal handle assembly **804**, as discussed previously, may be useful to provide a stabilizing force that ensure the cutting element **812** does not inadvertently twist or rotate given the differences hardness of the sacrum and ilium.

The cutting element **812** may be modified, as in FIG. 26G, to include an elongated central cutting blade **842**. Such a cutting element **812** may be useful when the cutting element is oriented perpendicular to the joint plane, as described previously, in that the elongated central cutting blade **842** may urge the cutting element **812** to stay within the joint plane as opposed to easily cutting into one of the boney surfaces of the joint. The tip **854** of the elongated central cutting blade **842** may be blunt to further urge the central cutting blade **842** to remain within the joint plane.

As seen in FIG. 26G, sample dimensions of the cutting element **812** may be as follows. The outer cutting blades may extend a distance D4 from the distal edge **848** to a distal tip **856** of about 0 mm to about 1.75 mm, from about 1.5 mm to about 2.5 mm, from about 2 mm to about 3.5 mm, from about 3 mm to about 4.75 mm, from about 4.25 mm to about 6 mm, from about 5 mm to about 6.75 mm, from about 5.5 mm to about 8 mm, from about 7.5 mm to about 10 mm, from about 9 mm to about 11.5 mm, and from about 11 mm to about 13 mm. In certain embodiments, the distance D4 may be about 1 mm, 3 mm, or 5 mm. The elongated central portion **842** may extend a distance D5 from the distal edge **848** to the tip **854** of about 3 mm to about 4.75 mm, from about 4.25 mm to about 6 mm, from about 5 mm to about 6.75 mm, from about 5.5 mm to about 8 mm, from about 7.5 mm to about 10 mm, from about 9 mm to about 11.5 mm, from about 11 mm to about 13 mm, and from about 12.5 mm to about 15 mm. In certain embodiments, the distance D5 may be about 5 mm, 6.5 mm, or 8 mm. The elongated central portion **842** may extend a distance D6 beyond that of the distal tips **856** of the outer cutting blades by about 3 mm to about 15 mm. In certain embodiments, the distance D6 may be about 5 mm, 6.5 mm, or 8 mm. A distance D7 between the distal and proximal edges **848**, **852** may be about 1.5 mm to about 2.25 mm, from about 2 mm to about 3.5 mm, from about 3 mm to about 4.75 mm, from about 4.25 mm to about 6 mm, from about 5 mm to about 6.75 mm, from about 5.5 mm to about 8 mm, from about 7.5 mm to about 10 mm, from about 9 mm to about 11.5 mm, from about 11 mm to about 13 mm, and may even range up to 40 mm-60 mm. In certain embodiments, the distance D7 may be 3.5 mm, 7.5 mm, 15 mm, 30 mm 40 mm or 45 mm. A distance D8 may be defined between one of the outer cutting blades **844** and the elongated central cutting blade **842**. D8 may be in a range of about 2.25 mm to about 2.75 mm, from about 2 mm to about 3.5 mm, from about 3 mm to about 4.75 mm, from about 4.25 mm to about 6 mm, from about 5 mm to about 6.75 mm, from about 5.5 mm to about 8 mm, from about 7.5

mm to about 10 mm, from about 9 mm to about 11.5 mm, from about 11 mm to about 13 mm. In certain embodiments, the distance D8 may be about 6 mm, 8 mm, or 10 mm.

While the cutting element is shown in FIGS. 26E-26G as including a certain configuration of cutting blades, other arrangements are possible and contemplated herein. For example, a cutting element **812** may include serrated cutting blades and may include additional or fewer cutting blades than are depicted in the figures. In one aspect, there may be four passageways **850** arranged into two pairs. The first pair may be arranged such that the first and second passageways are positioned and aligned relative to one another similar to the configuration in FIGS. 26F-26G such that a back wall member **846** of the first passageway is generally coplanar with a back wall member **846** of the second passageway and forming a first plane. The second pair of passageways **850** may also have a relationship between each of the second pair passageways **850** similar to the first and second passageways of the first pair of passageways such that a back wall member **846** of the first passageway of the second pair is generally coplanar with a back wall member **846** of the second passageway of the second pair and forming a second plane. The second pair of passageways may be arranged relative to the first pair of passageways such that the first plane formed by the first pair of back wall members is generally perpendicular to the second plane formed by the second pair of back walls.

D. Trial Fit Preparation Tool with Trial Fit Implant and Cutting Tool with Translating Cutting Element

The discussion of preparing the sacroiliac joint, among other joints, for implant delivery will now focus on additional tools that may be used independently from or in combination with the previously mentioned tools.

1. Trial Fit Assembly and Cutting Tool with Offset Shafts

To begin, reference is made to FIG. 27, which is an isometric side view of a joint preparation tool assembly **300** that is configured to test-fit an implant size and make a transverse cut into either or both the sacrum and ilium to make way for a keel of an implant that is configured to extend into the bone. As seen in the figure, the joint preparation tool assembly **300** includes a trial tool assembly **302** and a cutting tool **304** that is configured to translate relative to the trial tool assembly **302** in order to make the transverse keel-cuts into the patient's bone.

The trial tool assembly **302** includes an implant trial **306** at a distal end **308** of the assembly **302**. The implant trial **306** is a planar member with a tapered tip **310** that includes a width **312** that corresponds with a width of an implant that may be subsequently delivered into a joint. The implant trial **306** may be removably coupled with a shaft **314** that extends proximally. The shaft **314** is removably attached to a handle assembly **316** at a proximal end **318** of the shaft **314**. The handle assembly **316** includes a coupler **320** configured to removably attach to the shaft **314** of the trial tool assembly **302**. The coupler **320** is attached to a handle shaft **410** that extends to a gripping handle **322**.

As mentioned previously, the implant trial **306** is used to gauge the size of the joint space so that an implant size may be chosen that best fits the joint space. Thus, the system described herein may include implant trials **306** of various sizes and configurations in order to gauge the size of the joint space. In operation, a surgeon may begin a surgical procedure by test-fitting the smallest size of implant trial **306** into the patient's joint to determine the fit. If the size of the implant trial **306** is too small, then the surgeon may remove the implant trial **306** and deliver a larger size implant trial **306** into the joint. Once an appropriate size of implant trial

31

306 is received within the joint, the surgeon may use the cutting tool 304 to deliver transverse keel-cuts into the boney surfaces in preparation for the implant delivery.

The cutting tool 304 is slidably coupled to the shaft 314 of the trial tool assembly 302 and configured to slide distal-proximal on the shaft 314. The cutting tool 304 is slidably coupled to the shaft 314 via a distal and a proximal collar 324 that extend around the shaft 314 of the trial tool assembly 302. The collars 324 are separated by a gap and are attached to a cutting tool shaft 326 that extends proximally. The cutting tool shaft 326 includes a curved mid-portion 328 such that the shaft 326 angles away from the shaft 314 of the trial tool assembly 302. A proximal end 330 of the cutting tool shaft 326 includes an impact plate 332 that is configured for being hit with a hammer or similar device to drive the cutting tool 304 distally. In this way, the surgeon may securely hold the handle 322 of the trial tool assembly 302 with one hand and strike the impact plate 332 with the other hand.

Reference is now made to FIG. 28, which is an isometric view of an opposite side of the joint preparation tool assembly 300. As seen in the figure, a distal end 334 of the cutting tool 304 includes a cutting element 336 that extends within a guide 338 formed in a top surface 340 to the tapered tip 310 of the implant trial 306 when the cutting element 336 translates relative to the implant trial 306. A distal tip 344 of the cutting element extends to the tapered tip 310 of the implant trial 306 when the shaft 326 of the cutting tool 304 abuts a proximal end 346 of the implant trial 306. The cutting tool 304 is configured to maintain an orientation relative to the guide 338 when the cutting element 336 is proximally retracted or distally extended towards the guide 338 via a channel 342 formed in the shaft 314 of the trial tool assembly 302.

For a detailed discussion of the cutting tool 304, reference is made to FIGS. 29-30, which are isometric views of the cutting tool 304. As seen in FIG. 29, the cutting tool 304 includes a protrusion 348 on each inner surface 350 of the collars 324 that extend around the shaft 314 of the trial tool assembly 302. The protrusion 348 is configured to fit within the channel 342 formed in the shaft 314 of the trial tool assembly 302 such that the shaft 314 cannot rotate when the protrusion 348 is fitted within the channel 342. Reference is now made to FIG. 30, which is a close-up view of the distal end 334 of the cutting tool 304. As seen in this figure, the protrusion 348 is semi-hemispherical and extends a length of the collars 324. Other shapes for the protrusion 348 are possible and contemplated herein.

Turning to the distal end 334 of the cutting tool 304 and still referring to FIG. 30, the cutting element 336 is a six-sided, box-type chisel with planar outer surfaces 360 that distally terminates in a beveled cutting edge 362 that forms a distal opening 364 that extends to lumen extending through the cutting element 336. While this embodiment of the cutting element 336 includes a six-sided, box-type chisel, other arrangements and designs of cutting tool elements 336 are contemplated herein. For example, a rectangular, box-type chisel, knife blade, or saw may be used without departing from the teachings of the disclosure.

Continuing with FIG. 30, the cutting element 336 further includes a cutting element guide 352 that extends off of the cutting element 336 and extends just proximally from the distal tip 334 of the cutting element 336 to a proximal end 354 of the cutting element 336. The cutting element guide 352 includes a rounded head 356 and a neck 358 that is thinner than a widest part of the head 356. Alternatively, cutting element guide 352 and guide channel 366 may have

32

complementary dovetail or flaring tenon and mortise configurations. As seen in FIG. 31, which is an isometric view of the cutting element 336 and implant trial 306 with a cross-section at the proximal end 354 of the cutting element 336, the cutting element guide 352 is received within a guide channel 366 that is a corresponding shape to that of the cutting element guide 352. In particular, the guide channel 366 includes a neck region 368 and a head region 370 that are only slightly larger than the corresponding neck 358 and head 356 of the cutting element guide 352. The guide channel 366 extends from a proximal surface 372 to a distal surface 374 of the implant trial 306. In this way, as the cutting tool 304 and, more particularly, the cutting element 336 are translated distally, the cutting element guide 352 is received within the guide channel 366, which ensures that the cutting element 336 remains within the guide 338 on the top surface 340 of the implant trial 306 during a cutting operation. Stated differently, the guide channel 366 prevents rotation and other errant movement of the cutting element 336 during a cutting operation such that the cutting element 336 remains reliably within the guide 338 to perform repeatable and accurate cuts into the patient's bone.

Still referring to FIG. 31 and also extending through the implant trial 306 from the proximal surface 372 to a distal surface 374 is a bore 376 that is configured receive a guidewire or similar device to guide the implant trial 306 into a joint space, for example. As best seen in FIGS. 32-33, which are respective front and back views of the implant trial 306, both the bore 376 and the guide channel 366 extend through the implant trial 306 parallel to a longitudinal axis of the implant trial 306. While shown in the figures as generally linear, the longitudinal axis of the implant trial 306 may be curved and may further include an arcuate portion with a radius between from about 3 cm and about 6 cm and may be about 2 cm, 2.5 cm, 3 cm, 3.5 cm, 4 cm, 4.5 cm, 5 cm, 5.5 cm, 6 cm, 6.5 cm and 7 cm. In one aspect, while shown in the figures as generally linear, the guide channel 366 may be curved and may further include an arcuate portion with a radius that matches the curved implant trial 306. The radius of the arcuate portion of the guide channel 366 may be between from about 3 cm and about 6 cm and may be about 2 cm, 2.5 cm, 3 cm, 3.5 cm, 4 cm, 4.5 cm, 5 cm, 5.5 cm, 6 cm, 6.5 cm and 7 cm. In another aspect, while shown in the figures as generally linear, the implant trial 306 may be curved and may further include an arcuate portion with a radius between from about 3 cm and about 6 cm and may be about 2 cm, 2.5 cm, 3 cm, 3.5 cm, 4 cm, 4.5 cm, 5 cm, 5.5 cm, 6 cm, 6.5 cm and 7 cm. In yet another aspect, the implant trial 306 and the guide channel 366 may both include a matching radius.

Still referring to FIGS. 32-33, while the guide 338 is centered between opposite side surfaces 378 of the implant trial 306, the bore 376 and the head region 370 of the guide channel 366 are offset from a center point between the opposite side surfaces 378. As seen in the figures, the guide 338 is an extrusion with a bottom surface 380 that is generally perpendicular to a pair of side surfaces 382. The bottom surface 380 adjoins one of the side surfaces 382 to form a perpendicular angle between the two surfaces while the opposite pair of surfaces are transected by the guide channel 366 extending about one hundred and thirty-five degrees from each of the bottom surface 380 and the side surface 382.

Reference is now made to FIG. 33 and the proximal end 346 of the implant trial 306. As seen in the figure, the channel 342 in the shaft 314 of the trial tool assembly 302 mirrors a portion of the circumference of the bore 376

extending through the implant trial 306. In this way, the trial tool assembly 302 may be delivered into a sacroiliac joint, or other joint, of a patient by way of a guidewire (not shown) being received through the bore 376 of the implant trial 306 which was previously delivered into the joint. The channel 342 in the shaft 314 provides a passageway for the guidewire when the trial tool assembly 302 is advanced into the joint. Subsequently, when it is appropriate to use the cutting tool 304 with the trial tool assembly 302, the channel 342 provides the function of guiding the cutting tool 304 in an appropriate orientation by aligning the protrusion 348 within the collars 324 of the cutting tool 304 within the channel 342 of the shaft 314 of the trial tool assembly 302.

As seen in FIGS. 43E and 43F, the implant trial 306 may have a locking means which reversibly secures the trial 306 within the joint during certain steps in the procedure. For example, the proximal surface 372 of the implant trial 306 may have at least one passageway 307 which communicates with either a top or bottom surface 340 which is configured to receive an anchoring member 305 which may be proximally acted upon to reversibly transition from a recessed condition to a deployed condition. The recessed condition, as seen in FIG. 43E, is such that the anchoring member 305 is recessed within the passageway 307 or simply not extending beyond the top surface 340 and thereby not engaging a bone defining the joint and thereby not preventing movement of the implant trial 306 relative to the joint. The deployed condition, as seen in FIG. 43F, is such that the anchoring member 305 projects out of the passageway 307 from the top surface 340 thereby engaging a bone of the joint which may prevent or at least limit the movement of the implant trial 306 during the course of the procedure. The anchoring member 305 may be a spike, pin, dart, screw or other suitable locking or restraining member.

As further seen in FIG. 34, which is a front view of the trial tool assembly 302, an outer surface 384 of the shaft 314 of the trial tool assembly 302 lies flush with one of the outer surfaces 378 of the implant trial 306. As discussed previously, the proximal end 318 of the shaft 314 is configured to engage with a handle assembly 316. To facilitate the coupling of the shaft 314 and the handle assembly 316, the shaft 314 includes a notch or indent 386 within the outer surface 384 of the shaft 314. Proximally from the notch 386 is a stop feature 388 that defines a partial planar resection or flattening 390 of the outer surface 378 of the shaft 314.

For a discussion of the engagement of the handle assembly 316 with the shaft 314, reference is made to FIG. 35, which is a cross-sectional isometric view of the handle assembly 316 and the proximal end 318 of the shaft 314. As seen in the figure, the coupler 320 includes a cylindrical sidewall 404 and a flat impacting end 412 at a proximal end 414 of the coupler 320. Opposite the proximal end 414, a distal end 394 of the coupler 320 includes an opening 392 that is configured to receive the proximal end 318 of the shaft 314. The opening 392 includes a passageway that extend partially through the coupler 320 and includes a proximal inner surface 396 that is sized slightly larger than the proximal end 318 of the shaft 314. The inner surface 396 includes a planar inner surface portion 398 that matches the planar surface 390 of the shaft 314 such that when the shaft 314 is inserted into the opening 392, the planar surface 390 of the shaft 314 lies flush and opposed with the planar inner surface 398 of the opening 392 in a single orientation. When the shaft 314 is fully inserted into the opening 392, the stop feature 388 abuts a corresponding feature 400 on the inner surface 396 of the opening 392, which prevents further extension of the shaft 314 into the opening 392. Also, when

the stop feature 388 abuts the corresponding feature 400, the notch 386 is aligned with a lock feature 402 that extends through a bore in the cylindrical sidewall 404 of the coupler 320. The lock feature 402 includes a tubular member that is configured to extend through the sidewall 404 and into the notch 386 while still being partially positioned in the sidewall 404 in order to lock the shaft 314 in place relative to the coupler 320. The lock feature 402 may be engaged and disengaged from within the notch 386 by activation of a set screw 406 or similar mechanism. In this embodiment, the set screw 406 is maintained within the sidewall 404 of the coupler by a retainer 408 that inhibits movement of the set screw 406 from full retraction outside of the sidewall 404. The function of the lock feature 402 and the set screw 406 may be accomplished with many different mechanisms and methods. For example, the set screw 406 may be substituted for a mechanical switch that forces the lock feature 402 into the notch 386 when the switch is engaged. This and other such mechanisms are possible and contemplated by this disclosure.

Turning now to FIGS. 36A-36B, reference is made to another embodiment of the cutting tool 304. As seen in FIG. 36A, the cutting tool 304 include a similar shaft 326 with a curved mid-portion 328, distal and proximal collars 324 for receiving a shaft of a trial tool assembly, and an impact plate 332 at a proximal end 330 of the cutting tool 304 as described with reference to the previous embodiment of the joint preparation tool assembly 300. The present embodiment differs, however, from the previously described embodiment of the joint preparation tool assembly 300 in that it includes a saw-blade type cutting element 416 at a distal end 334 of the cutting tool 304. Referring to FIG. 36B, which is a close-up isometric view of the distal end 334 of the cutting tool 304, the cutting element 416 extends from a planar distal surface 418 of the tool 304 and includes opposite side surfaces 420, a bottom surface 422, and a top surface 424 that includes a series of teeth 426 arranged in a saw tooth shape that is configured to cut during a distal extension of the cutting tool 304. The series of teeth 426 extend generally perpendicularly from a top surface 430 of the shaft 326. At a distal end 334 of the cutting tool 304, the top surface 424 of the cutting element 416 tapers towards the bottom surface 422 to form a rounded, tapered distal tip 428.

In certain embodiments of the cutting tool 304, the cutting element 416 may include a width W416 between the opposite side surfaces within a range of about 1 mm to about 1.25 mm, from about 1 mm to about 1.75 mm, from about 1.5 mm to about 2.25 mm, from about 2 mm to about 2.75 mm, from about 2.5 mm to about 3 mm, from about 2.75 mm to about 4.25 mm, from about 4 mm to about 5 mm, from about 4.75 mm to about 6 mm, from about 5.75 mm to about 7 mm, and from about 6.5 mm to about 7.5 mm. In certain instances, the width W416 may be about 1.5 mm, 1.75 mm, 2 mm, 2.75 mm, 3 mm or 3.5 mm X. In certain embodiments, the cutting element 416 may include a length L416 from the planar distal surface 418 to the tapered distal tip 428 within a range of about 10 mm to about 15 mm, from about 13 mm to about 20 mm, from about 17.5 mm to about 30 mm, from about 25 mm to about 37.5 mm, from about 35 mm to about 40 mm, from about 37 mm to about 50 mm. In certain instances, the length L416 may be about 27 mm, 30 mm, 37 mm, or 40 mm. In certain embodiments, the cutting element may include a height H416 from the bottom surface 422 to the series of teeth 426 within a range of about 2.25 mm to about 2.65 mm, from about 2.5 mm to about 3 mm, from about 2.75 mm to about 4.25 mm, from about 4 mm to about 5 mm, from about 4.75 mm to about 6 mm, from about 5.75 mm to

about 7 mm, from about 6.5 mm to about 7.5 mm, from about 7 mm to about 8.75 mm, from about 8.5 mm to about 9.75 mm and from about 9.5 mm to about 11.25 mm. In certain instances, the height H416 may be about 3.25 mm, 4 mm, 4.5 mm, 5 mm or 5.25 mm.

The cutting tool **304** of FIGS. **36A-36B** is configured to be used with the trial tool assembly **302** as described previously. The cutting tool **304** in FIGS. **36A-36B** may be useful, for example, in making a keel-cut into either the sacrum or the ilium after the implant trial of the trial tool assembly is delivered non-transversely into the sacroiliac joint. Since the cutting element **416** extends generally perpendicular from the shaft **326** of the cutting tool **304**, when the implant trial is positioned non-transversely within the sacroiliac joint, the series of teeth **426** will be oriented generally perpendicularly to the sacrum/ilium such that a distal extension of the cutting tool **304** will provide a cut into the bone that may match a keel or wing member of an implant to be subsequently implanted into the joint space.

Reference is now made to FIGS. **36C-36E**, which depict an alternative implant trial **306** and cutting element **416**. As seen in FIG. **36C**, the cutting element **416** may include interconnected teeth **764** forming a chain that are configured to rotate around a portion of the implant trial **306**. The interconnected teeth **764** may be segmented into individual teeth **764** and each segmented tooth **764** may be in-line and linked with one another via rivets **766** or similar mechanisms. The interconnected teeth **764** may be configured similar to a tooth on a chainsaw and dimensioned as herein described, however, the overall length of each tooth **764** will be a fraction of the total length L416 of the cutting element segment assembly. For example, if the assembly comprises three teeth **764**, then the length of each tooth will be approximately one third of the overall length L416 of the cutting element segment assembly. In an aspect, an assembly comprises fifteen teeth **764** with each tooth approximately 2 mm in length. In one aspect, the teeth **764** are configured similar to chipper teeth or an OREGON no. 10 chipper chain, one of many STIHL saw chains or even a full-chisel chain. In other aspects, the teeth **764** may be configured as other linked-chains known in the art.

The interconnected teeth **764** may be configured to rotate through a portion of a length of the implant trial **306** such that a portion of the teeth **764** extend above a top surface **768** of the implant trial **306**. Thus, in operation and during rotation, the interconnected teeth **764** are configured to deliver a cut (e.g., keel-cut) into a joint bone when the implant trial **306** is positioned within a joint space. The interconnected teeth **764** opposite the top surface **768**, may extend outward from a bottom surface of the implant trial **306** such that rotation of the interconnected teeth **764** delivers simultaneous cuts to opposing bones in a joint space. Or, alternatively, the teeth **764** opposite the teeth **764** on the top surface **768** may remain housed within a passageway within the body of the implant trial **306** such that the teeth **764** only contact a joint bone that opposes the top surface **768**.

Referring to FIG. **36D**, which is a top view of an implant trial **306** that is suitable for use with the cutting element **416** described previously, the implant trial **306** may include a first guide or channel **338** formed in the top surface **768** and a second guide or channel (not shown) formed in the bottom surface of the implant trial **306**, which is opposite the top surface **768** and not shown in FIG. **36D**. And, at a distal end **774** of the implant trial **306**, there may be a passageway **770** communicating between implant trial top and bottom surfaces **768**. The passageway **770** may be configured and

dimensioned to receive the interconnected teeth **764** as they run distal-proximal along the first and second guides **338** through the passageway **770**. Such a configuration of the interconnected teeth **764** with the implant trial **306** having a passageway **770** at the distal end **774** may permit use of a rotating chain of teeth while protecting a patient's tissue that is distal to the distal end **774** of the implant trial **306**.

Referring now to FIG. **36E**, which is an isometric view of an arcuate implant trial **306** coupled with a shaft **780**, the teeth **764** may be linked together such that they pivot relative to one another with a pivot axis which is generally perpendicular to the length of the trial guide **338** and perpendicular to the top surface **768** of the implant trial **306**. Such a configuration would permit a saw chain of interconnected teeth **764** to travel an arcuate path via an arcuate trial guide path **772** formed on a generally planar implant trial top surface **768** where the opposite side surfaces **776** of implant trial **306** are curved and have a radius of approximately 2 cm to about 8 cm. In this arrangement a cutting tip of the interconnected teeth **764** remains oriented perpendicular to the top surface **768** of the implant trial **306**; however, the orientation of the pivot **766** is altered from the previous embodiment. As described previously, the interconnected teeth **764** may travel along the arcuate trial guide path **772** until the teeth **764** enter the passageway **770** at the distal end **774** of the implant trial **306**. The teeth **764** may then exit the passageway **770** and travel proximally on the arcuate trial guide path **772** formed on the bottom surface **778** of the implant trial **306**. In this arrangement, the interconnected teeth **764** may include an additional pivot **766** oriented generally perpendicular to the previously described pivot **766** such that the additional pivot **766** enables movement of the chain of interconnected teeth **764** to travel through the passageway **770**. Alternatively, the implant trial **306** may not include a passageway **770** and the teeth **764** may simply translate distally-proximally within the guide paths **772**.

Other cutting elements **416** are possible and contemplated herein. For example, the cutting element **416** may include a serrated or smooth knife blade. And, the joint preparation tool assembly **300** may include a series of cutting tools **304**, each cutting tool **304** with progressively larger (e.g., wider) blades that may or may not be used in succession to make larger and larger cuts until a desired cut size is made for subsequent implant delivery.

2. Trial Fit Assembly and Cutting Tool with Coaxially Aligned Shafts

Turning now to another embodiment of a joint preparation tool assembly **450**, reference is made to FIG. **37**. As seen in the figure, the joint preparation tool assembly **450** includes a trial tool assembly **452** and a cutting tool **454** that translates on a shaft **456** of the trial tool assembly **452**. The cutting tool **454** includes a tubular shaft **458** having an outer surface **460**, an inner surface **462**, and a hollow interior space **464**. The tubular shaft **458** also includes a series of apertures **466** extending from the outer surface **460** to the inner surface **462** of the shaft **458**. The apertures **466** provide for easier and improved steam cleaning compared with a tubular shaft without apertures. The apertures **466** also reduce weight of the assembly **450**, among other benefits. The tubular shaft **458** or, more particularly, the hollow interior space **464** is configured to receive the shaft **456** of the trial tool assembly **452** such that the shafts **456**, **458** are coaxially aligned. At a proximal end **468**, the cutting tool **454** includes a handle **470**. At a distal end **472**, the cutting tool **454** includes a cutting element **474**, which, in this embodiment, is a box-type chisel as described previously.

Regarding the trial tool assembly 452, the assembly includes an implant trial 476 at a distal end 478 of the assembly. As seen in FIG. 38, which is an isometric view of the cutting tool 454 and the trial tool assembly 452 in an uncoupled state, it can be seen that the trial tool assembly 452 is similar to and may include the same or different features of the joint preparation tool assembly 300 discussed previously in FIGS. 27-35. That is, the trial tool assembly 452 includes the implant trial 476 at the distal end 478 of the assembly, a guide 480 on a top surface 482 of the implant trial 476, and a guide channel 484 that is configured to guide the cutting element 474 during translation of the cutting element 474 within the guide 480 of the implant trial 476.

To couple the trial tool assembly 452 and the cutting tool 454, the shaft 456 of the trial tool assembly 452 is received through a pair of collars 486 on the cutting tool and is translated proximally such that the shaft 456 is received within the tubular shaft 458 of the cutting tool 454. As seen in FIG. 38, the cutting tool 454 includes a protrusion 488 within each of the collars 486 that fit within a corresponding channel 490 formed within an outer surface 492 of the shaft 456 of the trial tool assembly 452. The interaction of the protrusion 488 and the corresponding channel 490 ensures that the trial tool assembly 452 maintains its orientation relative to the cutting tool 454 during distal-proximal movement. As the trial tool assembly 452 is proximally retracted within the tubular shaft 458 of the cutting tool 454, a cutting guide element 494 of the cutting tool 454 will engage with and be received within the guide 480 of the implant trial 476. The interaction of the cutting guide element 494 and the guide 480 and guide channel 484 further ensures that the orientation of the cutting tool 454 and the trial tool assembly 452 will be maintained during a cutting stroke of the cutting tool 454 during a surgical procedure.

3. Trial Fit Assembly, Cutting Tool, and Trial Impact Rod with Coaxially Aligned Shafts

Turning now to another embodiment of a joint preparation tool assembly 500, reference is made to FIG. 39, which depicts the individual components of the assembly 500 in an uncoupled state. As seen in the figure, the joint preparation tool assembly 500 includes a trial tool assembly 502, a trial impact rod assembly 504, a handle assembly 506, and a cutting tool 508.

In one aspect, the trial impact rod assembly 504 is configured to be used in conjunction with the trial tool assembly 502 to provide stability during delivery of a distal end 510 of the trial tool assembly 502 into a joint of a patient. In particular, slidable coupling of the trial impact rod assembly 504 and the trial tool assembly 502 adds stability and rigidity to the assembly 500 by reducing potential bending, among other movements, of the trial tool assembly 502 shaft 512 during a striking of the handle assembly 506.

In another aspect, the cutting tool 508 is configured to be used in conjunction with the trial tool assembly 502 to deliver a transverse keel-cut into a bone of a joint. For example, the distal end 510 of the trial tool assembly 502 may be delivered non-transversely into a sacroiliac joint of a patient with stabilizing support from the trial impact rod assembly 504 and, then, once the trial impact rod assembly 504 is decoupled from the trial tool assembly 502, the cutting tool 508 may be slidably coupled with the trial tool assembly 502 and used to transversely cut into either or both of the sacrum and the ilium to make way for subsequent delivery of an implant having transversely extending members that match the cuts made into the sacrum/ilium. In each of the examples described above, the handle assembly 506 may be coupled to a proximal end of

the trial impact rod 504 or the cutting tool 508 and a device (e.g., hammer, mallet) may be used to strike the handle assembly 506 in order to distally drive the assembly 500.

To begin the discussion of the components of the joint preparation tool assembly 500, reference is made to the trial tool assembly 502 in FIG. 39. As seen in the figure, the trial tool assembly 502 includes an implant trial 514 at the distal end 510 of the assembly 502. The implant trial 514 is a planar member with a top surface 516, a bottom surface 518 that is opposite the top surface 516, and opposite side surfaces 520. The top surface 516 includes a channel 522 that guides a cutting element 524 of the cutting tool 508. The channel 522 extends from a tapered distal tip 526 to a proximal end 528 of the implant trial 514 and is coaxial with a shaft channel 530 that extends the length of the shaft 512 from the proximal end 528 of the implant trial 514 to a proximal end 532 of the shaft 512. In this way, the cutting element 524 of the cutting tool 508 may be guided along the shaft channel 530 while the cutting element 524 is proximal of the implant trial 514. And, when the cutting element 524 is distally advanced it will also be guided by the channel 522 in the top surface 516 of the implant trial 514. Shaft channel 530 may simply be a planar surface along shaft 512 and aligned with a corresponding planar surface of channel 522.

As seen in FIG. 39, the shaft 512 of the trial tool assembly 502 is centrally positioned on a proximal surface 534 of the implant trial 514. On the proximal surface 534 of the implant trial 514 and on either side of the shaft 514 are bores 536 that extend distally through a portion of the implant trial 514. The bores 536 are configured to receive a corresponding pair of stud members 538 on a distal end 540 of the trial impact rod assembly 504. When the stud members 538 are received within the bores 536, the implant trial 514 is correctly aligned with the distal end 540 of the trial impact rod 504. Alternatively, the bores may be studs and the studs bores.

Now the discussion will focus on the trial impact rod assembly 504 of FIG. 39. As seen in the figure, the trial impact rod assembly 504 includes a tubular shaft 542 that couples or transitions to an implant trial extension member 544 at the distal end of the trial impact rod assembly 504. The implant trial extension member 544 is a planar member that includes the stud members 538 on a planar distal surface 546 of the member 544. The shaft 512 of the trial tool assembly 502 is configured to be received within an interior space 548 in the tubular shaft 542 and the stud members 538 are configured to be received within the bores 536 on the proximal surface 534 of the implant trial 514. In this arrangement, when the shaft 512 of the trial tool assembly 502 is fully received within the tubular shaft 542 of the trial impact rod assembly 504, the proximal surface 534 of the implant trial 514 and the distal surface 546 of the implant trial extension member 544 abut each other. The implant trial extension member 544 acts as a natural extension of the implant trial 514 such that when the implant trial 514 is delivered into a patient's joint, the distal end 540 of the trial impact rod assembly 504 may also be delivered into the joint space without stoppage. Stated differently, the implant trial extension member 544 includes top and bottom surfaces 550, 552 and opposite side surfaces 554 that align with and provide a smooth transition between (i.e., coplanar) the top, bottom, and opposite side surfaces 516, 518, 520 of the implant trial 514. Alternatively, implant trial extension member 544 may have a transition which intentionally interferes with a bone of the joint in order to act as a stop. The stop feature may be adjustable or fixed.

At a mid-portion 570 of the trial impact rod assembly 504, a screw-lock 572 is rotatably coupled to the tubular shaft 542

and configured to frictionally lock or support the shaft 512 of the trial tool assembly 502 when the shaft 512 is received within the tubular shaft 542 of the trial impact rod assembly 504. The screw-lock 572 may function to lock the shaft 512 in place in many ways. For example, the screw-lock 572 may rotationally advance on a pair of threaded push-locks (not shown) that extend through the tubular shaft 542 such that when the screw-lock 572 is rotationally engaged over the push-locks, the push-locks are caused to extend further through the tubular shaft 542 and into contact with the shaft 512 of the trial tool assembly 502. Such contact with the shaft 512 of the trial tool assembly 502 may cause sufficient friction to securely support the positioning of the shaft 512 within the tubular shaft 542.

Also as seen in FIG. 39, a proximal end 556 the trial impact rod assembly 504 includes a handle engagement mechanism 558 that includes a pair of block-like members 560 with four generally perpendicular sidewalls 562 separated by mid-section member 564 with four slightly concave sidewalls 566 that are generally coplanar with a pair of corresponding sidewall 562 of the pair of block-like members 560. The handle engagement mechanism 558 is configured to be received and secured within a distal opening 568 in the handle assembly 506. The distal opening 568 extends to a cavity 586 for housing and securing of the handle engagement mechanism 558.

Moving on, reference is made to the cutting tool 508 in FIG. 39. As seen in the figure, the tool 508 includes a shaft 590 that is coupled to the cutting element 524 at a distal end 592 of the cutting tool 508. The cutting element 524 is a planar member with generally parallel opposite sides and a top surface 598 that extends outward and distally from an outer surface 594 of the shaft 590. The cutting element 524 includes a series of teeth 596 on the top surface 598 of the cutting element 524. The cutting element in this embodiment is similar to as described in reference to FIGS. 36A-36B. Alternatively, the cutting element 524 may be as described in other portions of this disclosure. For example, the cutting element 524 may include a box chisel, serrated knife blade, etc.

The shaft 590 of the cutting tool 508 is tubular and includes an internal passageway 600 that is configured to receive the shaft 512 of the trial tool assembly 502. When the shaft 512 is fully received within the tubular shaft 590 of the cutting tool 508, the cutting element 524 or, more particularly, a bottom surface 602 and a portion of opposite sidewall surfaces 604 of the cutting element 524 are guided by and positioned within the channel 522 on the top surface 516 of the implant trial 514. The cutting tool 508 may include a protrusion (not shown) on the internal passageway 600 of the shaft 590 that is configured to engage with and be guided by the shaft channel 530 of the trial tool assembly 502. When the implant trial 514 is delivered into a joint of a patient, a distal stroke of the cutting element 524 relative to the implant trial 514 is configured to make a keel-cut perpendicular to a plane defined by the joint for the subsequent delivery of an implant having matching keels or wing members.

Referring to a proximal end 606 of the cutting tool 508, the shaft 590 is coupled or transitions to a handle engagement mechanism 608 that is similar to the mechanisms 558 on the trial impact rod assembly 504. The handle engagement mechanism 608 includes a pair of block-like members 610 with four generally perpendicular sidewalls 612 separated by a smaller mid-section member 614 with four slightly concave sidewalls 616 that are generally coplanar with a pair of corresponding sidewall 612 of the pair of

block-like members 610. The handle engagement mechanism 608 is configured to be received and secured within the distal opening 568 in the handle assembly 506. As stated previously, the distal opening 568 extends to the cavity 586 for housing and securing of the handle engagement mechanism 608.

Referring to the handle assembly 506 in FIG. 39, the assembly 506 includes a coupler 574 that is configured to receive and support the handle engagement mechanisms 558, 608 on the trial impact rod assembly 504 and the cutting tool 508 within the distal opening 568. The coupler 574 includes a cylindrical sidewall 576 and a flat impact plate 578 that is opposite the distal opening 568 and configured to be struck with a hammer, mallet, or similar device in order to distally drive the joint preparation tool assembly 500 within a joint. Extending from and attached to the cylindrical sidewall 576 is a shaft 580 that further extends to a handle 582.

Still referring to the handle assembly 506 of FIG. 39, the coupler 574 includes a camming mechanism 584 that is configured to securely support the trial impact rod assembly 504 or the cutting tool 508 when the proximal end of the assembly 504 or tool 508 is positioned within the cavity 586 of the handle assembly 506. The camming mechanism 584 includes a handle 588 that transitions to a camming head having a cam-shaped surface. The camming head is coupled to the coupler 574 by an axle that extends through an aperture in the cylindrical sidewall 576 and is configured such that when the camming head is rotated about the axle, the cam-shaped surface contacts and locks against one of the concave sidewalls 566, 616 that is positioned adjacent the aperture. When the camming head is rotated in an opposite direction, the cam-shaped surface disengages with the concave sidewalls 566, 616 such that the trial impact rod assembly 504 or the cutting tool 508 may be removed from the cavity 586 in the coupler 574.

Reference is now made to FIGS. 40A-C, which are isometric views of the trial tool assembly 502 and the trial impact rod assembly 504 coupling together. As seen in FIG. 40A, the tubular shaft 542 of the trial impact rod assembly 504 is coaxially aligned with the shaft 512 of the trial tool assembly 502 such that the shaft 512 may be received within the interior space 548 of the tubular shaft 542. In this arrangement, as seen in FIG. 40B, which is a close-up view of the engagement of the implant trial 514 with the distal end 540 of the trial impact rod assembly 504, the stud members 538 on the trial impact rod 504 are aligned and configured to be received within the bores 536 on the proximal surface 534 of the implant trial 514. As seen in FIG. 40C, once the trial tool assembly 502 is received within the trial impact rod assembly 504, the screw-lock 572 may be rotationally engaged to frictionally support the shaft 512 of the trial tool assembly 502, which, in turn, securely supports the positioning of the trial tool assembly 502 relative to the trial impact rod assembly 504.

Reference is now made to FIG. 41, which is an isometric view of the trial impact rod assembly 504 and the trial tool assembly 502 coupled together with the handle assembly 506 in close proximity. As seen in the figure, the handle engagement mechanism 558 is positioned to be received within the distal opening 568 in the handle assembly 506. Also, a guidewire 618 is positioned to be received within the channel 522 on the top surface 516 of the implant trial 514. After being received within the channel 522, the guidewire 618 may be further received within and guided by the shaft channel 530 in the shaft 512 of the trial tool assembly 502. In this way, the guidewire 618 may be delivered into a joint

of a patient and the assembly 500 including the impact rod assembly 504 and the trial tool assembly 502 may be delivered into the joint via the guidewire 618 being received within the channel 522. Once the handle assembly 506 is coupled to the trial impact rod assembly 504, a mallet may be used to impact the handle assembly 506 in order to sufficiently drive the distal end 510 of the trial tool assembly 502 into the joint. And, once the implant trial 514 is sufficiently delivered within the joint space, the handle assembly 506 may be decoupled with the trial impact rod assembly 504. Next, the screw-lock 572 on the trial impact rod assembly 504 may be loosened so that the assembly 504 may be slidably removed from the trial tool assembly 502, which remains within the joint space. At this point, the guidewire 618 may be removed. Alternatively, the guide wire may be removed at any time during the procedure.

Reference is now made to FIGS. 42A-42B, which are isometric views of the trial tool assembly 502 and the cutting tool 508 coupling together. As seen in FIG. 42A, the shaft 512 of the trial tool assembly 502 is coaxially aligned with and configured to be received within the internal passage-way 600 of the shaft 590 of the cutting tool 508. The cutting element 524 is aligned with and guided by the channel 522 on the top surface 516 of the shaft 512 as the cutting tool 508 is distally advanced relative to the trial tool assembly 502. That is, the bottom surface 602 and a portion of the opposite sidewall surfaces 604 are fitted and guided within the channel 522 such that rotation of the cutting tool 508 relative to the trial tool assembly 502 is restricted.

As seen in FIG. 42B, once the trial tool assembly 502 is coupled with the cutting tool 508, the handle assembly 506 may be coupled with the handle engagement mechanism 608 on the cutting tool 508. The handle assembly 506 may be struck with a mallet in order to distally drive the cutting element 524 relative to the implant trial 514 in order to make a keel-cut transverse to the joint. The cutting tool 508 may be distally driven relative to the implant trial 514 until a distal edge 620 of the shaft 590 abuts the proximal surface 534 of the implant trial 514. At this point, the distal end 592 of the cutting element 524 is positioned at the distal tip 526 of the implant trial 514.

Once the keel-cut has been made, the handle assembly 506 and the cutting tool 508 may be decoupled from the trial tool assembly 502 (either together or individually). Then, the trial tool assembly 502 may be removed from the joint space for subsequent delivery of an implant that matches the space that was cleared by the implant trial 514 and the cutting tool 508.

While the joint preparation tool assembly 500 as described in the previous figures includes an implant trial 514 with a single channel 522 and a cutting tool 508 with a single cutting element 524, the assembly 500 may include implant trials 514 and cutting tools 508 with multiple channels 522 and cutting elements 524. For example, a certain joint preparation tool assembly 500 may include an implant trial 514 with channels 522 on a top and bottom surface 516, 518 and a cutting tool 508 with cutting elements 524 on opposite sides of the shaft 590 such that the assembly 500 may deliver simultaneous, dual keel-cuts into a joint space (e.g., into both sacrum and ilium). As another example, a certain joint preparation tool assembly 500 may include an implant trial 514 with a pair of channels 522 on both a top and a bottom surface 516, 518 and a cutting tool 508 with a pair of cutting elements 524 on opposite sides of the shaft 590 in order to make quad keel-cuts into the bones defining the sacroiliac joint space to make way for an implant having an I-beam shape as described in U.S. patent

application Ser. No. 14/447,612, mentioned previously, and hereby incorporated by reference in its entirety. Other embodiments of the assembly 500 are contemplated and within the scope of the present disclosure.

As further examples of alternative configurations of the implant trial 514 and cutting element 524, reference is made to FIGS. 43A-43D, which are respective front views of implant trials 514 with various configurations of cutting elements 524 channels 522. As seen in FIG. 43A, the channel 522 is formed by one of the side surfaces 520 that extends from the proximal end 528 of the implant trial 514 to the distal end 510 of the trial tool assembly. The channel 522 includes a neck portion 622 and a bulb-end portion 624 that is wider than the neck portion 622. In this way, once the cutting element 524 is received within the channel 522, the cutting element 524 is restrained from movement out of the channel 522 except by distal-proximal translation of the cutting element 524 relative to the implant trial 514.

Regarding the cutting element 524, it includes an implant trial engagement end 626 and a cutting end 628. The engagement end 626 includes a neck member 630 that extends to a bulb-member 632 that is slidingly and matingly received within the channel 522 by distally translating the cutting element 524 such that the engagement end 626 of the cutting element 524 is engaged and fitted within the channel 522 at the proximal end 528 of the implant trial 514. The channel 522 described herein may include additional mechanisms to restrain the cutting element 524 during distal-proximal translation. The description of a channel 522 having a neck portion 622 and a bulb portion 624 is illustrative and not intended to be limiting.

Regarding the cutting end 628 of the cutting element 524, as seen in FIG. 43A, the cutting end 628 transitions generally ninety degrees from the implant trial engagement end 626 and extends generally parallel with the side surface 520 of the implant trial 514. In particular, the cutting end 628 terminates in a cutting tip 634 that extends beyond the top surface 516 of the implant trial 514. In this way, as the cutting element 524 is distally translated, the patient's bone (e.g., sacrum or ilium) that abuts the top surface 516 of the implant 514 will be cut.

Referring to FIG. 43B, the cutting element 524 may be a T-shaped member and include a pair of cutting tips 634 where one cutting tip extends beyond the top surface 516 and one cutting tip extends beyond the bottom surface 518 of the implant trial 514. In this arrangement, the cutting element 524 may be used to deliver simultaneous cuts into opposing bones defining a joint (e.g., sacrum and ilium). And, referring to FIG. 43C, the cutting element 524 may include two T-shaped members wherein one T-shaped member is on each side surface 520 of the implant trial. In this arrangement, the cutting element 524 may be used to deliver dual-keel cuts into each of the sacrum and ilium. Such cuts may be useful for delivery of an implant having a pair of keels that are configured to extend into the sacrum and ilium.

And, while this discussion has focused on cutting elements 524 with cutting tips 634, other cutting devices that include a similar implant trial engagement end may be used with the implant trial 514 of the present discussion. For example and as seen in FIG. 43D, the cutting element 524 includes a T-shaped member with a cutting tip 634 as previously described on one side surface 520 and a box-chisel 636 on the opposite side surface 520. The box-chisel 636 may be useful, for example, to clear the plane of the joint while the T-shaped member with the cutting tips 634 may be useful for cutting into the sacrum and ilium to prepare for the subsequent delivery of a matching implant.

Similarly, instead of the box chisel 636 as shown and positioned in FIG. 43D, a drill guide collar 710 may be positioned and arranged in place of the box chisel; however, the collar would be positioned adjacent the proximal surface of the implant trial as in FIG. 44 by aligned with one or both opposite side surfaces 520. In an aspect, the drill guide collar may have a slot like configuration similar to the collar shown in FIGS. 47A and 47B except that the slot length is positioned near the implant trial opposite side surface 520 as just described regarding the drill guide collar 710 in place of the box chisel of FIG. 43D. In an aspect with the slot length parallel to the implant trial opposite surface 520, a milling cutter bit may be passed immediately adjacent surface 520 while sweeping in a plane generally parallel to the surface 520 and in doing so the milling bit may be caused to project beyond top and bottom surfaces of the implant trial—effectively preparing a cut similar to that prepared by the cutting end 628 of FIG. 43B. In yet another aspect, a guide collar including a slot aperture may align a milling bit with an opposite surface 520 yet the slot length may extend generally perpendicularly away from the surface 520, thereby permitting preparation along the joint plane by safely milling from a reference surface 520 and perpendicularly directing the motion of the bit away from the surface 520 (e.g., the other opposite surface 520 may be facing the sciatic notch).

These are only some versions of alternative embodiments of the implant trial 514 and cutting element 524 that are applicable to all joint preparation tools described herein. Other arrangements of channels 522 on different surfaces of the implant trial 514 are possible and contemplated herein. Additionally and alternatively, the implant trial 514 and cutting element 524 described in reference to FIGS. 43A-43D may include other features described in reference to the previous embodiments. For example, the implant trial 514 of the present embodiment may additionally include a cutting element as described previously that extends over the top surface of the implant trial. Also, the cutting element 524 of the present embodiment may include a cutting element guide as described previously that is configured to fit within a reciprocally shaped opening in the implant trial.

4. Trial Fit Assembly and Cutting Tool with Drill Guiding System

Turning now to FIGS. 44-47, reference is made to an additional embodiment of a joint preparation tool assembly 700. As seen in FIG. 44, the joint preparation tool assembly 700 includes a trial tool assembly 702, a drill guide 704, and a handle assembly 706.

In one aspect, the joint preparation tool assembly 700 is configured to guide a drill bit 708 during distal-proximal translation of the drill bit 708 relative to the drill guide 704 and trial tool assembly 702. In particular, the drill guide 704 is similar to as described previously with respect to the various embodiments of the cutting tool, except that the drill guide 704 includes a guide collar 710 at a distal end 712 of the drill guide 712 as opposed to a cutting element. The guide collar 710 is a tubular member that is positioned to guide the drill bit 708 above a channel 714 formed in a top surface 716 of an implant trial 718, which is located at a distal end 720 of the trial tool assembly 702, when the distal end 712 of the drill guide 704 abuts a proximal end 722 of the implant trial 718.

As seen in FIG. 44, the handle assembly 706 is releasably secured to a proximal end 724 of a shaft 726 of the trial tool assembly 702. The handle assembly 706 includes drill shank guide 728 that is formed within a body 730 of the handle assembly 706 and is configured to receive and guide a drill

bit shank 732 during distal-proximal translation of the drill bit 708. The drill shank guide 728 is a cylindrical or partially cylindrical opening or cutout that is sized slightly larger than a diameter of the drill bit shank 732. In this way, as the drill bit shank 732 is translated distal-proximal a distal end 734 of the drill bit 708 is guided to be received within, and further guided by, an internal passageway 736 defined within the guide collar 710.

Moving on to FIG. 45, reference is made to the various components of the joint preparation tool assembly 700 in an uncoupled state. As seen in the figure, the drill guide 704 is similar to previously described embodiments of the cutting tool in that it includes a pair of collars 738 with protrusions 740 extending radially inward from inner walls 742 of the collars 738. The protrusions 740 are configured to fit within and be guided by a groove 744 formed within the shaft 726 of the trial tool assembly 702. The drill guide 704 additionally includes a drill guide element 746 at distal end 712 of the drill guide 704 that is configured to slidably engage with and be guided by a reciprocally shaped opening 748 formed within the implant trial 718.

Turning now to FIG. 46, reference is made to the various components of the joint preparation tool assembly 700 in a coupled state. As seen in the figure, the drill bit 708 may include a stop feature 750 that limits a depth that the distal end 734 of the drill bit 708 may distally extend relative to the implant trial 718. The stop feature 750 may be permanently fixed (e.g., welded) or may be adjustable based on the needs of a particular surgical procedure.

In operation, the joint preparation tool assembly 700 may function as follows. The trial tool assembly 702 may be delivered into the sacroiliac joint of a patient with or without guidance by a guide wire. The drill guide 704 may be slidably engaged with the shaft 726 of the trial tool assembly 702 by fitting the proximal end 724 of the shaft 726 within and through the collars 738 such that the protrusions 740 (not shown in FIG. 46) are fitted within the groove 744 of the shaft 726. The drill guide 704 may be translated distally while being guided by the collars 738 of the trial tool assembly 702. As the drill guide 704 approaches the implant trial 718, the drill guide element 746 will engage with, and be further guided by, the reciprocally shaped opening 748 formed in the implant trial 718. The drill guide 704 will continue its distal translation until the distal end 712 of the drill guide 704 abuts the proximal end 722 of the implant trial 718. At this point, the guide collar 710 is adjacent the channel 714 on the top surface 716 of the implant trial 718.

Next, the drill bit 708 or, more particularly, the drill bit shank 732 may be fitted within the drill bit shank guide 728 in the handle assembly 706. The drill bit 708 may then be distally advanced while being guided by the drill bit shank guide 728 until the distal end 734 of the drill bit 708 engages with and is caused to enter the internal passageway 736 of the guide collar 710. At this point the drill bit 708 may be further distally advanced to deliver a bore into a patient's bone or cartilage while being guided by the collar 710 on the drill guide 704 and by the drill bit shank guide 728 on the handle assembly 706.

Reference is now made to FIGS. 47A-47B, which are alternative configurations for the guide collar 710. As seen in FIG. 47A, the guide collar 710 may include generally parallel sidewalls 752 that are generally perpendicular to a lower collar wall 754. Defined between the sidewalls 752 and the lower collar wall 754 is a slot or opening 756 that is open on a top side 758. Thus, as the drill bit 708 is distally translated relative to the guide collar 710, the sidewalls 752 prevent the drill bit 708 from angling laterally in a direction

towards one of the side surfaces of the implant trial **718**. The drill bit **708**, however, is free to angle towards or away from the top surface **716** of the implant trial **718**. In this way, the drill bit **708** (i.e., with a drill bit configured for milling) may be used to mill or machine a portion of a patient's bone that abuts the top surface **716** of the implant trial **718**.

The guide collar **710** of FIG. **47B** is similar to the collar of FIG. **47A**, except that the guide collar **710** in FIG. **47B** includes a top wall member **760** on the top side **758** of the guide collar **710**. In this way, the guide collar **710** restrains the movement of the drill bit **708** as it angles away from the top surface **716** of the implant trial **718**. Otherwise, the guide collar **710** functions very similarly to the collar of FIG. **47A**. It is noted that a proximal opening **762** on the guide collar **710** may be sized larger than the drill bit **708** a particular amount such that the drill bit **708** may be angled slightly downward towards the implant trial **718**. The exact size of the opening **762** may be chosen such that the drill bit **708** can angle somewhat downward towards the top surface **716** of the implant trial **718** without contacting the top surface **716**.

Other mechanisms are possible to guide the drill bit **708** during distal-proximal movement in drilling or milling a patient's bone. The aforementioned embodiments are merely exemplary and are not intended to be limiting. Additionally and alternatively, the trial tool assembly **702** and drill guide **704** discussed in the present embodiment may include features described in previous embodiments. For example, while not discussed previously, the drill guide **704** may include an alignment guide that is similar to the cutting guide element discussed previously. The alignment guide may extend distally from the guide collar **710** and be received within a reciprocally shaped opening in the implant trial **718**.

III. Methods of Preparing the Sacroiliac Joint for Fusion

The following discussion will focus on various methods of preparing a sacroiliac joint for a surgical fusion procedure utilizing the tools and devices discussed previously. While the discussion focuses on fusing the sacroiliac joint, the methods discussed herein are not limiting; rather, the methods are applicable to the preparation of other joints as well.

A. Preoperative Planning for a Surgical Fusion Procedure

Prior to any joint preparation, a surgeon or other medical person may select a suitable procedure to fuse the sacroiliac joint. The procedure may include fusing the joint with or without delivering an implant in the joint space. If the surgeon selects a procedure involving delivery of an implant within the joint space, the surgeon will select an implant configuration for delivery into the sacroiliac joint of the patient based on preoperative or intraoperative data. The data may be the result of post-processing of raw or other imaging data (e.g. CT or MRI DICOM files). The post-processing may include the use of a software program (e.g., 3DSLICER available from <http://www.slicer.org>) that may be used for medical image processing and 3D visualization of image data. Other data may include the patient's weight, activity level, and general health.

The preoperative or intraoperative data may assist in the planning and selecting of desirable anchor trajectories (e.g., starting and stopping points on patient's soft tissue and near or within bone tissue), anchor dimensions (e.g., length, diameter, head size, washer, thread pitch), implant types and dimensions, and joint preparation tool types, dimensions, and configurations. A particularly system for preparing and fusing the sacroiliac joint may be selected, for example, for a hypermobile joint, which may include an implant or fusion system that is resistant to the expected forces present at that particular patient's sacroiliac joint. The determination of

fixation sufficiency may be calculated based on the patient's data and also on the performance results of various bench and/or finite element analysis ("FEA") tested implant assembly configurations. For example, a calculated anchor and/or implant trajectory may be considered and determined from certain patient imaging and post-processing data with an overlaid implant assembly. Further, the implant assembly footprint within the joint plane may be selected as a lower percent of total joint surface to permit sufficient boney fusion across the joint while maintaining a sufficient implant sacral and iliac face surface area to prevent implant subsidence.

Specific measurements and characteristics of the patient's anatomy may influence the selection of a particular joint fusion system. For example, the patient's bone density may be measured at numerous locations in proximity to and surrounding the elements of the implant assembly. Lower bone density (e.g., osteopenia, osteoporosis) corresponding to a T-score lower than -1 , sacroiliac joint instability, or hypermobility may require the use of an implant assembly with a greater amount of keel (i.e., the material cross section as defined by thickness of the keel and its length along implant longitudinal axis and also keels extending a greater distance into both bones defining the sacroiliac joint) and anchor extending across the sacroiliac joint and into the ilium and sacrum. Additionally, the relative angles between the implant longitudinal axis and anchor or anchors, and also the relative angles between multiple anchors (e.g., parallel, divergent, convergent) may be preselected based on the patient's anatomy.

A comparison of the preoperative or intraoperative data (e.g., sacroiliac joint surface area, joint mobility, loading, bone density, desirable anatomic pathways) and the selected implant assembly and joint preparation tools may be conducted to ensure or validate compatibility before the manufacture ships the implant system and/or before the surgeon employs the system in a surgical procedure. After implant assembly and preparation tools validation, the selected assemblies may be shipped to the surgeon and the surgeon may proceed with the surgical fusion procedure utilizing the selected assemblies.

B. Fusion of the Sacroiliac Joint via Implant Delivery

In order to fully understand the steps to prepare the sacroiliac joint for a fusion procedure, this section will detail one, among many, methods of fusion a sacroiliac joint for which the preparation tools discussed herein may be beneficial. To begin, reference is made to FIGS. **48A-48B**, which depict various bone landmarks adjacent, and defining, the sacroiliac joint **1000** of a patient **1001**.

Reference is first made to FIG. **48A**, which is a right lateral view of a hip region **1002** of a patient **1001** lying prone, wherein the soft tissue **1003** surrounding the skeletal structure **1006** of the patient **1001** is shown in dashed lines. Delivery of an implant into the sacroiliac joint **1000** and, thus, preparing of the joint **1000** for delivery of the implant are via a posterior approach to the hip region **1002**. FIG. **48B**, which is an enlarged view of the hip region **1002** of FIG. **48A**, depicts a lateral view of the patient's hip region **1002** reveals certain features of the ilium **1005**, including the anterior superior iliac spine **2000**, the iliac crest **2002**, the posterior superior iliac spine **2004**, the posterior inferior iliac spine **2006**, the greater sciatic notch **2008** extending from the posterior inferior iliac spine **2006** to the ischial spine **2010**, and the tubercle of iliac crest **2012**.

The sacroiliac joint articular region **1044** is shown in dashed lines. A posterior inferior access region **2016** of the sacroiliac joint articular region **1044** has a superior end **2018**

on the sacroiliac joint line **2019** that is between approximately 0 mm and approximately 40 mm inferior the posterior inferior overhang **2020** of the posterior superior iliac spine **2004**. The posterior inferior access region **2016** of the sacroiliac joint articular region **1044** has an inferior end **2022** on the sacroiliac joint line that is at approximately the intersection of the posterior inferior iliac spine **2006** with the lateral anterior curved boundary **2024** of the sacrum **1004**. In other words, the posterior inferior access region **2016** of the sacroiliac joint articular region **1044** has an inferior end **2022** on the sacroiliac joint line that is at approximately the superior beginning of the greater sciatic notch **2008**.

Still referring to FIG. **48B**, the sacroiliac joint articular region **1044** roughly defines an L-shape that includes a caudal region **1086** and a cranial region **1087**. Access into the caudal region **1086** of the sacroiliac joint is via the posterior inferior access region **2016** that extends between corners defined by the superior end **2018** and the inferior end **2022**. Access into the cranial region **1087** may be accomplished by continual, anterior travel in the caudal region **1086** until the articular region **1044** turns superiorly into the cranial region **1087**.

To begin a discussion of implant delivery into the sacroiliac joint articular region **1044**, reference is made to FIG. **48C**, which is a close-up lateral side view of the hip region **1002** of a patient **1001** with a nearest ilium **1005** removed in order to show the sacroiliac joint boundary **3000** defined along the sacrum **1004** and outlining the sacroiliac joint articular region **1044**, and an implant **25** positioned for implantation within the sacroiliac joint articular region **1044**.

As seen in FIG. **48C**, boundaries along the sacroiliac joint articular region **1044** include an inferior boundary segment **3002**, an anterior boundary segment **3004**, a superior boundary segment **3006**, and a posterior boundary segment **3008**. The inferior boundary segment **3002** is immediately adjacent, and extends along, the sciatic notch **2024**.

The inferior boundary segment **3002** and anterior boundary segment **3004** intersect to form an anterior-inferior corner **3010**. The anterior boundary segment **3004** and superior boundary segment **3006** intersect to form an anterior-superior corner **3012**. The superior boundary segment **3006** and posterior boundary segment **3008** intersect to form a superior-posterior corner **3014**. The posterior boundary segment **3008** and posterior inferior access region **2016** intersect to form a superior-posterior corner **3016** of the posterior inferior access region **2016**. The inferior boundary segment **3002** and posterior inferior access region **2016** intersect to form an inferior-posterior corner **3018** of the posterior inferior access region **2016**.

The inferior boundary segment **3002** extends between corners **3010** and **3018**. The anterior boundary segment **3004** extends between corners **3010** and **3012**. The superior boundary segment **3006** extends between corners **3012** and **3014** and provides an access into the cranial portion **1087** of the sacroiliac joint. The posterior boundary segment **3008** extends between corners **3014** and **3016**. The posterior inferior access region **2016** extends between corners **3016** and **3018** and provides an access into the caudal region **1086** of the sacroiliac joint. The posterior boundary segment **3008** separates articular region **1044** and extra-articular region **3007**, which includes the sacral fossa on the sacrum **1004** and the corresponding iliac tuberosity on the ilium **1005** and defined by the extra-articular region boundary **3009**.

In one aspect and as seen in FIG. **48C**, the implant **25** may be delivered via an implant arm **111** of a delivery tool into the caudal region **1086** of the sacroiliac joint articular region

1044. As shown via the implant **25** and implant arm **110** shown in solid lines, in one embodiment, the implant **25** enters the posterior inferior access region **2016**, and is further advanced into the caudal region **1086** of the sacroiliac joint articular region **1044**, in an orientation such that the implant arm **110** and wide planar members **51** are in the joint plane and the longitudinally extending edge **3050** of the wide planar member **51** next to the inferior boundary segment **3002** is generally parallel to, and immediately adjacent to, the inferior boundary segment **3002**. Thus, the distal end **43** of the implant is heading generally perpendicular to, and towards, the anterior boundary segment **3004**.

As shown in FIG. **48C** via the implant **25** and implant arm **110** shown in dashed lines, in one embodiment, the implant **25** enters the posterior inferior access region **2016**, and is further advanced into the caudal region **1086** of the sacroiliac joint articular region **1044**, in an orientation such that the implant arm **111** and wide planar members **51** are in the joint plane and the longitudinally extending edge **3050** of the wide planar member **51** next to the inferior boundary segment **3002** is somewhere between being generally parallel to the inferior boundary segment **3002** (as illustrated by the solid-lined implant **25** in FIG. **48C**) or forming an angle **AJ** with the inferior boundary segment **3002** of up to approximately 50 degrees. Thus, the distal end **43** of the implant shown in dashed lines can be said to head anywhere from generally perpendicular to, and towards, the anterior boundary segment **3004** to heading generally towards the superior-anterior corner **3012**, or points in between.

In one embodiment, the implant **25** may be first directed into the joint space as illustrated by the solid-lined implant **25** in FIG. **48C** after which the implant **25** is rotated within the joint space to be positioned somewhere between, and including, angled position depicted by the dashed-lined implant **25**. In other embodiments, the implant **25** may be first directed into the joint space as illustrated by the dashed-lined implant **25** in FIG. **48C** after which the implant **25** is rotated within the joint space to be positioned somewhere between, and including, the parallel position depicted by the solid-lined implant **25**. Thus, an implant **25** may be delivered non-transversely (i.e., within the joint and not across the joint) into the caudal region **1086**, the cranial portion **1087**, or partially within each of the caudal and cranial regions **1086**, **1087** of the sacroiliac joint articular region **1044**. Further details of the implant delivery can be found in related applications, mentioned previously, such as U.S. patent application Ser. No. 12/998,712, which is incorporated by reference herein in its entirety.

C. Utilization of the Tools and Assemblies Described Herein to Prepare the Sacroiliac Joint for Fusion

Now that an overview of the relevant anatomical landmarks and an example fusion procedure has been described, the discussion may now focus on preparing the sacroiliac joint for a fusion procedure. In doing so, reference will be made to FIGS. **49A-49D**, among additional figures, which are steps in the methodology and illustrated in the same transverse cross section taken in along a plane extending medial-lateral and anterior posterior. In this cross section, articular surfaces **1016** are covered by a thick layer of articular cartilage with a joint space existing between them, the FIGS. **49A-49D** are simplified for illustrative purposes and do not show these features to scale.

Now referring primarily to FIG. **49A**, an embodiment of the method can include the step of placing a patient under sedation prone on a translucent operating table (or other suitable surface). The sacroiliac joint **1000** can be locally anesthetized to allow for injecting a radiographic contrast

1046 (as a non-limiting example, Isovieu 300 radiographic contrast) under fluoroscopic guidance into the inferior aspect of the sacroiliac joint **1000** to outline the articular surfaces **1016** of the sacroiliac joint **1000**) defined between the sacrum **1004** and ilium **1005**, the sacroiliac joint **1000** having an interarticular region **1044**. Injection of the radiographic contrast **1046** within the sacroiliac joint **1000** can be accomplished utilizing a tubular member **1047** (e.g., a syringe needle) having first tubular member end **1048** which can be advanced between the articulating surfaces **1016** of the sacroiliac joint **1000** and having a second tubular member end **1049** which removably couples to a hub **1050**. The hub **1050** can be configured to removably couple to a syringe barrel **1051** or other device to contain and deliver an amount of radiographic contrast **1046**. In the example of a syringe barrel **1051**, the syringe barrel **1051** can have an internal volume capable of receiving an amount of the radiographic contrast **1046** sufficient for outlining the articular surfaces **1016** of the sacroiliac joint **1000**, for example, under lateral fluoroscopy. A plunger **1052** can be slidably received within the barrel **1051** to deliver the radiographic contrast **1046** through the tubular member **1047** into the sacroiliac joint **1000**. The tubular member **1047** can have a gauge in the range of about 16 gauge and about 20 gauge and can further be incrementally marked on the external surface to allow determination of the depth at which the first needle end **1048** has advanced within the sacroiliac joint **1000**. As the first needle end **1048** advances into the sacroiliac joint **1000** the radiographic dye **1046** can be delivered from within the syringe barrel **1051** into the sacroiliac joint **1000** to allow visualization of the sacroiliac joint **1000** and location of the tubular needle **1047** within the sacroiliac joint **1000**.

Now referring primarily to FIG. **49B**, once the first tubular member end **1048** has been sufficiently advanced into the sacroiliac joint **1000** and the articular surfaces **1016** of the sacroiliac joint **1000** have been sufficiently visualized, the hub **1050** can be removed from the tubular member **1047** leaving the tubular member **1047** fixed within the sacroiliac joint **1000** as an initial guide for tools subsequently used to locate or place the sacroiliac joint implant non-transversely between the articulating surfaces **1016** of the sacroiliac joint **1000** (e.g., locate the implant non-transversely to the joint plane **1030** generally defined by the articulating surfaces **1016** of the interarticular region **1044** of the sacroiliac joint **1000**) or in removal of a portion of the sacroiliac joint **1000** within the region defined by the articular surfaces **1016** to generate an implant receiving space **1029**. Alternately, one or more guide pins **1013** can be inserted along substantially the same path of the tubular member **1047** for fixed engagement within the sacroiliac joint **1000** and used in subsequent steps as a guide(s).

Now referring primarily to FIG. **49C**, a small incision **1053** can be made in the skin at the posterior superior, or as to certain embodiments inferior, aspect of the sacroiliac joint **1000**, extending proximal and distal to the tubular member **1047** along the line of the sacroiliac joint **1000** to provide a passage to access the interarticular space between the articulating surfaces **1016** (see FIG. **49B**) of the sacroiliac joint **1000**. More specifically, the small incision **1053** can be made along the joint line of the sacroiliac joint **1000** in the tissue covering the posterior inferior access region **2016** of the sacroiliac joint articular region **1044**. A cannulated probe **1054** can be slidably engaged with the tubular member **1047** (or guide pin **1013**) extending outwardly from the sacroiliac joint **1000** (while the sacroiliac joint may be shown in the figures as being substantially linear for illustrative purposes, it is to be understood that the normal

irregular features of the sacroiliac joint have not been removed). The cannulated probe **1054** can have a probe body **1054** of generally cylindrical shape terminating in a spatulate tip **1055** at the end advanced into the sacroiliac joint **1000**. A removable cannulated probe handle **1056** couples to the opposed end of the probe body **1054**. The spatulate tip **1055** can be guided along the tubular needle **1047** or guide wire **1013** into the posterior portion of the sacroiliac joint **1000** and advanced to the anterior portion of the sacroiliac joint **1000** under lateral fluoroscopic visualization. The cannulated probe handle **1056** can then be removed providing the generally cylindrical probe body **1054** extending outwardly from the sacroiliac joint **1000** through the incision **1053** made in the skin.

Alternatively, the probe **1054** can be used to guide, advance or place a needle, guide wire or other instrument up to, near, or into the joint.

Additionally, in particular embodiments, probe handle **1056** or the opposed end of the probe body **1054**, or both, can be configured to have an interference fit or a luer lock hub to communicate with a syringe barrel **1051** in order to advance contrast, in situ curable biocompatible materials, stem cells, or etc through the cannulated probe **1054** or cannulated probe handle **1056**.

Now referring primarily to FIG. **49D**, a passage from the incision **1053** (see FIG. **49C**) to the sacroiliac joint **1000** can be generated by inserting a cannula **1057** into the incision. A soft tissue dilator **1058** having a blunt end **1059** can be advanced over the probe body **1054**, or a plurality of soft tissue dilators of increasing size, until the blunt end **1059** of the soft tissue dilator **1058** and the corresponding cannula end contact the posterior aspect of the sacroiliac joint **1000**. More specifically, in one embodiment, the ends of the dilator **1058** and cannula **1057** contact the joint line **2019** of the sacroiliac joint **1000** at the posterior inferior access region **2016** of the sacroiliac joint articular region **1044**. The soft tissue dilator **1058** can be removed from within the cannula **1057**. The external surface of the cannula **1057** can be sufficiently engaged with the surrounding tissue to avoid having the tissue locate with in the hollow inside of the cannula **1057**. A non-limiting embodiment of the cannula **1057** provides a tubular body having substantially parallel opposed side walls which terminate in a radius at both ends (lozenge shape) into which a plurality of different jigs can be inserted. Alternatively, as a non-limiting example, according to particular embodiments, cannula **1057** and corresponding dilators **1058** and alignment jigs **1060** can be configured to have tubular bodies with an elliptical or circular cross section.

In some embodiments, the cannula **1057** may be additionally configured to have within or near its walls a light source such as, for example, a fiberoptic or a LED light source to assist in visualization of the working area. Also, in some embodiments, irrigation and suction tubing may communicate with the inside passage of cannula **1057**.

At this stage, additional tools and methods may be employed to provide access to the sacroiliac joint **1000** as described in U.S. patent application Ser. No. 13/475,695 filed May 18, 2012 entitled "SYSTEMS FOR AND METHODS OF FUSING A SACROILIAC JOINT," which is hereby incorporated by reference in its entirety. For example, drill jigs may be further advanced over the probe body **1054** to align a drill or other joint preparation tool. Accordingly, the discussion will now focus on employing the tools and devices described in previous sections of this application.

Now referring primarily to FIGS. 49E-49G, a cannula alignment jig 1060 can be advanced over the probe body 1054 (or guide pins 1013) and received within the cannula 1057. Substantially, identical cross hairs 1063, 1064 can be disposed on the upper jig surface 1065 and the lower jig surface 1066. Alignment of the cross hairs 1063, 1064 under x-ray with the sacroiliac joint 1000 can confirm that the cannula 1057 has proper orientation in relation to the paired articular surfaces 1016 of the sacroiliac joint 1000. The cannula 1057 properly oriented with the paired articular surfaces 1016 can then be disposed in fixed relation to the sacroiliac joint by placement of fasteners through the cannula 1057 into the sacrum 1004 or the ilium 1005.

Now referring to FIGS. 49H and 49I, a first drill jig 1067 can be advanced over the probe body 1054 (or guide pins 1013) and received within the cannula 1057. The probe body 1054 (or guide pins 1013) extending outwardly from the sacroiliac joint 1000 passes through a drill guide hole 1068 of the first drill jig 1067 (or a plurality of guide pins 1013 can extend through a corresponding plurality of guide pin holes 1069). The drill guide hole 1068 can take the form of a circular hole as shown in the Figures, a slot, or other configuration to restrict the movement of a drill bit 1062 within the drill jig 1067 and provide a guide for a drill bit 1062 in relation to the sacroiliac joint 1000. Guide pin holes 1069 can receive guide pins which can be positioned between the articular surfaces 1016 of the sacroiliac joint 1000 to demarcate the zone of desired treatment or safe working zones while using, for example, lateral fluoroscopy. As a non-limiting example, a first guide pin 1013 can be advanced through a first guide pin hole 1069, or alternatively a guide pin 1013 is first inserted into the sacroiliac joint 1000 and subsequently a guide jig 1067 is advanced over the guide pin 1013, the first guide pin 1013 can enter near inferior end 2022 of the posterior inferior access region 2016 of the sacroiliac joint articular region 1044 via the sacroiliac joint line 2019 to border a portion of the greater sciatic notch 2008 thereby allowing a medical person, computer guided surgical system, or other observer to more easily highlight under x-ray a border which should not be crossed during the procedure due to the presence of nerve and other structures. Additionally, as a non-limiting example, first guide pin 1013 can be configured as an electrode, insulated from the operator and the patient's soft tissues, and may be connected to a monitor to signal to an operator or surgeon when implant 12, configured with a stimulating electrode (NM), e.g., as shown and described in U.S. Provisional Patent Application 61/860,185, comes into contact with first guide pin. Similarly, a second guide pin 1013 can be placed in another guide pin hole 1069 to demarcate a second limit to a desired zone of treatment, or safe working zone. For example, a second guide pin 1013 can enter near the superior end 2018 of the posterior inferior access region 2016 of the sacroiliac joint articular region 1044 via the sacroiliac joint line 2019 to be positioned to border an area of the sacroiliac joint 1000 such as a transition zone between the extra-articular 3007 and the interarticular region 1044 which, for example, has been highlighted by contrast material as above described.

Referring to FIGS. 49J-49R, a cannula 1057 may be used to facilitate access to the surgical region during a procedure to implant the implant assembly 14 (not

shown). In one embodiment, the cannula 1057 may be used in conjunction with a sacroiliac joint repair procedure via a known surgical access region including, but not limited to, the posterior inferior access region 2016 as illustrated in FIGS. 49J-49R. The cannula 1057 may include a cannula body 1057H forming a wall enclosing an internal volume 1057J, which opens to a proximal opening 1057A and a distal opening 1057I3. Upon insertion of the cannula 1057 within the surgical access region, the internal volume 1057J may be maintained, thereby functioning as an opening through which surgical instruments, appliances, fasteners, and any other associated surgical equipment or supplies may be inserted or removed and through which the surgical procedure may be visually monitored.

The outer surface of the cannula body 1057H may include one or more contoured regions or projections to enhance the close fit of the cannula 1057 between the skeletal structures surrounding the surgical access region 2016. The outer surface of the body 1057H may form a cannula sacral contour 1057C on one side and may additionally form a cannula iliac contour 1057D on a side opposite to the cannula sacral contour 1057C. The cannula 1057 may also include a distal projection 1057E which extends distally beyond the cannula sacral contour 1057C and may be shaped to fit within a portion of the greater sciatic notch 2008 (see FIG. 49P). In addition, the outer distal surface of the cannula body 1057H may form a PSIS contact area 1057F to enhance the fit of the portion of the cannula 1057 contacting the posterior superior iliac spine (PSIS) 2004 (see FIG. 49N).

The cannula body 1057H may further define one or more additional bores configured to reversibly receive handles and/or fasteners used to situate the cannula within the surgical region and/or to reversibly receive fasteners used to fix the cannula in place within the surgical region during the surgical procedure. The cannula body 1057H may define a fastener bore 1057K passing through the cannula body 1057H from the outer surface into the internal volume 1057J of the cannula 1057. The cannula bore may open at one end to a cannula fastener bore proximal opening 1057G, which may be in communication with the internal volume 1057J of the cannula 1057. The cannula bore may also open at an opposite end to a cannula fastener bore distal opening 1057L which may be further configured to permit a fastener 1057Z to i) extend generally perpendicular to the cannula PSIS contact area 1057F; and/or, ii) be in a divergent relation relative to distal projection 1057E. Furthermore, the cannula 1057 may have a handle 1057Y extending from the cannula body 1057H for inserting, removing, and/or otherwise manipulating the cannula 1057 during a surgical procedure. As illustrated in FIG. 49J, the handle 1057Y may be reversibly attached to the cannula body 1057 via a handle bore 1057M formed with the cannula body 1057H. The handle bore 1057M may be provided with fastener features including, but not limited to, threads, that may cooperatively engage corresponding fastener features at a distal end 1057N of the handle 1057Y in order to implement the reversible attachment of the handle 1057Y to the cannula 1057.

Referring again to FIGS. 49J to 49R, a surgical procedure employing the cannula 1057 may be conducted using a method described herein below. A cannula 1057 may be positioned near a sacroiliac joint line 2019 and in an

area including the posterior inferior access region 2016 such that the sacroiliac joint line 2019 may be visible and/or accessible via a cannula proximal opening 1057A, as illustrated in FIG. 49O. The cannula 1057 may be further positioned to align the distal extension 1057E with a portion of the greater sciatic notch 2008, as illustrated in FIG. 49P. The cannula 1057 may be further positioned to align the cannula PSIS contact area 1057F with a portion of a posterior superior iliac spine 2004 as illustrated in FIG. 49N. The cannula 1057 may then be disposed in fixed relation to the sacroiliac joint by placement of fasteners 1057Z through the cannula 1057 into the sacrum 1004 or the ilium 1005, as illustrated in FIG. 49P.

In certain embodiments of the method, an amount of articular cartilage or other tissues from between the articular surfaces of the sacroiliac joint 1000 can be removed sufficient to allow embodiments of the sacroiliac joint implant to be implanted in replacement of the removed articular cartilage or tissue. Because the method removes the degenerative articular cartilage or tissue between the articular surfaces of the sacroiliac joint 1000, the articular surfaces of the sacroiliac joint 1000 can remain intact or substantially intact allowing the sacroiliac joint implant to be non-transversely located between the articular surfaces of the sacroiliac joint 1000.

Reference is now made to FIG. 50A, which depicts a joint preparation tool 4000 including a tooling head 4002, as described in FIGS. 9-10, approaching the sacroiliac joint 1000. The joint preparation tool 4000, in particular, includes a cutting element 4004 that outwardly extends from a shaft 4006 at the distal end of the tooling head 4002. The cutting element 4004 includes a sharpened proximal edge 4008 such that a cutting stroke occurs with a proximal retraction of the joint preparation tool 4000.

As seen in FIG. 50A, the joint preparation tool 4000 is oriented relative to sacroiliac joint articular region 1044 such that the outwardly extending cutting element 4004 is positioned parallel to the joint plane 1030. That is, each of the side walls the cutting element 4004 is oriented between the articular surfaces of the joint 1000 and the proximal edge 4008 is, initially, oriented transversely across the joint plane 1030. As illustrated in FIG. 50B, the joint preparation tool 4000 is advanced into the sacroiliac joint articular region 1044 in the previously described orientation.

Now reference is made primarily to FIG. 50C, which is a similar view to that of FIG. 48C, except that instead of an implant being delivered into the sacroiliac joint 1000, the joint 1000 is being prepared for implant delivery. As seen in the figure, the distal end of the tooling head 4002 may enter the posterior inferior access region 2016 and extend into the caudal region 1086 of the sacroiliac joint articular region 1044. As an example and as seen by the solid line depiction of the tooling head 4002, the head 4002 may be delivered into the caudal region 1086 such that the shaft 4006 is generally adjacent and parallel to the inferior boundary segment 3002. At a sufficient depth, the joint preparation tool 4000 may be rotated within the joint plane (as seen by the broken line depiction of the joint preparation tool 4000) such that the shaft 4006 angles the cutting element 4004 towards the cranial region 1087 of the articular region 1044. This and other movements will cause the proximal edge 4008 of the cutting element 4004 to cut into or shear the articular cartilage from the articular surfaces of the sacroiliac joint articular region 1044.

As another example of preparing the articular region 1044 once the tool 4000 is positioned within the articular region

1044, reference is made to FIG. 50D, which depicts the joint preparation tool 4000 fully in into the articular region 1044 such that the shaft 4006 of the tooling head 4002 is adjacent and parallel to the inferior boundary segment 3002 and the cutting element 4004 is adjacent the anterior-inferior corner 3010. In this orientation, the cutting element 4004 extends from the shaft 4006 towards the cranial region 1087 of the articular region 1044. It is noted that insertion of the tool 4000 into the articular region 1044 causes an initial abrasion to the articular cartilage in the portions of the articular region 1044 where the tool 4000 is inserted. To further prepare the articular region 1044, a force F1 may be applied to joint preparation tool 4000 in a direction perpendicular to the extension of the shaft 4006 and in a direction towards the cranial region 1087. As seen in FIG. 50E, which depicts the joint preparation tool 4000 moved superiorly according to the applied force F1, the cutting element 4004 is now in contact with additional articular cartilage that was not previously abraded by the insertion of the tool 4000 into the articular region 1044. At this point, a force F2 may be applied proximally on the joint preparation tool 4000.

As seen in FIG. 50F, the force F2 and the proximal retraction of the tooling head 4002 from the articular region 1044 will cause articular cartilage in-line with the cutting element 4004 to be cut or otherwise sheared from the articular surfaces of the articular region 1044 leaving a prepared joint surface 4010. At this point, the joint preparation tool having a curette-type tooling head may be used to remove the abraded articular cartilage in the joint space by any number of methods.

The previously mentioned steps may be repeated in order to increase the size of the prepared joint surface 4010 as may be needed for a particular surgical procedure. For example, a joint preparation tool 4000 having a tooling head 4002 with a larger outwardly extending cutting element 4004 may be subsequently used to prepare an even larger joint surface 4010.

Now primarily referring to FIG. 51A, the joint preparation tool 4000 previously described may be used to make keel-cuts generally perpendicularly into the sacrum 1004 and/or the ilium 1005. As seen in the figure, which is a transverse cross section of the sacrum 1004 and the ilium 1005 taken in along a plane extending medial-lateral and anterior posterior, the joint preparation tool 4000 may be delivered into the sacroiliac joint articular region 1044, as described previously in FIGS. 50A-50B, such that the cutting element 4004 extends from the shaft 4006 of the tooling head 4002 parallel to the joint plane 1030. In this orientation, the proximal edge 4008 of the cutting element 4004 extends across the joint plane 1030. Once the joint preparation tool 4000 is at a sufficient depth within the articular region 1044, as seen in FIG. 51A, the shaft 4006 of the tool 4000 may be rotated such that the cutting element extends within either the sacrum 1004 or the ilium 1005 (cutting element extends within ilium 1005 in FIG. 51A) and is oriented perpendicular to the joint plane 1030. Next, a force F3 may be proximally applied (e.g., via a slap hammer assembly) to the joint preparation tool 4000 such that the proximal edge 4008 of the cutting element 4004 cuts a channel, groove, or other feature as defined by the shape of the proximal edge 4008 into the bone of the ilium 1005. As seen in FIG. 51B, the proximal retraction of the joint preparation tool 4000 forms a receiving space 4012 within the bone of the ilium 1005 for use in a particular fusion procedure. While FIG. 51B depicts the cutting element 4004 only partially retracted from the articular region 1044, the cutting element 4004 may be fully

retracted such that the keel-cuts forming the receiving space **4014** extend to the proximal end of the joint line **1030**.

Alternatively and as seen in FIG. **51C**, which is the same as FIG. **51B** except the shaft **4006** of the joint preparation tool **4000** is rotated about ninety degrees, the tooling head **4002** may be removed from the articular region **1044** after the ninety degree rotation by a proximal force **F4**. Thus, the tooling head **4002** is removed from the joint without performing a full keel-cut that would extend the receiving space **4012** to the proximal end of the joint line **1030**. Turning to FIG. **51D**, which depicts the receiving space **4012** after the joint preparation tool **4000** has been proximally withdrawn; the receiving space **4012** may be filled with a biological material **4014** such as an auto/graft, synthetic biologic, or scaffold, among other materials. Next, a bone tamp **4016** or other device may be used to apply a distal force **F5** along the joint line **1030** so as to compress the biological material **4014** into the receiving space **4012**. As seen in FIG. **51E**, the bone tamp **4016** may be compressed along the joint line **1030** up to a depth of the keel-cut, among other possible depths, such that the biological material **4014** may compress across the articular surface of the sacrum **1004** and the groove formed in the receiving space **4012**.

In certain embodiments of the method, keel-cuts can be made in either or both of the sacrum **1004** and the ilium **1005** and such a decision will be based on the particular fusion procedure and the type and configuration of an implant to be delivered into the joint. For example, an implant having coplanar wing member may require dual keel-cuts where both the sacrum **1004** and the ilium **1005** are cut for the subsequent delivery of the implant. In such an example and referring to FIG. **52A**, a joint preparation tool **4000** having a tooling head **4002** with dual-cutting elements **4004**, as described in reference to FIG. **13**, may be employed. Similar to as discussed previously, the joint preparation tool **4000** having dual-cutting elements **4004** may be delivered into the sacroiliac joint articular region **1044** with the outwardly extending cutting elements **4004** positioned within the joint plane **1030** such that the proximal edges **4008** extend across the joint line **1030**. Once the joint preparation tool **4000** is delivered into the articular region **1044** at an appropriate depth, as seen in FIG. **52A**, the tool **4000** may be rotated about ninety degrees such that the cutting elements extend generally perpendicularly into the sacrum **1004** and the ilium **1005**. Next, as seen in FIG. **52B**, the joint preparation tool **4000** may be proximally retracted by a force **F6** (e.g., via a slap hammer) such that the dual-cutting elements **4004** form opposing channels **4018** in the sacrum **1004** and the ilium **1005** that match the shape of an implant to be delivered in the surgical procedure.

In certain embodiments, the dual-cutting elements **4004** are identical in shape and size. In other embodiments, the dual-cutting elements **4004** may be differently configured based on the physical characteristics of the bone type to be cut, the implant to be delivered, etc. That is, since the ilium **1005** is generally a harder bone than the sacrum, a different type of cutting edge configuration may be used on one of the cutting elements **4004**.

Now the discussion will focus on methods of preparing the sacroiliac joint **1000** for a surgical fusion procedure with a joint preparation tool assembly including a trial tool assembly and a cutting tool as described in reference to FIGS. **27-47**.

Referring primarily to FIG. **53A**, a trial tool assembly **4022** having an implant trial **4024** at a distal end of the assembly **4022** may be delivered into the sacroiliac joint articular region **1044** of a patient. The trial tool assembly

4022 may be guided into the articular region **1044** by a guide wire (not shown) that was previously delivered into the joint by previously described methods. In particular, the guide wire may be received within a bore that extends from a distal end to a proximal end of the implant trial **4024**. The implant trial **4024** may be delivered within the joint plane **1030** such that the planar top and bottom surfaces **4026** are parallel to the joint plane **1030** and the opposite side surfaces **4028** of the implant trial **4024** are perpendicular to the joint plane **1030**.

The implant trial **4024** may be forcibly delivered into the articular region **1044** by using a hammer or mallet to strike an impact plate (not shown) at a proximal end of the joint preparation tool assembly **4020**. And, in certain embodiments, a trial impact rod assembly (not shown) may be used in conjunction with the trial tool assembly **4022** to provide stiffness during the forceful delivery of the implant trial **4024** within the articular region **1044**.

The implant trial **4024** is used to determine an appropriate fit of an implant. So, implant trials **4024** of increasingly larger size may be delivered into the articular region **1044** until an implant trial **4024** is chosen that appropriately fits the top and bottom surfaces **4026** of the implant trial **4024** against the articular surfaces of the articular region **1044**.

Referring primarily to FIG. **53B**, which depicts the implant trial **4024** positioned within the articular region **1044**, a cutting tool **4030** may be slidably engaged with a shaft **4032** of the trial tool assembly **4022** and translated distally on the shaft **4032**. As seen in FIG. **53B** and as described previously, the cutting tool **4030** is guided along the shaft **4032** in a single orientation such that it will be guided within a channel (not shown) on the top surface **4026** of the implant trial **4024**. The channel is configured to guide the cutting tool **4030** such that a cutting element **4034** of the cutting tool **4030** extends generally perpendicular to the top surface **4026** of the implant trial **4024**. Thus, as seen in FIG. **53C**, as the cutting element **4034** advances distally into the channel of the implant trial **4024** and within the articular region **1044**, the cutting element **4034** extends and cuts into the articular surface of either the sacrum **1004** or the ilium **1005**. A reciprocating motion may be employed.

While, as seen in FIG. **53C**, the cutting element **4034** extends and cuts into the ilium **1005** during a distal stroke of the cutting tool **4030**, the process may be similarly performed with respect to the sacrum **1004**. Alternatively, a cutting tool **4030** with dual-cutting elements **4034** may be employed to deliver simultaneous and opposing cuts into both the sacrum **1004** and the ilium **1005**. In such an embodiment of the joint preparation tool assembly **4020** with dual-cutting elements **4034** (and, thus, dual-channels in the implant trial **4024**) the individual cutting elements **4034** may be the same or different. The individual cutting elements **4034** may, for example, be different types and configurations of cutting elements **4034** since the ilium **1005** is a generally harder bone than the sacrum **1004**. Additionally, cutting tools **4030** with increasingly larger cutting elements **4034** may be employed such that initial cuts are smaller and of a shallower depth into the articular surfaces while subsequent cuts are larger and of a deeper depth into the articular surfaces of the sacrum **1004** and ilium **1005**.

After employing the joint preparation tool **4020** to make appropriate keel-cuts, as seen in FIG. **53D**, the tool **4020** may be removed from the articular region **1044** leaving one or more channels **4036** that match an implant to be delivered into the joint **1000**.

As stated previously, the various tools and assemblies discussed herein may be used independently or in combi-

nation with each other. Thus, in certain embodiments and at various steps within the methodology the anchor arm assembly 258, as discussed in reference to FIGS. 24-25, may be employed with any of the joint preparation tools to deliver an anchoring element 282 across the sacroiliac joint. The anchoring arm assembly 258 may, for example, orient the anchoring element 282 to be delivered first through the ilium, transversely across the joint line of the sacroiliac joint, and then through the sacrum. Alternatively, the anchoring arm assembly 258 may orient the anchoring element 282 to be delivered first through the sacrum, transversely across the joint line of the sacroiliac joint, and then through the ilium.

Understandably, other instruments can be utilized separately or in combination during the course of any of the steps of the methodology, e.g., for the removal of articular cartilage or tissue between articular surfaces, such as any of the tools previously described or any of: endoscopy tools, box chisels, side cutting router bits, burs, flexible burs and bits, hole saws, key hole saw, medical bone chainsaw osteotome, curettes, lasers (e.g., CO₂, Neodymium/Y AG (yttrium-aluminum-garnet), argon, and ruby), electrosurgical equipment employing electromagnetic energy (the cutting electrode can be a fine micro-needle, a lancet, a knife, a wire or band loop, a snare, an energized scalpel, or the like) where the energy transmitted can be either monopolar or bipolar and operate with high frequency currents, for example, in the range of about 300 kHz and about 1000 kHz whether as pure sinusoidal current waveform where the “crest factor” can be constant at about 1.4 for every sinus waveform, and a voltage peak of approximately 300 V to enable a “pure” cutting effect with the smallest possible coagulation effect or as amplitude modulated current waveforms where the crest factor varies between 1.5 and 8, with decreasing crest factors providing less of a coagulation effect. Electrosurgical waveforms may be set to promote two types of tissue effects, namely coagulation (temperature rises within cells, which then dehydrate and shrink) or cut (heating of cellular water occurs so rapidly that cells burst). The proportion of cells coagulated to those cut can be varied, resulting in a “blended” or “mixed” effect. Additionally, a fully rectified current, or a partially rectified current, or a fulguration current where a greater amount or lateral heat is produced can be employed to find the articular surfaces of the joint and aid in advancing a probe or guide wire into a position in between the articulating surfaces. These currents can effectively degrade the cartilage and allow advance into the joint without grossly penetrating much beyond the cartilage.

The foregoing merely illustrates the principles of the embodiments described herein. Various modifications and alterations to the described embodiments will be apparent to those skilled in the art in view of the teachings herein. It will thus be appreciated that those skilled in the art will be able to devise numerous systems, arrangements and methods which, although not explicitly shown or described herein, embody the principles of the embodiments described herein and are thus within the spirit and scope of the present disclosure. From the above description and drawings, it will be understood by those of ordinary skill in the art that the particular embodiments shown and described are for purposes of illustrations only and are not intended to limit the scope of the present disclosure. References to details of particular embodiments are not intended to limit the scope of the disclosure.

What is claimed is:

1. A method of surgically preparing a sacroiliac joint having a sacrum, an ilium, and a sacroiliac joint space defined therebetween for a surgical fusion procedure, the method comprising:

a) approaching the sacroiliac joint space with a joint preparation tool comprising:

an implant trial tool assembly comprising an implant trial at a distal end of the joint preparation tool and an implant trial shaft extending proximally from the implant trial, the implant trial comprising a length extending between a proximal end and a distal end of the implant trial, a first top surface, and a first bottom surface generally opposite the first top surface; and a cutting tool configured to releasably and slidably couple with the implant trial tool assembly, the cutting tool comprising a cutting element at a distal end of the cutting tool and a cutting shaft extending proximally from the cutting element, the cutting element comprising a second length extending between a proximal and a distal end, wherein the implant trial tool assembly is configured to guide the cutting tool during distal-proximal translation;

b) delivering at least a portion of the implant trial non-transversely into the sacroiliac joint space, the implant trial being oriented in the sacroiliac joint space such that the first top and bottom surfaces are generally coplanar with a joint plane of the sacroiliac joint space; and

c) causing the cutting tool to be distally driven relative to the implant trial tool assembly such that the cutting element makes a cut extending into at least one of the sacrum or the ilium.

2. The method of claim 1, wherein the implant trial tool assembly is configured to guide the cutting tool during the distal-proximal translation such that as the cutting element distally advances relative to the implant trial, at least a portion of the cutting element extends generally over and perpendicularly outward from the first top surface of the implant trial.

3. The method of claim 1, wherein the implant trial further comprises a channel formed in the first top surface that extends at least a portion of the first length of the implant trial, the channel guiding the cutting element during the distal-proximal translation.

4. The method of claim 3, wherein the cutting element is partially positioned within the channel.

5. The method of claim 4, wherein the cutting element further comprises a cutting element guide extending at least a portion of the second length and fitting within a reciprocating portion of the channel.

6. The method of claim 5, wherein the channel defines an opening on a proximal end of the implant trial such that as the cutting element is distally driven relative to the implant trial, the cutting element is received within the channel and the cutting element guide is received within the reciprocating portion of the channel.

7. The method of claim 6, wherein the reciprocating portion of the channel comprises a cylindrical portion.

8. The method of claim 5, wherein the cutting element guide fitting within the reciprocating portion of the channel restrains the cutting element from rotating relative to the implant trial.

9. The method of claim 3, wherein the channel does not extend to and form an opening in the first bottom surface.

10. The method of claim 1, wherein the implant trial further comprises a bore extending through the implant trial

59

from the distal to the proximal end and configured to receive and be guided into the sacroiliac joint space by a guide wire.

11. The method of claim 10, wherein the implant trial shaft is offset from a central portion of a proximal end of the implant trial.

12. The method of claim 11, wherein the implant trial shaft includes a groove formed within the implant trial shaft, the groove being generally coaxial with the bore.

13. The method of claim 1, wherein the implant trial shaft includes a groove formed within and extending lengthwise of the implant trial shaft, the cutting tool including a protrusion that engages with the groove during distal-proximal translation of the cutting tool relative to the implant trial tool assembly.

14. The method of claim 13, wherein the engagement of the protrusion and the groove prevents rotation of the cutting tool relative to the implant trial tool assembly.

15. The method of claim 1, wherein the joint preparation tool further comprises: a trial impact rod assembly comprising an implant trial extension member at a distal end of the trial impact rod assembly, a trial impact shaft coupled to and extending proximally from the implant trial extension member, and a trial impact cavity extending through the implant trial extension member and through at least a portion of the trial impact shaft, the trial impact cavity configured to receive the implant trial shaft such that the implant trial and the implant trial extension member abut each other in a particular arrangement.

16. The method of claim 15, wherein the implant trial extension member includes a second top surface, a second bottom surface opposite the second top surface, and a second thickness defined between the second top and second bottom surfaces, wherein in the particular arrangement the first top surface aligns with the second top surface to form a generally smooth transition between the surfaces.

17. The method of claim 15, wherein, in the particular arrangement, corresponding features on a distal end of the implant trial extension member and on the proximal end of the implant trial engage with each other to restrict rotational movement of the trial impact rod assembly relative to the implant trial tool assembly.

18. The method of claim 17, wherein the corresponding features include a stud member and a bore configured to receive the stud member within the bore.

19. The method of claim 15, wherein the trial impact shaft includes a lock feature that is configured to secure a position of the implant trial shaft when the implant trial shaft is received within the trial impact cavity.

20. The method of claim 15, wherein a proximal end of the trial impact rod assembly includes a handle engagement feature configured to be releasably secured to a handle.

21. The method of claim 1, wherein the cutting tool simultaneously makes a cut into the sacrum and the ilium.

22. The method of claim 1, wherein the cutting tool makes a cut into only one of the sacrum or the ilium.

23. The method of claim 1, wherein the implant trial shaft comprises a first cylindrical rod, and the cutting shaft comprises a second cylindrical rod.

24. The method of claim 1, further comprising: d) delivering an implant into the sacroiliac joint space.

25. The method of claim 24, wherein at least a portion of the implant occupies a space resulting from the cut extending into at least one of the sacrum or the ilium.

26. The method of claim 25, wherein the at least a portion comprises a keel of the implant.

27. The method of claim 24, wherein the implant approximates a shape and size of the implant trial.

60

28. The method of claim 1, wherein the implant trial further comprises a first side surface, a second side surface, and a guide wire bore, the first side surface extending between the first top surface and the first bottom surface on a first side of the implant trial, the second side surface extending between the first top surface and the first bottom surface on a second side of the implant trial that is opposite the first side, the guide wire bore extending through the implant trial from the distal to the proximal end and configured to receive and be guided into the sacroiliac joint space by a guide wire.

29. The method of claim 28, wherein the implant trial further comprises a channel formed in the first top surface that extends at least a portion of the first length of the implant trial, the channel comprising a head region and a contracted neck region, wherein the cutting element further comprises a cutting element guide extending at least a portion of the second length, the cutting element guide configured to fit within the head region and the contracted neck region.

30. The method of 29, wherein the cutting element guide is configured to be received within the head region and the contracted neck region when the cutting element distally converges with the implant trial such that, once converged, the cutting element is restrained from rotating relative to the implant trial via the cutting element guide fitting within the head region and the contracted neck region.

31. A method of surgically preparing a sacroiliac joint having a sacrum, an ilium, and a sacroiliac joint space defined therebetween for a surgical fusion procedure, the method comprising:

a) approaching the sacroiliac joint space with a joint preparation tool comprising:

an implant trial tool assembly comprising an implant trial at a distal end of the joint preparation tool and an implant trial portion extending proximally from the implant trial, the implant trial comprising a length extending between a proximal end and a distal end of the implant trial; and

a cutting tool configured to releasably couple with the implant trial tool assembly, the cutting tool comprising a cutting element at a distal end of the cutting tool and a cutting tool portion extending proximally from the cutting element, the cutting element comprising a second length extending between a proximal and a distal end, wherein the implant trial tool assembly is configured to guide the cutting tool during step c);

b) delivering at least a portion of the implant trial non-transversely into the sacroiliac joint space; and

c) causing the cutting tool to be actuated relative to the implant trial tool assembly such that the cutting element makes a cut extending into at least one of the sacrum, the ilium or the sacroiliac joint space.

32. The method of claim 31, wherein the cut extends into the sacroiliac joint space and the joint preparation tool further comprises a guide assembly having a guide comprising a first passageway configured to guide the cutting element comprising a drill or mill bit during cutting of the sacroiliac joint space.

33. The method of claim 32, wherein the first passageway is a generally cylindrical bore.

34. The method of claim 33, wherein the cutting element having a longitudinal axis is caused to be coaxially displaced relative to a central axis of the first passageway during a constrained distal-proximal translation.

61

35. The method of claim 34, wherein the constrained distal-proximal translation is such that the longitudinal axis of the cutting element and the central axis of the passageway remain coaxially aligned during step c).

36. The method of claim 34, wherein the constrained distal-proximal translation is such that a stop coupled with the cutting element limits a depth of distal extension of the distal end of the cutting element relative to the implant trial during step c).

37. The method of claim 32, wherein the first passageway comprises a slot-like configuration comprising a slot length extending generally perpendicular to a length of the first passageway.

38. The method of claim 37, wherein prior to step c), the method further comprises orienting the slot length generally parallel with a plane of the sacroiliac joint space.

39. The method of claim 38, wherein the implant trial comprises a first surface extending the length and a second surface opposite the first surface and extending the length, and wherein prior to step c), the method further comprises orienting the implant trial such that the first surface faces a sciatic notch and the slot length extends in a direction generally perpendicular to the second surface thereby permitting preparation along the plane of the sacroiliac joint by directing a motion of the cutting element away from both the second surface and the sciatic notch.

40. The method of claim 32, wherein the guide assembly is configured to releasably and slidably couple with the implant trial tool assembly, and wherein the guide is supported by a guide shaft extending proximally from the guide.

41. The method of claim 31, wherein the cutting tool portion includes a dogleg portion such that the cutting tool portion and the trial portion are offset from each other.

42. The method of claim 31, wherein the cut extends into the sacroiliac joint space and the cutting element comprises a box-chisel configuration.

43. The method of claim 31, wherein the implant trial comprises a first side and a second side opposite the first side each extending the length, and wherein the cutting element includes two T-shaped members, wherein a first T-shaped member is on the first side and a second T-shaped member is on the second side of the implant trial, and during step c) the cutting element makes the cut comprising multiple cuts simultaneously into each of the sacrum and ilium.

44. The method of claim 31, wherein the implant trial further comprises a channel formed in a surface that extends at least a portion of the length of the implant trial, the channel guiding the cutting element during step c).

45. The method of claim 44, wherein the channel is formed in the first top surface of the implant trial, the channel does not extend to and form an opening in the first bottom surface.

46. The method of claim 31, wherein the implant trial comprises a first side and a second side opposite the first side, each of the first and second sides extending the length, and wherein the cutting element includes at least a first member and a second member, wherein the first member is guided along the first side and the second member is guided along the second side of the implant trial, and during step c) the cutting element makes the cut comprising multiple cuts simultaneously into each of the sacrum and ilium.

47. The method of claim 46, wherein each of the first member and second member of the cutting element comprises an implant trial engagement end and a cutting end, the implant trial engagement end includes a neck member that extends to a wide-member that is slidingly and matingly received within a channel formed in the implant trial.

62

48. The method of claim 47, wherein a cutting end of the first member of the cutting element transitions generally ninety degrees from the implant trial engagement end of the first member of the cutting element and extends generally parallel with a first side surface comprising the first side of the implant trial.

49. The method of claim 48, wherein the implant trial comprises a third side and a fourth side opposite the third side each extending the length, the third side extending between a first side edge of the first side and a first side edge of the second side, the fourth side extending between a second side edge of the first side and a second side edge of the second side, wherein the cutting end terminates in a first cutting tip that extends beyond the third surface of the implant trial and a second cutting tip that extends beyond the fourth surface of the implant trial.

50. The method of claim 49, wherein step b) further comprises orienting the implant trial in the sacroiliac joint space such that: the third side of the implant trial faces the sacrum and the fourth side of the implant trial faces the ilium; and, during step c) the cutting element is distally translated to make the cut extending into the sacrum and ilium such that the first cutting tip of each of the first member and second member of the cutting element cuts into the sacrum and the second cutting tip of each of the first member and second member cuts into the ilium.

51. The method of claim 50, wherein step a) further comprises approaching a posterior aspect of the sacroiliac joint space with the joint preparation tool and step b) further comprises delivering the joint preparation tool through an access region defined between a posterior superior iliac spine and a posterior inferior iliac spine.

52. The method of claim 51, further comprising: d) delivering an implant into the sacroiliac joint space.

53. The method of claim 52, wherein at least a portion of the implant occupies a space resulting from the cut extending into at least one of the sacrum or the ilium.

54. The method of claim 53, wherein the at least a portion comprises a keel of the implant.

55. The method of claim 53, wherein the implant comprises:

an intraarticular element extending an implant length between an implant proximal end and an implant distal end, and further extending an implant height between an implant upper edge and an opposed implant lower edge, the intraarticular element comprising a first articular face and a second articular face opposite the first articular face, the first and second articular faces extending the implant height and at least a portion of the implant length;

a graft window formed within at least a portion of the intraarticular element and extending through the intraarticular element from the first articular face to the second articular face; and

at least one keel attached to the intraarticular element along at least a portion of the implant length.

56. The method of claim 55, wherein the at least one keel comprises a first keel extending from the implant proximal end to the implant distal end, wherein the first keel is attached along the implant upper edge or the implant lower edge.

57. The method of claim 56, wherein the at least one keel further comprises a second keel extending from the implant proximal end to the implant distal end, wherein the second keel is attached along the implant upper edge or the implant lower edge opposite to the first keel.

63

58. The method of claim 57, wherein at least one of the intraarticular element and the at least one keel distally tapers into a distal edge of the implant.

59. The method of claim 52, wherein the implant approximates a shape and size of the implant trial.

60. The method of claim 51, wherein each of the first and second cutting tips of each of the first and second members comprises a serrated face having a series of cutting teeth, wherein the serrated face tapers from a proximal end to a distal end of each cutting tip.

61. The method of claim 31, wherein the implant trial further comprises a channel formed in a surface that extends at least a portion of the length of the implant trial, the channel guiding the cutting element in an arcuate path during step c).

62. The method of claim 31, wherein the implant trial portion comprises a first cylindrical shaft, and the cutting tool portion comprises a second cylindrical shaft.

63. The method of claim 31, wherein the implant trial further is configured to be reversibly secured within the sacroiliac joint space by a locking element.

64. The method of claim 63, further comprising fixing the implant trial relative to the sacroiliac joint space via the locking element.

65. The method of claim 63, wherein the implant trial includes at least one passageway which communicates between an inner portion of the implant trial and an outer surface of the implant trial, and wherein the method further comprises securing the implant trial within the sacroiliac joint space via causing an anchoring member to reversibly transition from a recessed condition to a deployed condition, the recessed condition being when the anchoring member is recessed within the passageway and not engaging a bone defining the sacroiliac joint, the deployed condition being when at least a portion of the anchoring member projects out of the passageway from the outer surface of the implant trial and engaging at least one bone defining the sacroiliac joint, the anchoring member configured to limit the movement of the implant trial during step c).

66. The method of claim 63, wherein a proximal surface of the implant trial includes at least one passageway which communicates with a portion of an outer surface of the implant trial, the portion being distal to the proximal surface, the passageway configured to receive an anchoring member comprising the locking element.

67. The method of claim 66, further comprising securing the implant trial within the sacroiliac joint space via the anchoring member by acting upon a proximal end of the anchoring member to reversibly transition the anchoring member from a recessed condition to a deployed condition, the recessed condition being when the anchoring member is recessed within the passageway and not engaging a bone defining the sacroiliac joint, the deployed condition being when a distal end of the anchoring member projects out of the passageway from the portion of the outer surface of the implant trial and engaging at least one bone defining the sacroiliac joint, the anchoring member configured to limit the movement of the implant trial during step c).

68. The method of claim 67, wherein the anchoring member comprises at least one of a spike, pin, dart or screw.

69. The method of claim 31, further comprising: d) delivering an implant into the sacroiliac joint space.

70. The method of claim 69, wherein at least a portion of the implant occupies a space resulting from the cut extending into at least one of the sacrum, the ilium or the sacroiliac joint space.

64

71. The method of claim 70, wherein the at least a portion comprises a keel of the implant.

72. The method of claim 69, wherein the implant approximates a shape and size of the implant trial.

73. The method of claim 23, wherein the implant trial further comprises a first side surface, a second side surface, and a guide wire bore, the first side surface extending between the first top surface and the first bottom surface on a first side of the implant trial, the second side surface extending between the first top surface and the first bottom surface on a second side of the implant trial that is opposite the first side, the guide wire bore extending through the implant trial from the distal to the proximal end and configured to receive and be guided into the sacroiliac joint space by a guide wire.

74. The method of claim 73, wherein the implant trial further comprises a channel formed in the first top surface that extends at least a portion of the first length of the implant trial, the channel comprising a head region and a contracted neck region, wherein the cutting element further comprises a cutting element guide extending at least a portion of the second length, the cutting element guide configured to fit within the head region and the contracted neck region.

75. The method of claim 74, wherein the cutting element guide is configured to be received within the head region and the contracted neck region when the cutting element distally converges with the implant trial such that, once converged, the cutting element is restrained from rotating relative to the implant trial via the cutting element guide fitting within the head region and the contracted neck region.

76. The method of claim 75, wherein the head region includes a cylindrical portion.

77. The method of claim 31, wherein prior to step b), the method further comprises creating a void generally parallel to a plane of the sacroiliac joint, the void generally sized and shaped sufficiently to receive the implant trial during step b).

78. The method of claim 77, wherein creating the void comprises approaching the sacroiliac joint space with: an access cannula having a length and a first jig configured to fit within the access cannula, the first jig configured to guide a second cutting tool therethrough and into the sacroiliac joint space.

79. The method of claim 78, further comprising orienting the access cannula such that the length is generally parallel to a plane of the sacroiliac joint, delivering the second cutting tool through the first jig along the access cannula length and into the sacroiliac joint space.

80. The method of claim 79, further comprising delivering a box osteotome into the sacroiliac joint space.

81. The method of claim 79, further comprising delivering a rasp into the sacroiliac joint space.

82. The method of claim 79, further comprising: d) delivering an implant along the access cannula length and into the sacroiliac joint space.

83. The method of claim 82, wherein the access cannula comprises an exterior surface having a substantially non-circular cross-section perpendicular to the length.

84. The method of claim 83, wherein the exterior surface comprises a pair of planar walls opposite and generally parallel to one another and extending the length, and a pair of curved walls opposite one another and extending the length, wherein each curved wall is positioned between and connected to the pair of planar walls.

85. The method of claim 84, wherein a width separating the pair of planar walls is substantially less than the height separating the pair of curved walls.

65

86. The method of claim 83, wherein the exterior surface comprises a lateral wall opposite a medial wall, each lateral and medial wall extending the length, and a superior wall opposite an inferior wall, each superior and inferior wall extending the length, wherein the lateral and medial walls are separated by a width which is substantially less than a height separating the superior and inferior walls.

87. The method of claim 86, further comprising orienting the access cannula such that the lateral wall faces generally laterally, the medial wall faces generally medially, the inferior wall faces generally caudally and the superior wall faces generally cranially.

88. The method of claim 87, wherein a distal end of the inferior wall is positioned generally adjacent a posterior inferior iliac spine.

89. The method of claim 87, wherein step a) further comprises approaching a posterior aspect of the sacroiliac joint space with the joint preparation tool and step b) further comprises delivering the joint preparation tool through an access region defined between a posterior superior iliac spine and a posterior inferior iliac spine.

90. The method of claim 89, wherein prior to step b), the method further comprises approaching a posterior aspect of the sacroiliac joint space with a guide pin and a joint finder, the joint finder comprising a length between a distal and proximal end and a cannulated body extending between the distal and proximal ends, the cannulated body comprising a flattened end portion alignable with a sacroiliac joint plane and comprising a first planar surface opposite a second planar surface; and,

the method further comprising delivering the guide pin into and along the sacroiliac joint plane and orienting the flattened end portion first planar surface such that it opposes the sacrum and the flattened end portion second planar surface opposes the ilium, and delivering the joint finder over the guide pin being received by the cannulated body and advanced into the sacroiliac joint plane.

91. The method of claim 89, further comprising approaching the sacroiliac joint space with an access cannula having a length, an exterior surface having a substantially non-circular cross-section perpendicular to the length, the exterior surface comprises a lateral wall opposite a medial wall, each lateral and medial wall extending at least a portion of the length, and a superior wall opposite an inferior wall, each superior and inferior wall extending at least a portion of the length, wherein the lateral and medial walls are separated by a width which is substantially less than a height separating the superior and inferior walls, and orienting the access cannula such that i) the length is generally parallel to a plane of the sacroiliac joint, and ii) the lateral wall faces generally laterally, the medial wall faces generally medially, the inferior wall faces generally caudally and the superior wall faces generally cranially.

92. The method of claim 91, wherein the access cannula further comprises a distal projection extending distally off a distal opening of the access cannula from at least one of the superior or inferior walls.

66

93. The method of claim 91, wherein the at least one of the lateral or medial walls extends only a portion of the length while the superior and inferior walls extend the length.

94. The method of claim 91, wherein a distal end of the inferior wall is positioned generally adjacent a posterior inferior iliac spine.

95. The method of claim 89, further comprising: d) delivering an implant into the sacroiliac joint space.

96. The method of claim 95, wherein at least a portion of the implant occupies a space resulting from the cut extending into at least one of the sacrum or the ilium.

97. The method of claim 96, wherein the at least a portion comprises a keel of the implant.

98. The method of claim 95, wherein the implant approximates a shape and size of the implant trial.

99. The method of claim 31, wherein the joint preparation tool further comprises an anchor arm assembly, the method further comprising employing the anchor arm assembly to deliver an anchoring element into the sacrum and the ilium.

100. The method of claim 31, further comprising:

delivering an implant into the sacroiliac joint space;

approaching the sacroiliac joint with a delivery tool comprising an implant arm configured to support the joint implant and an anchor arm assembly comprising an arcuate portion slidable relative to the implant arm and having an anchor guide portion; and

delivering an anchor into at least one of the sacrum or ilium via the anchor guide portion.

101. The method of claim 31, wherein the method further comprises selecting the implant trial from a kit comprising various sizes of implant trials, the implant trial selected based on an implant trail which best fits the joint space.

102. The method of claim 31, wherein the method further comprises selecting the cutting tool from a kit comprising a plurality of cutting tools, the plurality of cutting tools comprising different sized cutting elements; and, repeating step c) more than once using multiple of the plurality of cutting tools.

103. The method of claim 31, wherein the joint preparation tool further comprises an indicator configured to permit a navigation system to provide data related to the position and orientation of the joint preparation tool.

104. The method of claim 103, wherein the navigation system comprises at least one of optical or electromagnetic tracking options.

105. The method of claim 104, wherein the indicator comprises a reference array.

106. The method of claim 105, wherein the indicator comprises a frame coupled to the joint preparation tool.

107. The method of claim 106, wherein the indicator comprises at least three tracking elements supported and connected to one another by the frame in a predetermined spaced apart arrangement.

* * * * *